

STORZ FASTKOBLING MED INDVENDIG GEVIND (FORTSAT)

Vare nummer	Storz type	BSP gevind	b	d	L		
1220M	B/3"	2"	89,0	50,0	38,0		
1221L	B/3"	2 1/2"	89,0	64,5	42,0		DIN 14 308
1221M	B/3"	2 1/2"	89,0	64,5	40,0		DIN 86 205
1223L	B/3"	3"	89,0	64,5	39,0		
1223M	B/3"	3"	89,0	64,5	39,0		
1225L *	B/3"	3"	89,0	64,5	40,0		
1225M *	B/3"	3"	89,0	64,5	40,0		
1230L	A/4"	3 1/2"	115,0	89,5	47,0		
1231L	A/4"	4"	115,0	89,5	47,0		
1231M	A/4"	4"	115,0	89,5	45,0		
1240L	110 mm	4"	133,0	100,0	48,0		
1240M	110 mm	4"	133,0	100,0	45,0		
1241L	110 mm	4 1/2"	133,0	100,0	48,0		
1241M	110 mm	4 1/2"	133,0	100,0	45,0		
1243L	125/5"	5"	148,0	115,0	52,0		
1242L	150/6"	6"	160,0	130,0	96,0		
1245L	205/8"	8"	220,0	186,0	75,0		
1247L	250/10"	10"	278,0	236,0	78,0		

STORZ FASTKOBLING MED INDVENDIG SPECIALGEVIND

Vare nummer	Storz type	Brand-gevind	b	d	L		
1218L	C/2"	2"	66,0	45,0	40,0		
1226L	B/3"	3"	89,0	65,0	40,0		
1227L	B/3"	2"	89,0	45,0	73,0		
Vare nummer	Type	Ålborg gevind	b	d	L		
1228L	B/3"	3"	89,0				
Vare nummer	Type	KV16 gevind	b	d	L		
1229L	B/3"	KV16	89,0				