



Range of Products 2018

FLEX
Das Original

Product features

The key features of our products are identified by the following symbols.



L-BOXX
FLEX transport and organisation system.



Patented guard adjustment
Patented tool-free guard adjustment from both sides (Patent No. DE10115635C1).



Automatic main filter cleaning
Time-controlled filter cleaning. Enables constantly high suction power.



Carrying case
Rugged metal or plastic case.



Spindle lock
Push-button spindle-lock facilitates fast, easy disc change.



Manual main filter cleaning
Manual filter cleaning. Enables constantly high suction power.



Carrying bag
Sturdy, cushioned, robust and light transport bag.



FixTec quick-lock nut
Tool-free disc change.



Container volume
Max. gross filling volume.



Saw blade pendulum action
Pendulum action selectable. Useful for fast sawing in wood.



Bail handle
Additional bail handle for a more comfortable grip.



Dust class L
Classification for dust-removing machines.



Lithium-ion technology
No self-discharge, no memory effect.



Side handgrip
Hand grip optionally on left or right side.



Dust class M
Classification for dust-removing machines.



Mains cable
Cable length



SoftVib hand grip
Vibration cushioning hand grip, preventing strain on the wrists.



Dust class H
Classification for dust-removing machines.



Mains cable
Mains cable PUR



Hook and loop fasteners
Quick grip for attaching abrasives – without adhesives or clamping.



Max. power consumption
ECO – economic, highly efficient fan motor.



Mains cable
Mains cable with flex red plug.



Central water feed
For wet-grinding granite and marble.



Dry suction function
Sucking up non-flammable and non-explosive dust/dirt.



VE electronic control
Continuous speed selection and overload protection.



Quick-fit coupling
Quick-fit brass coupling: for 1/2" water hose



Wet suction function
Sucking up non-flammable and non-toxic liquids.



FR electronic control
Tachogenerator-controlled constant speed, soft-start, overload protection.



GFCI operator protector circuit breaker
Integrated GFCI circuit breaker protection circuit breaker with normal Schuko plug for 230 V sockets.



Connected load
Socket from 100 Watt to ... for connecting power tools.



FV electronic control
Constant speed, soft-start and overload protection.



Control electronics with soft start
Reduced start-up current when the vacuum starts.



Vacuum/Pascal
Details in Pascal.



VV electronic control
Constant speed, soft-start with continuous speed selection trigger and overload protection.



Restart protection
Restart protection after power interruption.



Battery voltage
Details in Volt.



VR electronic control
Tachogenerator-controlled constant speed, soft-start, overload protection, speed selection with optimized low-speed range.



Dust extraction
Extractor connection



Battery voltage
Details in Volt.



Tool-free tool change
Easy tool change without the need for additional tools.



Antistatic equipment
Discharge function prevents static charging.



Guard adjustment
Tool-free guard adjustment from both sides.



Suction hose
Suction hose length.

	Angle grinders / Straight grinders	4
	Accessories for angle grinders / straight grinders	6
	Metal surface finishing	9
	Accessories for metal surface finishing	11
	Saws	18
	Accessories for saws	19
	Cordless tools	21
	Accessories for cordless tools	25
	Giraffe® wall and ceiling sander	27
	Accessories for ceiling and wall finishing	29
	Surface finishing sanding	32
	Accessories for surface finishing sanding	35
	Renovation machines	40
	Accessories for renovation grinder, scoring	44
	Special tools	48
	Accessories for special tools	48
	Rotary hammer drills	49
	Accessories for rotary hammer drills	50
	Safety vacuum cleaner	52
	Accessories for industrial/safety vacuum cleaners	54
	Mixers	59
	Accessories for mixers	61
	Measuring technology/laser	63
	Accessories for laser measuring technology	64
	Polishers	65
	Accessories for polishers	68
	Stone working	70
	Accessories for stone working	72
	Carrying case system L-BOXX®	75

Range of Products 2018

Angle grinders

NEW



L 8-11 115
800 watt angle grinder, 115 mm
Order no. 458.341

Max. disc diameter	115 mm
No load speed	11500 rpm
Power input	800 watt
Power output	460 watt
Tool fixture	M 14
Cable length	4,0 m
Weight	2,0 kg



Standard Equipment:
1 guard grinding 125 Ø (436.852) ·
1 handle (437.921) ·
1 clamping flange (335.282) ·
1 clamping nut M14 (100.080) ·
1 pin wrench (100.110)

NEW



L 8-11 125
800 watt angle grinder, 125 mm
Order no. 458.333

Max. disc diameter	125 mm
No load speed	11500 rpm
Power input	800 watt
Power output	460 watt
Tool fixture	M 14
Cable length	4,0 m
Weight	2,0 kg




Standard Equipment:
1 guard grinding 125 Ø (436.860) ·
1 handle (437.921) ·
1 clamping flange (335.282) ·
1 clamping nut M14 (100.080) ·
1 pin wrench (100.110)



LE 9-11 125
Universal 900 watt angle grinder,
125 mm
Order no. 436.291

Max. disc diameter	125 mm
No load speed	6000-11500 rpm
Power input	900 watt
Power output	600 watt
Tool fixture	M 14
Cable length	4,0 m
Weight	2,0 kg




Standard Equipment:
1 guard grinding 125 Ø (436.860) ·
1 handle (437.921) ·
1 clamping flange (335.282) ·
1 clamping nut M14 (100.080) ·
1 pin wrench (100.110)



LE 9-11 125 L-BOXX
Universal 900 watt angle grinder,
125 mm
Order no. 436.739

Max. disc diameter	125 mm
No load speed	6000-11500 rpm
Power input	900 watt
Power output	600 watt
Tool fixture	M 14
Cable length	4,0 m
Weight	2,0 kg




Standard Equipment:
1 guard grinding 125 Ø (436.860) ·
1 handle (437.921) ·
1 clamping flange (335.282) ·
1 clamping nut M14 (100.080) ·
1 pin wrench (100.110) ·
1 carrying case L-BOXX® 136 (414.085) ·
1 case insert (414.204)

NEW



L 10-11 125
Universal 1050 watt angle grinder,
125 mm
Order no. 447.552

Max. disc diameter	125 mm
No load speed	11500 rpm
Power input	1050 watt
Power output	650 watt
Tool fixture	M 14
Size (L x H)	300 x 105 mm
Cable length	4,0 m
Weight	2,0 kg



Standard Equipment:
1 guard grinding 125 Ø (436.860) ·
1 handle (437.921) ·
1 clamping flange (335.282) ·
1 clamping nut M14 (100.080) ·
1 pin wrench (100.110)



L 1506 VR
1200 watt angle grinder, 125 mm
Order no. 437.972

Max. disc diameter	125 mm
No load speed	2200-6800 rpm
Power input	1200 watt
Power output	700 watt
Tool fixture	M 14
Cable length	4,0 m
Weight (without guard, handle)	1,9 kg



Standard Equipment:
1 side handle (194.034) ·
1 guard grinding 125 Ø (394.394) ·
1 pin wrench (100.110) ·
1 clamping nut M14 (100.080) ·
1 clamping flange (191.612) ·
1 hook and loop backing pad 115 Ø (208.817)


NEW



L 14-11 125
1400 watt angle grinder with superior torque, 125 mm
Order no. 447.560

Max. disc diameter	125 mm
No load speed	11500 rpm
Power input	1400 watt
Power output	880 watt
Tool fixture	M 14
Size (L x H)	310 x 105 mm
Cable length	4,0 m
Weight	2,4 kg

Standard Equipment:
1 guard grinding 125 Ø (436.860) ·
1 SoftVib handle (316.857) ·
1 clamping flange (335.282) ·
1 clamping nut M14 (100.080)



L 3406 VRG
Variable-speed 1400 watt angle grinder, 125 mm
Order no. 406.503

Max. disc diameter	125 mm
Max. polishing pad diameter	160 mm
No load speed	2100-7500 rpm
Power input	1400 watt
Power output	880 watt
Tool fixture	M 14
Cable length	4,0 m
Weight	2,2 kg

Standard Equipment:
1 guard grinding 125 Ø (394.394) ·
1 SoftVib handle (316.857) ·
1 clamping flange (191.612) ·
1 FixTec quick-clamp nut M 14 (313.459)

NEW



LE 14-11 125
Variable-speed 1400 watt angle grinder, 125 mm
Order no. 447.587

Max. disc diameter	125 mm
No load speed	2800-11500 rpm
Power input	1400 watt
Power output	880 watt
Tool fixture	M 14
Size (L x H)	310 x 105 mm
Cable length	4,0 m
Weight	2,4 kg

Standard Equipment:
1 guard grinding 125 Ø (436.860) ·
1 SoftVib handle (316.857) ·
1 clamping flange (335.282) ·
1 clamping nut M14 (100.080)

NEW



L 15-10 150
1500 watt angle grinder, 150 mm
Order no. 447.609

Max. disc diameter	150 mm
No load speed	10000 rpm
Power input	1500 watt
Power output	880 watt
Tool fixture	M 14
Clamping collar Ø	45 mm
Cable length	4,0 m
Weight	3,6 kg

Standard Equipment:
1 guard grinding 150 Ø (461.881) ·
1 handle (461.873) ·
1 clamping flange (335.282) ·
1 clamping nut M14 (100.080) ·
1 pin wrench (100.110)



LE 14-7 125 INOX
1400 watt INOXFLEX, specialist for stainless steels and steel alloys, 125 mm
Order no. 406.546

Max. disc diameter	125 mm
Max. polishing pad diameter	160 mm
No load speed	2100-7500 rpm
Power input	1400 watt
Power output	880 watt
Tool fixture	M 14
Cable length	4,0 m
Weight	2,4 kg

Standard Equipment:
1 guard grinding 125 Ø (394.394) ·
1 SoftVib handle (325.376) ·
1 clamping flange (191.612) ·
1 FixTec quick-clamp nut M 14 (313.459)



L 21-8 180
2100 watt angle grinder, 180 mm
Order no. 392.782

Max. disc diameter	180 mm
No load speed	8300 rpm
Power input	2100 watt
Power output	1250 watt
Tool fixture	M 14
Clamping collar Ø	64 mm
Weight	4,7 kg

Standard Equipment:
1 guard grinding 180 Ø (416.517) ·
1 SoftVib handle (325.384) ·
1 pin wrench BL 5 (100.110) ·
1 clamping flange (338.753) ·
1 clamping nut M14 (100.080)

Range of Products 2018



L 21-6 230
2100 watt angle grinder, 230 mm
Order no. 391.514

Max. disc diameter 230 mm
No load speed 6500 rpm
Power input 2100 watt
Power output 1250 watt
Tool fixture M 14
Clamping collar Ø 64 mm
Cable length 4,0 m
Weight 4,9 kg



Standard Equipment:
1 guard grinding 230 Ø (338.729) ·
1 SoftVib handle (325.384) ·
1 pin wrench BL 5 (100.110) ·
1 clamping flange (338.753) ·
1 clamping nut M14 (100.080)



L 24-6 230
2400 watt angle grinder, 230 mm
Order no. 391.522

Max. disc diameter 230 mm
No load speed 6500 rpm
Power input 2400 watt
Power output 1450 watt
Tool fixture M 14
Clamping collar Ø 64 mm
Cable length 4,0 m
Weight 5,8 kg



Standard Equipment:
1 guard grinding 230 Ø (338.729) ·
1 SoftVib handle (325.384) ·
1 pin wrench BL 5 (100.110) ·
1 clamping flange (338.753) ·
1 clamping nut M14 (100.080) ·
1 hexagon socket wrench, SW 6 (104.167)



L 26-6 230
2600 watt angle grinder T-Rex with
enormous reserves of power, 230 mm
Order no. 436.704

Max. disc diameter 230 mm
No load speed 6500 rpm
Power input 2600 watt
Power output 1800 watt
Tool fixture M 14
Clamping collar Ø 64 mm
Cable length 4,0 m
Weight 6,35 kg



Standard Equipment:
1 guard grinding 230 Ø (338.729) ·
1 SoftVib handle (325.384) ·
1 pin wrench BL 5 (100.110) ·
1 clamping flange (338.753) ·
1 hexagon socket wrench, SW 6 (104.167) ·
1 SDS-Clc quick-clamp nut M 14 (253.049)

Straight grinders



H 1105 VE
710 watt low-speed straight grinder
Order no. 269.956

Max. disc diameter resin/
ceramic up to 30 mm
Max. disc diameter fiber
reinforced up to 50 mm
Tool fixture Ø 3, 6, 8 mm, 1/4"
No load speed 2500-6500 rpm
Power input 710 watt
Power output 420 watt
Cable length 4,0 m
Weight 2,1 kg



Standard Equipment:
1 collet 6 mm Ø with clamping nut (228.656) ·
1 stopping claw SW 14 (254.917) ·
1 open-ended wrench SW 19 (104.914)



H 1127 VE
710 watt variable high-speed straight
grinder
Order no. 270.067


Max. disc diameter resin/
ceramic up to 30 mm
Max. disc diameter fiber
reinforced up to 50 mm
Tool fixture Ø 3, 6, 8 mm, 1/4"
No load speed 10000-30000 rpm
Power input 710 watt
Power output 420 watt
Cable length 4,0 m
Weight 1,8 kg



Standard Equipment:
1 collet 6 mm Ø with clamping nut (228.656) ·
1 stopping claw SW 14 (254.917) ·
1 open-ended wrench SW 19 (104.914)

Accessories for angle grinders

Guards



Cutting guard

Designation	Diameter in mm	QTY/ PKG	Order no.		
GU-C D125 48/C2	125	1	437.069		
GU-C D125 48/C	125	1	409.774		
GU-C D230 64/C L21-6/L24-6	230	1	389.625		

Extractor hoods



Dust extraction guard

Designation	Diameter in mm	QTY/ PKG	Order no.		
DE AG D125 Set	125	1	445.479		
DE AG D230 Set	230	1	445.487		



Disc guard cover

Designation	Diameter in mm	QTY/ PKG	Order no.		
GU-AD D125	125	1	446.041		
GU-AD D150	150	1	454.087		
GU-AD D180	180	1	446.718		
GU-AD D230	230	1	446.068		



Disc guard with removable edge segment

Designation	Dimensions in mm	QTY/ PKG	Order no.		
SG-R D125	125 Ø	1	452.572		



Brush ring

Designation	Dimensions in mm	QTY/ PKG	Order no.		
Brush ring SG-RD 125	125 Ø	1	454.656		

Cutting discs



Diamantjet - diamond cutting disc, standard, concrete

Dimensions in mm	QTY/ PKG	Order no.		
125 Ø x 22,2	1	349.046		
230 Ø x 22,2	1	349.054		



Diamantjet - diamond cutting disc, premium, tile

Dimensions in mm	QTY/ PKG	Order no.		
115 Ø x 22,2	1	349.011		
125 Ø x 22,2	1	349.038		

Flap discs



Flap disc for metal and stainless steel, cambered

Dimensions in mm	Grit	QTY/ PKG	Order no.		
125 Ø x 22,2	P 60	10	349.925		
125 Ø x 22,2	P 80	10	349.933		



SC-VL polishing flap wheel for metal and stainless steel, cambered


Dimensions in mm	Grit	QTY/ PKG	Order no.		
125 Ø x 22,2	medium	5	358.606		

Velcro system for LE 14-11 125, L 3406 VRG, LE 14-7 125 INOX, L 1506 VR



Velcro backing M 14

Dimensions in mm	QTY/ PKG	Order no.		
115 Ø	1	208.817		
125 Ø	1	231.983		



Velcro pad, cushioned M 14

Designation	Dimensions in mm	QTY/ PKG	Order no.		
BP-M D115 M14	115 Ø	1	240.311		
BP-M D125 M14	125 Ø	1	350.737		



Velcro sanding paper PURFLEX

Designation	Dimensions in mm	Grit	QTY/ PKG	Order no.		
D115 PU-P24 VE25	115 Ø	P 24	25	381.195		
D115 PU-P40 VE50	115 Ø	P 40	50	381.209		
D115 PU-P60 VE50	115 Ø	P 60	50	381.217		
D115 PU-P80 VE50	115 Ø	P 80	50	381.225		
D115 PU-P100 VE50	115 Ø	P 100	50	381.233		
D115 PU-P120 VE50	115 Ø	P 120	50	381.241		
D115 PU-P150 VE50	115 Ø	P 150	50	381.268		
D115 PU-P180 VE50	115 Ø	P 180	50	381.276		



Velcro sanding paper ZIRCOFLEX

Designation	Dimensions in mm	Grit	QTY/ PKG	Order no.		
D125-8 ZI-A40 VE25	125 Ø	A 40	25	393.185		
D125-8 ZI-A60 VE25	125 Ø	A 60	25	393.193		
D125-8 ZI-A80 VE25	125 Ø	A 80	25	393.207		

Range of Products 2018



Velcro sanding paper CERAFLEX

Designation	Dimensions in mm	Grit	QTY/ PKG	Order no.		
D125 CE-K80 VE50	125 Ø	K 80	50	393.215		
D125 CE-K120 VE50	125 Ø	K 120	50	393.223		
D125 CE-K180 VE50	125 Ø	K 180	50	393.231		



Natural fibre felt pad

Designation	Dimensions in mm	Type	QTY/ PKG	Order no.		
FP D125 S VE5	125 Ø	soft	5	393.355		
FP D125 H VE5	125 Ø	hard	5	393.347		

Brush for LE 14-11 125



Brush, steel wire 0,3 mm

Dimensions in mm	QTY/ PKG	Order no.		
60 Ø	1	124.516		



Brush, steel wire 0,5 mm

Dimensions in mm	QTY/ PKG	Order no.		
65 Ø	1	124.524		

Quick-clamp nut



FixTec quick clamp nut M 14

QTY/ PKG	Order no.		
1	313.459		



SDS-Clic quick-clamp nut

QTY/ PKG	Order no.		
1	253.049		

Side handles



SoftVib side handle

Designation	Type	QTY/ PKG	Order no.		
GS-M M8 SV/S	M 8	1	316.857		



SoftVib side handle

Designation	Type	QTY/ PKG	Order no.		
GS-M M8 SV	M 8	1	325.376		
GS-M M14 SV	M 14	1	325.384		



Side handgrip

Designation	Type	QTY/ PKG	Order no.		
GS-K/II M8	M 8	1	437.921		



Side handgrip

Designation	Type	QTY/ PKG	Order no.		
GS-K M10	M 10	1	461.873		

Carrying case



Carrying case L-BOXX®

Designation	External dimensions L x W x H	Internal dimensions L x W x H	Weight	QTY/ PKG	Order no.		
TK-L 136	442 x 357 x 151 mm	378 x 311 x 107 mm	2,2 kg	1	414.085		

Case insert

Designation	QTY/ PKG	Order no.		
TKE 1 HD	1	414.204		



Carrying case

Designation	Weight	QTY/ PKG	Order no.		
TK-S L230/LD180/LD150	4,0 kg	1	444.391		

Accessories for straight grinders

Collets for H 1105 VE and H 1127 VE




Collet

Dimensions in mm	QTY/ PKG	Order no.		
3 Ø	1	229.741		
1/4" Ø	1	229.776		
6 Ø	1	228.656		
8 Ø	1	229.768		

Metal surface finishing

NEW



BME 8-4
TRINOXFLEX basic motor
Order no. 459.305

Power input	800 watt
Power output	325 watt
Tool width	50 mm
Tool fixture	Quick-fit coupling
No load speed	1330-4000 rpm
Cable length	4,0 m
Weight	1,9 kg

NEW



BRE 8-4 INOX Set
Pipe belt sander and belt file
TRINOXFLEX Set
Order no. 453.463

Power input	800 watt
Power output	325 watt
Belt speed	2,8-8,4 m/sec
Belt dimensions	533 x 4 / 20 / 30 mm
Pipe Ø max.	50 mm
No load speed	1330-4000 rpm
Cable length	4,0 m
Weight	2,7 kg

Standard Equipment:
1 sanding attachment, pipe belt BR 50 (459.585) ·
1 sanding attachment belt file BF 140 (459.593) ·
1 replacement roller set BR 30 Set (459.607) ·
2 sanding belts ZIRCOFLEX, P 60, 9 mm (2 pieces of 257.105) ·
2 sanding belts ZIRCOFLEX, P 120, 9 mm (2 pieces of 257.102) ·
1 carrying case L-BOXX® 136 (414.085) ·
1 case insert (457.337)

NEW




BSE 8-4 50
Burnishing machine TRINOXFLEX
Order no. 453.404

Power input	800 watt
Power output	325 watt
Max. tool Ø	125 mm
Tool width	50 mm
Tool fixture	19 mm
No load speed	1330-4000 rpm
Cable length	4,0 m
Weight	2,4 kg

Standard Equipment:
1 sanding attachment for burnishing BS 50 (459.577)

NEW



FBE 8-4 140
Belt file TRINOXFLEX
Order no. 453.455

Power input	800 watt
Power output	325 watt
Belt speed	2,8-8,4 m/sec
Belt dimensions	533 x 4-9 / 4-30 mm
Cable length	4,0 m
Weight	2,5 kg

Standard Equipment:
1 sanding attachment belt file BF 140 (459.593) ·
2 sanding belts ZIRCOFLEX P 60, 4 mm (2 pieces of 303.615) ·
2 sanding belts ZIRCOFLEX, P 120, 4 mm (2 pieces of 303.623) ·
2 sanding belts ZIRCOFLEX, P 60, 9 mm (2 pieces of 257.105) ·
2 sanding belts ZIRCOFLEX, P 120, 9 mm (2 pieces of 257.102) ·
2 sanding belts ZIRCOFLEX, P 60, 30 mm (2 pieces of 255.328) ·
2 sanding belts ZIRCOFLEX, P 120, 30 mm (2 pieces of 255.329) ·
1 sanding belt MESHFLEX A 240, 9 mm (1 piece of 318.663) ·
1 sanding belt MESHFLEX A 240, 30 mm (1 piece of 318.647) ·
1 side handle (194.034) ·
1 hexagon socket wrench, SW 5 (115.460) ·
1 carrying case L-BOXX® 136 (414.085) ·
1 case insert (457.337)

NEW



BRE 8-4 9
Pipe belt sander TRINOXFLEX Set
Order no. 453.420

Power input	800 watt
Power output	325 watt
Belt speed	2,8-8,4 m/sec
Belt dimensions	533 x 4 / 20 / 30 mm
Pipe Ø max.	50 mm
No load speed	1330-4000 rpm
Cable length	4,0 m
Weight	2,7 kg

Standard Equipment:
1 sanding attachment, pipe belt BR 50 (459.585) ·
2 sanding belts ZIRCOFLEX, P 60, 9 mm (2 pieces of 257.105) ·
2 sanding belts ZIRCOFLEX, P 120, 9 mm (2 pieces of 257.102) ·
1 carrying case L-BOXX® 136 (414.085) ·
1 case insert (457.337)

Range of Products 2018



BME 14-3 L
TRINOXFLEX basic motor
Order no. 433.403

Power input	1400 watt
Power output	880 watt
Max. tool Ø	125 mm
Tool width	100 mm
Tool fixture	Quick-fit coupling
No load speed	1000-3500 rpm
Cable length	4,0 m
Weight	2,1 kg



BSE 14-3 100
Burnishing machine TRINOXFLEX
Order no. 433.411

Power input	1400 watt
Power output	880 watt
Max. tool Ø	125 mm
Tool width	100 mm
Tool fixture	19 mm
No load speed	1000-3500 rpm
Cable length	4,0 m
Weight	2,9 kg



Standard Equipment:
1 sanding attachment for burnishing
BS 100 (433.462)



BRE 14-3 125 Set
Pipe belt sander TRINOXFLEX Set
Order no. 433.446

Power input	1400 watt
Power output	880 watt
Belt speed	3,5-10 m/sec
Belt dimensions	760 x 40 mm
Pipe Ø max.	125 mm
No load speed	1000-3500 rpm
Cable length	4,0 m
Weight	3,6 kg



Standard Equipment:
1 sanding attachment, pipe belt BR 125 (433.470) ·
1 sanding-polishing belt S 600 (326.917) ·
1 superfinishing band S 1500 (326.933) ·
1 sanding belt MESHFLEX A 240 (1 piece of 326.879) ·
1 sanding belt MESHFLEX A 400 (1 piece of 326.852) ·
5 sanding belts CORUFLEX P 80 (5 pieces of 326.739) ·
5 sanding belts CORUFLEX P 120 (5 pieces of 326.755) ·
5 sanding belts CORUFLEX P 220 (5 pieces of 326.771) ·
1 carrying case L-BOXX® 238 (414.093) ·
1 case insert (433.918)



BSE 14-3 100 Set
Burnishing machine TRINOXFLEX Set
Order no. 433.438

Power input	1400 watt
Power output	880 watt
Max. tool Ø	125 mm
Tool width	100 mm
Tool fixture	19 mm
No load speed	1000-3500 rpm
Cable length	4,0 m
Weight	2,9 kg




Standard Equipment:
1 sanding attachment for burnishing
BS 100 (433.462) ·
1 rubber air roller (433.896) ·
1 air pump (256.284) ·
1 fleece A 280/fine (256.975) ·
1 sanding-polishing sleeve, S 600 (436.429) ·
1 sanding-polishing sleeve, S 1500 (436.437) ·
1 MESHFLEX sanding sleeve A 400 (434.612) ·
3 ZIRCOFLEX sanding sleeves P 80 (3 pieces of 434.515) ·
3 ZIRCOFLEX sanding sleeves P 120 (3 pieces of 434.523) ·
3 CERAFLEX sanding sleeves K 120 (3 pieces of 434.566) ·
3 CORUFLEX sanding sleeves P 180 (3 pieces of 434.574) ·
1 carrying case L-BOXX® 238 (414.093) ·
1 case insert (433.918)



BSE 14-3 INOX Set
Burnishing machine and pipe belt sander TRINOXFLEX Set
Order no. 433.454

Power input	1400 watt
Power output	880 watt
Max. tool Ø	125 mm
Tool width	100 mm
Tool fixture	19 mm
Belt speed	3,5-10 m/sec
Belt dimensions	760 x 40 mm
Pipe Ø max.	125 mm
No load speed	1000-3500 rpm
Cable length	4,0 m
Weight	3,6 kg




Standard Equipment:
1 sanding attachment, pipe belt BR 125 (433.470) ·
1 sanding attachment for burnishing
BS 100 (433.462) ·
1 rubber air roller (433.896) ·
1 air pump (256.284) ·
1 sanding-polishing belt S 600 (326.917) ·
1 superfinishing band S 1500 (326.933) ·
1 sanding belt MESHFLEX A 240 (1 piece of 326.879) ·
1 sanding belt MESHFLEX A 400 (1 piece of 326.852) ·
5 sanding belts CORUFLEX P 80 (5 pieces of 326.739) ·
5 sanding belts CORUFLEX P 120 (5 pieces of 326.755) ·
5 sanding belts CORUFLEX P 220 (5 pieces of 326.771) ·
1 carrying case L-BOXX® 238 (414.093) ·
1 case insert (433.918)



LBR 1506 VRA
1200 watt weld and pipe belt sander
Order no. 282.499

Power input 1200 watt
Power output 700 watt
Belt speed 10-30 m/sec
Belt dimensions 618 x 40 mm
Cable length 4,0 m
Weight 4,2 kg




Standard Equipment:
1 side handle (252.721) ·
1 sanding belt ZIRCOFLEX P 60
(1 piece of 445.061) ·
1 sanding belt ZIRCOFLEX P 120
(1 piece of 266.132) ·
1 sanding belt MESHFLEX A 240
(1 piece of 317.977) ·
1 hexagon socket wrench, SW 5
(115.460) ·
1 hexagon socket wrench, SW 6
(104.167) ·
1 hexagon socket wrench, SW 3 (178.772)



LLK 1503 VR
Fillet weld grinder
Order no. 315.257

Power input 1200 watt
Power output 700 watt
Max. disc diameter 152 mm
No load speed 1500-4700 rpm
Cable length 4,0 m
Weight 3,4 kg




Standard Equipment:
1 profiling stone (315.494) ·
1 FixTec quick-clamp nut M 14 (313.459) ·
1 compact grinding disc, 3 mm, soft
(313.416) ·
1 compact grinding disc, 3 mm, hard
(313.424) ·
1 compact grinding disc, 6 mm, soft
(313.432) ·
1 compact grinding disc, 6 mm, hard
(313.440) ·
1 carrying case L-BOXX® 238 (414.093) ·
1 case insert (436.658)



ST 1005 VE
Finger sander
Order no. 259.540

Power input 400 watt
Power output 220 watt
Sanding medium 39 x 60 mm
Orbit 8 mm
Orbit rate, no load 1200-4500 opm
Cable length 4,0 m
Weight 2,2 kg



Standard Equipment:
2 polishing shoes with velcro polishing
cushion (1 set) ·
10 velcro sand papers, P 60 (258.299) ·
10 velcro sand papers, P 120 (258.300) ·
10 velcro sand papers, P 180 (258.301) ·
10 velcro fleece, A 240, 39 x 60 mm
(258.302) ·
1 hexagon socket wrench, SW 3 (217.794)

Accessories for metal surface finishing

Accessories INOXFLEX LE 14-7 125



Thin cutting disc for stainless steel

Dimensions in mm	QTY/ PKG	Order no.		
125 Ø x 1 x 22,2	10	349.836		



Flap disc for metal and stainless steel, cambered

Dimensions in mm	Grit	QTY/ PKG	Order no.		
125 Ø x 22,2	P 60	10	349.925		
125 Ø x 22,2	P 80	10	349.933		



SC-VL polishing flap wheel for metal and stainless
steel, cambered

Dimensions in mm	Grit	QTY/ PKG	Order no.		
125 Ø x 22,2	medium	5	358.606		



Fillet disc

Dimensions in mm	Grit	QTY/ PKG	Order no.		
125 Ø x 6 x 22,2	6 A medium	10	358.711		
125 Ø x 6 x 22,2	3 S fine	10	358.703		



Grinding disc PYRAFLEX

Designation	Dimensions in mm	Grit	QTY/ PKG	Order no.		
D125 PY-A30 VE10	125 Ø	A 30 (K 600)	10	358.819		
D125 PY-A45 VE10	125 Ø	A 45 (K 400)	10	358.800		
D125 PY-A65 VE10	125 Ø	A 65 (K 280)	10	358.797		
D125 PY-A160 VE10	125 Ø	A 160 (K 120)	10	364.592		



SC-Fleece velcro backed disc

Designation	Dimensions in mm	Grit	QTY/ PKG	Order no.		
D125 SC-C VE10	125 Ø	coarse	10	358.614		
D125 SC-M VE10	125 Ø	medium	10	358.622		
D125 SC-VF VE10	125 Ø	very fine	10	358.630		

Range of Products 2018




Superfinishing pad

Designation	Dimensions in mm	Grit	QTY/ PKG	Order no.		
D125 SU-S600	125 Ø	S 600	1	318.191		
D125 SU-S1500	125 Ø	S 1500	1	318.205		
D125 SU-S2500	125 Ø	S 2500	1	320.234		




Natural fibre felt pad

Designation	Dimensions in mm	Type	QTY/ PKG	Order no.		
FP D125 H VE5	125 Ø	hard	5	393.347		
FP D125 S VE5	125 Ø	soft	5	393.355		



Polishing paste Poli white

Weight in kg	QTY/ PKG	Order no.		
0,7	1	255.004		




Polishing paste Poli blue

Weight in kg	QTY/ PKG	Order no.		
0,7	1	255.005		



Polishing cream Poli creme

Weight in kg	QTY/ PKG	Order no.		
1	1	255.006		



Poli set mini white/blue/creme

Designation	Weight in kg	QTY/ PKG	Order no.		
PP-W/B/C	3 x 0,1	1 set	365.041		



Velcro backing pad

Designation	Dimensions in mm	QTY/ PKG	Order no.		
SP D125-8 H/F	125 Ø	1	391.727		



Velcro backing pad „Hook“

Dimensions in mm	Type	QTY/ PKG	Order no.		
125 Ø x M 14	Velcro hook	1	364.584		



FixTec quick clamp nut M 14

QTY/ PKG	Order no.		
1	313.459		



Carrying case

Designation	Size (W x L x H)	QTY/ PKG	Order no.		
TK-L 530x375x130	530 x 375 x 130 mm	1	367.192		

Case insert

Designation	QTY/ PKG	Order no.		
TKE LE14-7 INOX	1	367.206		

Accessories TRINOXFLEX BSE/BRE 14-3



Sanding attachment, burnishing

Designation	QTY/ PKG	Order no.		
BS 100	1	433.462		



Sanding attachment, pipe belt

Designation	QTY/ PKG	Order no.		
BR 125	1	433.470		



Dust extraction guard

Designation	QTY/ PKG	Order no.		
BG D 110	1	461.547		



Rubber air roller

Designation	Dimensions in mm	QTY/ PKG	Order no.		
AS 100x100	100 Ø x 100	1	433.896		
AS 90x100	90 Ø x 100	1	256.415		



Air pump

Designation	Dimensions in mm	QTY/ PKG	Order no.		
		1	256.284		



Sanding attachment, pipe belt

Designation	QTY/ PKG	Order no.		
BR 50	1	459.585		



Expansion roller

Designation	Dimensions in mm	QTY/ PKG	Order no.		
ES 100x100	100 Ø x 100	1	433.926		



Interchangeable roller set

Designation	QTY/ PKG	Order no.		
BR 9 set	1	459.615		



Drive roller

Designation	Dimensions in mm	QTY/ PKG	Order no.		
RA 60x100	60 Ø x 100	1	255.731		



Interchangeable roller set

Designation	QTY/ PKG	Order no.		
BR 30 Set	1	459.607		



Drive roller

Designation	Dimensions in mm	QTY/ PKG	Order no.		
RA 62x70 INOX	62 Ø x 70	1	303.054		



Sanding attachment belt file

Designation	QTY/ PKG	Order no.		
BF 140	1	459.593		



Distance ring set

Designation	QTY/ PKG	Order no.		
	6	250.522		



INOX Clean spray

Contents	QTY/ PKG	Order no.		
400 ml	1	298.301		



Poli-clean

Dimensions in mm	Grit	QTY/ PKG	Order no.		
100 Ø x 100	extra coarse	1	257.375		



Flap wheel sanding

Dimensions in mm	Grit	QTY/ PKG	Order no.		
100 Ø x 50	P 40	1	250.496		
100 Ø x 50	P 60	1	250.498		
100 Ø x 50	P 80	1	250.499		
100 Ø x 50	P 120	1	250.501		
100 Ø x 50	P 180	1	250.504		
100 Ø x 50	P 240	1	250.505		
100 Ø x 100	P 40	1	358.827		
100 Ø x 100	P 60	1	358.835		
100 Ø x 100	P 80	1	358.843		
100 Ø x 100	P 120	1	358.851		
100 Ø x 100	P 180	1	358.878		
100 Ø x 100	P 240	1	358.886		

Accessories TRINOXFLEX BSE/BRE 14-3, 8-4



Sanding attachment, burnishing

Designation	Width	QTY/ PKG	Order no.		
BS 50	50 mm	1	459.577		

Range of Products 2018



Sanding fleece top

Dimensions in mm	Grit	QTY/ PKG	Order no.		
100 Ø x 100	A 80 (coarse)	1	377.910		
100 Ø x 100	A 180 (medium)	1	377.929		
100 Ø x 100	A 280 (fine)	1	377.937		



Stainless steel wire brush

Dimensions in mm	QTY/ PKG	Order no.		
100 Ø x 70	1	251.625		



Sanding fleece

Dimensions in mm	Grit	QTY/ PKG	Order no.		
100 Ø x 50	A 80 (coarse)	1	250.509		
100 Ø x 50	A 160 (medium)	1	250.510		
100 Ø x 50	A 280 (fine)	1	250.512		
100 Ø x 50	A 400 (very fine)	1	250.513		
100 Ø x 100	A 80 (coarse)	1	256.973		
100 Ø x 100	A 160 (medium)	1	256.974		
100 Ø x 100	A 280 (fine)	1	256.975		
100 Ø x 100	A 400 (very fine)	1	256.976		



Stranded wire brushes

Dimensions in mm	QTY/ PKG	Order no.		
100 Ø x 70	1	251.626		



Polishing felt

Dimensions in mm	QTY/ PKG	Order no.		
100 Ø x 50	1	257.374		



Sanding fleece flap

Dimensions in mm	Grit	QTY/ PKG	Order no.		
100 Ø x 50	P 80/A 160	1	250.515		
100 Ø x 50	P 150/A 280	1	250.516		
100 Ø x 50	P 240/A 280	1	358.894		
100 Ø x 100	P 80/A 160	1	256.977		
100 Ø x 100	P 150/A 280	1	256.978		
100 Ø x 100	P 240/A 280	1	358.908		



Cotton buffing wheel

Dimensions in mm	QTY/ PKG	Order no.		
100 Ø x 10	8	317.950		



Grinding fleece, folded

Dimensions in mm	Grit	QTY/ PKG	Order no.		
100 Ø x 100	A 100	1	347.272		
100 Ø x 100	A 180	1	347.280		
100 Ø x 100	A 280	1	347.299		



Sanding-polishing sleeve

Designation	Dimensions in mm	Grit	QTY/ PKG	Order no.		
90x100 SU-S600	90 Ø x 100	S 600	1	318.175		
90x100 SU-S1500	90 Ø x 100	S 1500	1	318.183		
100x100 SU-S600	100 Ø x 100	S 600	1	436.429		
100x100 SU-S1500	100 Ø x 100	S 1500	1	436.437		



Fine polishing roller

Designation	Dimensions in mm	Grit	QTY/ PKG	Order no.		
Fine polishing roller K60 D100x50	100 Ø x 50	K 60	1	250.525		
Fine polishing roller K180 D100x50	100 Ø x 50	K 180	1	250.526		



Sanding sleeve ZIRCOFLEX

Designation	Dimensions in mm	Grit	QTY/ PKG	Order no.		
90x100 ZI-P60 VE5	90 Ø x 100	P 60	5	256.285		
90x100 ZI-P100 VE5	90 Ø x 100	P 100	5	256.286		
90x100 ZI-P180 VE5	90 Ø x 100	P 180	5	256.287		
100x100 ZI-P60 VE5	100 Ø x 100	P 60	5	434.507		
100x100 ZI-P80 VE5	100 Ø x 100	P 80	5	434.515		
100x100 ZI-P120 VE5	100 Ø x 100	P 120	5	434.523		



Nylon brushes

Dimensions in mm	Grit	QTY/ PKG	Order no.		
100 Ø x 70	S 80	1	251.624		



Sanding sleeve CERAFLEX

Designation	Dimensions in mm	Grit	QTY/ PKG	Order no.		
100x100 CE-K60 VE5	100 Ø x 100	60	5	434.531		
100x100 CE-K80 VE5	100 Ø x 100	80	5	434.558		
100x100 CE-K120 VE5	100 Ø x 100	120	5	434.566		



Sanding sleeve CORUFLEX

Designation	Dimensions in mm	Grit	QTY/ PKG	Order no.		
100x100 CR-P180 VE5	100 Ø x 100	P 180	5	434.574		
100x100 CR-P240 VE5	100 Ø x 100	P 240	5	434.582		



Sanding belt ZIRCOFLEX

Designation	Dimensions in mm	Grit	QTY/ PKG	Order no.		
760x40 ZI-P36 VE10	760 x 40	P 36	10	438.464		
760x40 ZI-P40 VE10	760 x 40	P 40	10	438.472		
760x40 ZI-P60 VE10	760 x 40	P 60	10	438.480		
760x40 ZI-P80 VE10	760 x 40	P 80	10	438.499		
760x40 ZI-P120 VE10	760 x 40	P 120	10	438.502		



Sanding sleeve MESHFLEX

Designation	Dimensions in mm	Grit	QTY/ PKG	Order no.		
90x100 ME-A100	90 Ø x 100	A 100	1	256.288		
90x100 ME-A240	90 Ø x 100	A 240	1	256.289		
90x100 ME-A400	90 Ø x 100	A 400	1	256.290		
100x100 ME-A100	100 Ø x 100	A 100	1	434.590		
100x100 ME-A240	100 Ø x 100	A 240	1	434.604		
100x100 ME-A400	100 Ø x 100	A 400	1	434.612		



Sanding belt CERAFLEX

Designation	Dimensions in mm	Grit	QTY/ PKG	Order no.		
760x40 CE-K60 VE10	760 x 40	60	10	438.510		
760x40 CE-K80 VE10	760 x 40	80	10	438.529		
760x40 CE-K120 VE10	760 x 40	120	10	438.537		



Velcro sanding belt

Dimensions in mm	Grit	QTY/ PKG	Order no.		
600 x 40	P 60	10	284.718		
600 x 40	P 120	10	284.726		



Sanding belt CORUFLEX

Designation	Dimensions in mm	Grit	QTY/ PKG	Order no.		
760x40 CR-P80 VE10	760 x 40	P 80	10	326.739		
760x40 CR-P120 VE10	760 x 40	P 120	10	326.755		
760x40 CR-P180 VE10	760 x 40	P 180	10	434.906		
760x40 CR-P240 VE10	760 x 40	P 240	10	434.914		



Velcro fleece

Dimensions in mm	Grit	QTY/ PKG	Order no.		
600 x 40	A 100	2	281.069		
600 x 40	A 180	2	281.077		
600 x 40	S 400	2	281.085		



Sanding belt MESHFLEX

Designation	Dimensions in mm	Grit	QTY/ PKG	Order no.		
760x40 ME-A100 VE3	760 x 40	A 100	3	326.895		
760x40 ME-A240 VE3	760 x 40	A 240	3	326.879		
760x40 ME-A400 VE3	760 x 40	A 400	3	326.852		



Superfinishing band

Dimensions in mm	Grit	QTY/ PKG	Order no.		
600 x 40	S 1500	2	318.736		



Superfinishing band

Designation	Dimensions in mm	Grit	QTY/ PKG	Order no.		
760x40 SU-S600	760 x 40	S 600	1	326.917		
760x40 SU-S1500	760 x 40	S 1500	1	326.933		



Velcro drive belt, blue

Dimensions in mm	QTY/ PKG	Order no.		
700 x 30	2	281.050		



Carrying case L-BOXX®

Designation	External dimensions L x W x H	Internal dimensions L x W x H	Weight	QTY/ PKG	Order no.		
TK-L 136	442 x 357 x 151 mm	378 x 311 x 107 mm	2,2 kg	1	414.085		
TK-L 238	442 x 357 x 253 mm	378 x 306 x 209 mm	2,8 kg	1	414.093		



Adhesive tape for sanding belt

Dimensions in mm	QTY/ PKG	Order no.		
40 x 5000	1	251.838		

Range of Products 2018

Case insert



Designation	QTY/ PKG	Order no.		
TKE BRE 8-4/ FBE 8-4	1	457.337		
TKE BSE/BRE14-3	1	433.918		

Accessories FBE 8-4 140



Sanding arm, 9 mm, pointed

Dimension of roller in mm	QTY/ PKG	Order no.		
25 Ø x 9	1	256.525		



Sanding arm, 9 mm, cambered

Dimension of roller in mm	QTY/ PKG	Order no.		
25 Ø x 9	1	256.532		



Sanding arm, 30 mm, small roller

Dimension of roller in mm	QTY/ PKG	Order no.		
20 Ø x 30	1	255.282		



Sanding arm, 30 mm, large roller

Dimension of roller in mm	QTY/ PKG	Order no.		
30 Ø x 30	1	258.888		



Sanding belt ZIRCOFLEX

Designation	Dimensions in mm	Grit	QTY/ PKG	Order no.		
533x4 ZI-P60 VE10	533 x 4	P 60	10	303.615		
533x4 ZI-P80 VE10	533 x 4	P 80	10	434.620		
533x4 ZI-P120 VE10	533 x 4	P 120	10	303.623		
533x9 ZI-P40 VE10	533 x 9	P 40	10	257.101		
533x9 ZI-P60 VE10	533 x 9	P 60	10	257.105		
533x9 ZI-P80 VE10	533 x 9	P 80	10	434.639		
533x9 ZI-P120 VE10	533 x 9	P 120	10	257.102		
533x30 ZI-P40 VE10	533 x 30	P 40	10	256.538		
533x30 ZI-P60 VE10	533 x 30	P 60	10	255.328		
533x30 ZI-P80 VE10	533 x 30	P 80	10	434.647		
533x30 ZI-P120 VE10	533 x 30	P 120	10	255.329		

Sanding belt CERAFLEX

Designation	Dimensions in mm	Grit	QTY/ PKG	Order no.		
533x4 CE-K60 VE10	533 x 4	60	10	434.655		
533x4 CE-K80 VE10	533 x 4	80	10	434.663		
533x4 CE-K120 VE10	533 x 4	120	10	434.671		
533x9 CE-K60 VE10	533 x 9	60	10	434.698		
533x9 CE-K80 VE10	533 x 9	80	10	434.701		
533x9 CE-K120 VE10	533 x 9	120	10	434.728		
533x30 CE-K60 VE10	533 x 30	60	10	434.736		
533x30 CE-K80 VE10	533 x 30	80	10	434.744		
533x30 CE-K120 VE10	533 x 30	120	10	434.752		



Sanding belt CORUFLEX

Designation	Dimensions in mm	Grit	QTY/ PKG	Order no.		
533x4 CR-P120 VE10	533 x 4	P 120	10	434.760		
533x4 CR-P180 VE10	533 x 4	P 180	10	434.779		
533x4 CR-P240 VE10	533 x 4	P 240	10	434.787		
533x9 CR-P120 VE10	533 x 9	P 120	10	434.795		
533x9 CR-P180 VE10	533 x 9	P 180	10	434.809		
533x9 CR-P240 VE10	533 x 9	P 240	10	434.817		
533x30 CR-P120 VE10	533 x 30	P 120	10	434.825		
533x30 CR-P180 VE10	533 x 30	P 180	10	434.833		
533x30 CR-P240 VE10	533 x 30	P 240	10	434.841		



Sanding belt MESHFLEX

Designation	Dimensions in mm	Grit	QTY/ PKG	Order no.		
533x9 ME-A240 VE3	533 x 9	A 240	3	318.663		
533x9 ME-A400 VE3	533 x 9	A 400	3	318.671		
533x30 ME-A100 VE3	533 x 30	A 100	3	434.868		
533x30 ME-A240 VE3	533 x 30	A 240	3	318.647		
533x30 ME-A400 VE3	533 x 30	A 400	3	318.655		



Superfinishing band

Designation	Dimensions in mm	Grit	QTY/ PKG	Order no.		
533x30 SU-S600	533 x 30	S 600	1	318.132		
533x30 SU-S1500	533 x 30	S 1500	1	318.140		




Felt belt, 9 mm

Dimensions in mm	QTY/ PKG	Order no.		
533 x 9	1	259.420		



Felt belt, 30 mm

Dimensions in mm	QTY/ PKG	Order no.		
533 x 30	1	259.419		




Polishing paste Poli white

Weight in kg	QTY/ PKG	Order no.		
0,7	1	255.004		



Fleece belt

Dimensions in mm	QTY/ PKG	Order no.		
618 x 40	1	255.003		



Polishing paste Poli blue

Weight in kg	QTY/ PKG	Order no.		
0,7	1	255.005		

Accessories LLK 1503 VR




Compact grinding disc

Dimensions in mm	Grit	QTY/ PKG	Order no.		
152 x 3 x 25	soft	1	313.416		
152 x 3 x 25	hard	1	313.424		
152 x 6 x 25	soft	1	313.432		
152 x 6 x 25	hard	1	313.440		




Polishing cream Poli creme

Weight in kg	QTY/ PKG	Order no.		
1	1	255.006		



Profiling stone

QTY/ PKG	Order no.		
1	315.494		



Poli set mini white/blue/creme

Designation	Weight in kg	QTY/ PKG	Order no.		
PP-W/B/C	3 x 0,1	1 set	365.041		



FixTec quick clamp nut M 14

QTY/ PKG	Order no.		
1	313.459		

Accessories LBR 1506 VRA



Sanding belt ZIRCOFLEX

Designation	Dimensions in mm	Grit	QTY/ PKG	Order no.		
618x40 ZI-P36 VE10	618 x 40	P 36	10	223.670		
618x40 ZI-P60 VE10	618 x 40	P 60	10	223.689		
618x40 ZI-P80 VE10	618 x 40	P 80	10	434.876		
618x40 ZI-P120 VE10	618 x 40	P 120	10	266.132		



Carrying case L-BOXX®

Designation	External dimensions L x W x H	Internal dimensions L x W x H	Weight	QTY/ PKG	Order no.		
TK-L 238	442 x 357 x 253 mm	378 x 306 x 209 mm	2,8 kg	1	414.093		



Sanding belt CORUFLEX

Designation	Dimensions in mm	Grit	QTY/ PKG	Order no.		
618x40 CR-P180 VE10	618 x 40	P 180	10	434.884		
618x40 CR-P240 VE10	618 x 40	P 240	10	434.892		

Case insert

Designation	QTY/ PKG	Order no.		
TKE LLK1503	1	436.658		




Sanding belt MESHFLEX

Designation	Dimensions in mm	Grit	QTY/ PKG	Order no.		
618x40 ME-A100 VE3	618 x 40	A 100	3	317.969		
618x40 ME-A240 VE3	618 x 40	A 240	3	317.977		
618x40 ME-A400 VE3	618 x 40	A 400	3	317.985		

Range of Products 2018

Accessories ST 1005 VE



Velcro sanding paper

Dimensions in mm	Grit	QTY/ PKG	Order no.		
39 x 60	P 60	10	258.299		
39 x 60	P 120	10	258.300		
39 x 60	P 180	10	258.301		



Velcro sanding fleece

Dimensions in mm	Grit	QTY/ PKG	Order no.		
39 x 60	A 240	10	258.302		



Polishing shoe, square

QTY/ PKG	Order no.			
1	258.031			



Polishing shoe, pointed

QTY/ PKG	Order no.			
1	255.265			



Carrying case with insert


QTY/ PKG	Order no.			
1	319.074			

Saws



RS 11-28 1100 watt universal reciprocating saw with accelerator trigger switch Order no. 432.776

Orbit rate, no load	0-2700 opm
Orbit	28 mm
Power input	1100 watt
Power output	600 watt
Max. material thickness, timber	230 mm
Max. material thickness, metal	20 mm
Cable length	4,0 m
Weight	3,6 kg




Standard Equipment:
1 assortment of saw blades (198.757) ·
1 carrying case (436.607)

NEW



RS 13-32 1300 watt reciprocating saw with variable speed Order no. 438.383

Orbit rate, no load	0-3000 opm
Orbit	32 mm
Power input	1300 watt
Power output	720 watt
Max. material thickness, timber	230 mm
Max. material thickness, metal	20 mm
Cable length	4,0 m
Size (L x H)	520 x 180 mm
Weight	4,6 kg



Standard Equipment:
1 assortment of saw blades (198.757) ·
1 carrying case (455.059)

NEW



RSP 13-32 1300 watt reciprocating saw with orbital cutting action Order no. 438.367

Orbit rate, no load	0-3000 opm
Orbit	32 mm
Power input	1300 watt
Power output	720 watt
Max. material thickness, timber	230 mm
Max. material thickness, metal	20 mm
Cable length	4,0 m
Size (L x H)	520 x 180 mm
Weight	4,6 kg



Standard Equipment:
1 assortment of saw blades (198.757) ·
1 carrying case (455.059)



SBG 4910 Metal-cutting band saw with swivelling saw frame Order no. 390.518

Power input 850 watt
Power output 445 watt
Size of saw band 1335x13x0,65 mm
Belt speed 60 / 80 m/min
Size (W x L x H) 640x310x390 mm
Max. cutting range: round cross
sectional cut at 45°/90° 68 mm / 80 mm
Max. cutting range: square cross
sectional cut at 45°/90° 60 mm / 80 mm
Max. cutting range: rectangular
cross sectional cut
at 45°/90° 68x55 mm / 100x80 mm
Cable length 4,0 m
Weight of saw arm 7,9 kg
Weight (complete unit) 18,0 kg

Standard Equipment:
1 parallel guide fence (385.247) ·
1 bimetal saw blade (1 piece)



CSM 4060 Metal-cutting circular saw for dry cutting Order no. 307.815

Blade Ø 185 mm
Saw blade drill Ø 20 mm
Max. cutting depth (90°) 0-63 mm
Max. material thickness
in aluminium 250 N/mm² 6 mm
in steel 400 N/mm² 10 mm
No load speed 3800 rpm
Power input 1400 watt
Power output 720 watt
Cable length 4,0 m
Weight 5,4 kg

Standard Equipment:
2 carbide tipped saw blades for steel,
38 teeth (185 x 20 mm) (312.304 (2x)) ·
1 parallel guide fence (312.312) ·
1 ring / open-ended wrench (312.347) ·
1 safety glasses (1 piece) ·
1 carrying case (1 piece)

Accessories for saws

Accessories reciprocating saws



Sabre saw blades for metal and sheet material

Designation	Teeth per inch	Length in mm	QTY/ PKG	Order no.		
RS/Bi-150 14 VE5	14	150	5	462.055		
RS/Bi-150 18 VE5	18	150	5	462.063		
RS/Bi-150 14 VE5	14	150	5	462.071		



Reciprocating saw blades for metal, timber, plastic materials

Designation	Teeth per inch	Length in mm	QTY/ PKG	Order no.		
RS/Bi-150 6 VE5	6	150	5	462.098		
RS/Bi-150 10 VE5	10	150	5	462.101		
RS/Bi-230 6 VE5	10	230	5	462.128		



Reciprocating saw blades for demolition

Designation	Teeth per inch	Length in mm	QTY/ PKG	Order no.		
RS/Bi-230 6 VE5	6	230	5	462.136		



Reciprocating saw blade for insulation material

Designation	Length in mm	QTY/ PKG	Order no.		
RS/St-300 W VE2	300	2	462.144		



Reciprocating saw blades for timber

Designation	Teeth per inch	Length in mm	QTY/ PKG	Order no.		
RS/CV-230 10 VE2	10	230	2	462.152		

Reciprocating saw blade for pallets

Designation	Teeth per inch	Length in mm	QTY/ PKG	Order no.		
RS/Bi-230 6 VE5	10	230	5	462.160		



Sabre blade assortment for plastic/wood/metal

Designation	QTY/ PKG	Order no.		
RS/Bi Set VE3	3	462.179		



Sabre blade assortment for plastic/wood/metal

Designation	Length in mm	QTY/ PKG	Order no.		
Sabre blade assortment	150	3	198.757		

Range of Products 2018



Chain clamp fixture

QTY/ PKG	Order no.		
1	251.259		



Carrying case

Designation	QTY/ PKG	Order no.		
TK-S RS 11-28	1	436.607		
TK-S RS13-32	1	455.059		



Plastic multi-carrying case

Designation	QTY/ PKG	Order no.		
TK-S Multi	1	329.908		

Accessories SBG 4910, 4908



Saw blades

Designation	Teeth per inch	Size (W x L x H)	QTY/ PKG	Order no.		
SB 1335x13x0,65 Bi-M42 18 VE2	18	1335 x 13 x 0,65 mm	2	399.485		
SB 1335x13x0,65 Bi-M 8/12 VE3	8/12	1335 x 13 x 0,65 mm	3	359.289		
SB 1335x13x0,65 Bi-M 10/14 VE3	10/14	1335 x 13 x 0,65 mm	3	359.130		
SB 1335x13x0,65 WS 18 VE3	18	1335 x 13 x 0,65 mm	3	359.106		
SB 1335x13x0,65 WS 24 VE3	24	1335 x 13 x 0,65 mm	3	359.270		



Chuck jaws

Designation	QTY/ PKG	Order no.		
SBG-SP 10 VE2	2	388.718		

Accessories SB 2908



Saw blades

Designation	Teeth per inch	Length in mm	QTY/ PKG	Order no.		
Bimetal saw blade, 10T/1140 mm, pack of 3	10	1140	3	232.165		
Bimetal saw blade, 18T/1140 mm, pack of 3	18	1140	3	232.181		
Bimetal saw blade, 24T/1140 mm, pack of 3	24	1140	3	232.203		

Accessories CSM 4060



Carbide tipped saw blade for steel

Dimensions in mm	Teeth	QTY/ PKG	Order no.		
185 Ø x 20	38	1	312.304		

Accessories CS 62 18.0-EC (Ø 165 mm)



Standard circular saw blade with alternating teeth

Designation	Dimensions in mm	QTY/ PKG	Order no.		
D165x1,6/1,0x20HM Z=24WZ	165 Ø x 20	1	456.012		

Accessories CSE 55 T (Ø 160 mm)



Fine cut circular saw blade with flat, trapezoidal tooth

Designation	Dimensions in mm	QTY/ PKG	Order no.		
D160x1,8x20 HM Z48-FZ/TR	160 Ø x 20	1	386.774		



Diamond circular saw blade

Designation	Dimensions in mm	QTY/ PKG	Order no.		
D160x2,2x20 DIA Z4-S	160 Ø x 20	1	386.766		



Metal circular saw blade with alternating teeth

Designation	Dimensions in mm	QTY/ PKG	Order no.		
D160x1,8x20 HM Z38-WZ	160 Ø x 20	1	386.782		

Cordless tools



DD 2G 10.8-LD/4.0 Set 2-speed cordless drill driver 10,8 V „Light Duty“ Order no. 418.064

Battery voltage	10,8 V
Battery capacity	2,5 / 4,0 / 6,0 Ah
Max soft/hard torque	17 / 34 Nm
Torque positions	17+1
No load speed 1st gear	0-350 rpm
No load speed 2nd gear	0-1300 rpm
Chuck Ø	0,8 - 10 mm
Max. drill hole Ø in steel	10 mm
Max. drill hole Ø in wood	25 mm
Weight without battery	0,875 kg

Standard Equipment:
 1 belt clip (430.714) ·
 1 bit storage (430.862) ·
 2 batteries 4.0 Ah AP 10.8/4.0 (439.657) ·
 1 charger CA 10.8 (418.021) ·
 1 carrying case L-BOXX® 136 (414.085) ·
 1 case insert (440.841)



PD 2G 10.8-EC 2-speed cordless impact drill 10,8 V Order no. 418.013

Battery voltage	10,8 V
Battery capacity	2,5 / 4,0 / 6,0 Ah
Max soft/hard torque	32 / 58 Nm
Torque positions	24+1
No load speed 1st gear	0-450 rpm
No load speed 2nd gear	0-1700 rpm
Idle blows 1st gear	0-5850 bpm
Idle blows 2nd gear	0-22100 bpm
Chuck Ø	1,5 - 13 mm
Max. drill hole Ø in steel	13 mm
Max. drill hole Ø in wood	25 mm
Max. drill hole Ø masonry	13 mm
Weight without battery	1,14 kg

Standard Equipment:
 1 bit holder (442.380) ·
 1 belt clip (430.714) ·
 1 bit storage (430.862) ·
 1 carrying case L-BOXX® 136 (414.085) ·
 1 case insert (440.841)



DD 2G 10.8-EC 2-speed cordless drill driver 10,8 V Order no. 418.005

Battery voltage	10,8 V
Battery capacity	2,5 / 4,0 / 6,0 Ah
Max soft/hard torque	32 / 58 Nm
Torque positions	20+1
No load speed 1st gear	0-450 rpm
No load speed 2nd gear	0-1700 rpm
Chuck Ø	1,5 - 13 mm
Max. drill hole Ø in steel	13 mm
Max. drill hole Ø in wood	25 mm
Weight without battery	1,09 kg

Standard Equipment:
 1 bit holder (442.380) ·
 1 belt clip (430.714) ·
 1 bit storage (430.862) ·
 1 carrying case L-BOXX® 136 (414.085) ·
 1 case insert (440.841)



PD 2G 10.8-EC/6.0 Set 2-speed cordless impact drill 10,8 V Order no. 462.772

Battery voltage	10,8 V
Battery capacity	2,5 / 4,0 / 6,0 Ah
Max soft/hard torque	32 / 58 Nm
Torque positions	24+1
No load speed 1st gear	0-450 rpm
No load speed 2nd gear	0-1700 rpm
Idle blows 1st gear	0-5850 bpm
Idle blows 2nd gear	0-22100 bpm
Chuck Ø	1,5 - 13 mm
Max. drill hole Ø in steel	13 mm
Max. drill hole Ø in wood	25 mm
Max. drill hole Ø masonry	13 mm
Weight without battery	1,14 kg

Standard Equipment:
 1 bit holder (442.380) ·
 1 belt clip (430.714) ·
 1 bit storage (430.862) ·
 2 batteries 6.0 Ah AP 10.8/6.0 (438.294) ·
 1 charger CA 10.8 (418.021) ·
 1 carrying case L-BOXX® 136 (414.085) ·
 1 case insert (440.841)

NEW



DD 2G 10.8-EC/4.0 Set 2-speed cordless drill driver 10,8 V Order no. 462.764

Battery voltage	10,8 V
Battery capacity	2,5 / 4,0 / 6,0 Ah
Max soft/hard torque	32 / 58 Nm
Torque positions	20+1
No load speed 1st gear	0-450 rpm
No load speed 2nd gear	0-1700 rpm
Chuck Ø	1,5 - 13 mm
Max. drill hole Ø in steel	13 mm
Max. drill hole Ø in wood	25 mm
Weight without battery	1,09 kg

Standard Equipment:
 1 bit holder (442.380) ·
 1 belt clip (430.714) ·
 1 bit storage (430.862) ·
 2 batteries 4.0 Ah AP 10.8/4.0 (439.657) ·
 1 charger CA 10.8 (418.021) ·
 1 carrying case L-BOXX® 136 (414.085) ·
 1 case insert (440.841)

Range of Products 2018



DD 2G 18.0 2-speed cordless drill driver 18,0 V Order no. 417.831

Battery voltage	18 V
Battery capacity	2,5 / 5,0 Ah
Max soft/hard torque	52 / 68 Nm
Torque positions	20+1
No load speed 1st gear	0-380 rpm
No load speed 2nd gear	0-1650 rpm
Chuck Ø	1,5 - 13 mm
Max. drill hole Ø in steel	13 mm
Max. drill hole Ø in wood	30 mm
Weight without battery	1,4 kg

Standard Equipment:
1 handle (428.698) ·
1 belt clip (430.714) ·
1 bit storage (430.862) ·
1 carrying case L-BOXX® 136 (414.085) ·
1 case insert (423.238)



PD 2G 18.0/2.5 Set 2-speed cordless impact drill 18,0 V Order no. 436.585

Battery voltage	18 V
Battery capacity	2,5 / 5,0 Ah
Max soft/hard torque	52 / 65 Nm
Torque positions	24+1
No load speed 1st gear	0-380 rpm
No load speed 2nd gear	0-1650 rpm
Idle blows 1st gear	0-4940 bpm
Idle blows 2nd gear	0-21450 bpm
Chuck Ø	1,5 - 13 mm
Max. drill hole Ø in steel	13 mm
Max. drill hole Ø in masonry	16 mm
Max. drill hole Ø in wood	30 mm
Weight without battery	1,4 kg

Standard Equipment:
1 handle (428.698) ·
1 belt clip (430.714) ·
1 bit storage (430.862) ·
2 batteries 2.5 Ah AP 18.0/2.5 (417.890) ·
1 charger CA 10.8/18.0 (417.882) ·
1 carrying case L-BOXX® 136 (414.085) ·
1 case insert (423.238)



DD 2G 18.0/2.5 Set 2-speed cordless drill driver 18,0 V Order no. 436.577

Battery voltage	18 V
Battery capacity	2,5 / 5,0 Ah
Max soft/hard torque	52 / 68 Nm
Torque positions	20+1
No load speed 1st gear	0-380 rpm
No load speed 2nd gear	0-1650 rpm
Chuck Ø	1,5 - 13 mm
Max. drill hole Ø in steel	13 mm
Max. drill hole Ø in wood	30 mm
Weight without battery	1,4 kg

Standard Equipment:
1 handle (428.698) ·
1 belt clip (430.714) ·
1 bit storage (430.862) ·
2 batteries 2.5 Ah AP 18.0/2.5 (417.890) ·
1 charger CA 10.8/18.0 (417.882) ·
1 carrying case L-BOXX® 136 (414.085) ·
1 case insert (423.238)

NEW



DD 2G 18.0-EC 2-speed cordless drill driver 18,0 V Order no. 447.498

Battery voltage	18 V
Battery capacity	2,5 / 5,0 Ah
Max soft/hard torque	56 / 90 Nm
Torque positions	23+1
No load speed 1st gear	0-600 rpm
No load speed 2nd gear	0-2300 rpm
Chuck Ø	1,5 - 13 mm
Max. drill hole Ø in steel	13 mm
Max. drill hole Ø in wood	60 mm
Weight without battery	1,5 kg

Standard Equipment:
1 handle (428.698) ·
1 belt clip (430.714) ·
1 bit holder (453.994) ·
1 bit storage (430.862) ·
1 carrying case L-BOXX® 136 (414.085) ·
1 case insert (454.125)



PD 2G 18.0 2-speed cordless impact drill 18,0 V Order no. 417.858

Battery voltage	18 V
Battery capacity	2,5 / 5,0 Ah
Max soft/hard torque	52 / 65 Nm
Torque positions	24+1
No load speed 1st gear	0-380 rpm
No load speed 2nd gear	0-1650 rpm
Idle blows 1st gear	0-4940 bpm
Idle blows 2nd gear	0-21450 bpm
Chuck Ø	1,5 - 13 mm
Max. drill hole Ø in steel	13 mm
Max. drill hole Ø in masonry	16 mm
Max. drill hole Ø in wood	30 mm
Weight without battery	1,4 kg

Standard Equipment:
1 handle (428.698) ·
1 belt clip (430.714) ·
1 bit storage (430.862) ·
1 carrying case L-BOXX® 136 (414.085) ·
1 case insert (423.238)

NEW



DD 2G 18.0-EC/2.5 Set 2-speed cordless drill driver 18,0 V Order no. 461.733

Battery voltage	18 V
Battery capacity	2,5 / 5,0 Ah
Max soft/hard torque	56 / 90 Nm
Torque positions	23+1
No load speed 1st gear	0-600 rpm
No load speed 2nd gear	0-2300 rpm
Chuck Ø	1,5 - 13 mm
Max. drill hole Ø in steel	13 mm
Max. drill hole Ø in wood	60 mm
Weight without battery	1,5 kg

Standard Equipment:
1 handle (428.698) ·
1 belt clip (430.714) ·
1 bit holder (453.994) ·
1 bit storage (430.862) ·
2 batteries 2.5 Ah AP 18.0/2.5 (445.886) ·
1 charger CA 10.8/18.0 (417.882) ·
1 carrying case L-BOXX® 136 (414.085) ·
1 case insert (454.125)

NEW



PD 2G 18.0-EC
2-speed cordless impact drill 18,0 V
Order no. 447.501

Battery voltage	18 V
Battery capacity	2,5 / 5,0 Ah
Max soft/hard torque	56 / 90 Nm
Torque positions	24+1
No load speed 1st gear	0-600 rpm
No load speed 2nd gear	0-2300 rpm
Blows per minute	9600-37000 bpm
Chuck Ø	1,5 - 13 mm
Max. drill hole Ø in steel	13 mm
Max. drill hole Ø masonry	16 mm
Max. drill hole Ø in wood	60 mm
Weight without battery	1,6 kg

Standard Equipment:
1 handle (428.698) ·
1 belt clip (430.714) ·
1 bit holder (453.994) ·
1 bit storage (430.862) ·
1 carrying case L-BOXX® 136 (414.085) ·
1 case insert (454.125)

NEW



ID 1/4" 18.0/2.5 Set
Cordless impact drill driver 18,0 V
Order no. 462.780

Battery voltage	18 V
Battery capacity	2,5 / 5,0 Ah
Max. torque	180 Nm
No load speed	0-2300 rpm
Blows per minute	0-3200 bpm
Tool fixture	1/4"
Weight without battery	1,2 kg

Standard Equipment:
1 belt clip (430.714) ·
1 bit storage (430.862) ·
2 batteries 2.5 Ah AP 18.0/2.5 (445.886) ·
1 charger CA 10.8/18.0 (417.882) ·
1 carrying case L-BOXX® 136 (414.085) ·
1 case insert (423.238)

NEW



PD 2G 18.0-EC/2.5 Set
2-speed cordless impact drill 18,0 V
Order no. 461.741

Battery voltage	18 V
Battery capacity	2,5 / 5,0 Ah
Max soft/hard torque	56 / 90 Nm
Torque positions	24+1
No load speed 1st gear	0-600 rpm
No load speed 2nd gear	0-2300 rpm
Blows per minute	9600-37000 bpm
Chuck Ø	1,5 - 13 mm
Max. drill hole Ø in steel	13 mm
Max. drill hole Ø masonry	16 mm
Max. drill hole Ø in wood	60 mm
Weight without battery	1,6 kg

Standard Equipment:
1 handle (428.698) ·
1 belt clip (430.714) ·
1 bit holder (453.994) ·
1 bit storage (430.862) ·
2 batteries 2.5 Ah AP 18.0/2.5 (445.886) ·
1 charger CA 10.8/18.0 (417.882) ·
1 carrying case L-BOXX® 136 (414.085) ·
1 case insert (454.125)

NEW



IW 1/2" 18.0-EC
Cordless impact drill driver 18,0 V
Order no. 438.308

Battery voltage	18 V
Battery capacity	2,5 / 5,0 Ah
Max. torque	250 Nm
Torque positions	3 (140 / 170 / 250 Nm)
No load speed	600-2500 rpm
Blows per minute	3300 bpm
Tool fixture	1/2"
Weight without battery	1,1 kg

Standard Equipment:
1 belt clip (430.714) ·
1 bit storage (430.862) ·
1 carrying case L-BOXX® 136 (414.085) ·
1 case insert (423.238)

NEW



IW 1/2" 18.0-EC/2.5 Set
Cordless impact drill driver 18,0 V
Order no. 461.776

Battery voltage	18 V
Battery capacity	2,5 / 5,0 Ah
Max. torque	250 Nm
Torque positions	3 (140 / 170 / 250 Nm)
No load speed	600-2500 rpm
Blows per minute	3300 bpm
Tool fixture	1/2"
Weight without battery	1,1 kg

Standard Equipment:
1 belt clip (430.714) ·
1 bit storage (430.862) ·
2 batteries 2.5 Ah AP 18.0/2.5 (445.886) ·
1 charger CA 10.8/18.0 (417.882) ·
1 carrying case L-BOXX® 136 (414.085) ·
1 case insert (423.238)



ID 1/4" 18.0
Cordless impact drill driver 18,0 V
Order no. 417.866

Battery voltage	18 V
Battery capacity	2,5 / 5,0 Ah
Max. torque	180 Nm
No load speed	0-2300 rpm
Blows per minute	0-3200 bpm
Tool fixture	1/4"
Weight without battery	1,2 kg

Standard Equipment:
1 belt clip (430.714) ·
1 bit storage (430.862) ·
1 carrying case L-BOXX® 136 (414.085) ·
1 case insert (423.238)

Range of Products 2018



CHE 18.0-EC Cordless rotary hammer drill 18,0 V Order no. 430.005

Battery voltage	18 V
Battery capacity	2,5 / 5,0 Ah
No load speed	0-1400 rpm
Blows per minute	0-4500 bpm
Single impact energy (EPTA)	1,7 J
Max. drill hole Ø in steel	13 mm
Max. drill hole Ø in concrete	18 mm
Max. drill hole Ø in wood	20 mm
Tool fixture	SDS-plus
Weight without battery	2,0 kg

Standard Equipment:
1 handle (436.364) ·
1 depth stop (436.372) ·
1 carrying case L-BOXX® 238 (414.093) ·
1 case insert (435.945)

NEW



RS 29 18.0/5.0 Set Cordless reciprocating saw 18,0 V Order no. 462.799

Orbit rate, no load	0-3100 opm
Orbit	29 mm
Battery voltage	18 V
Battery capacity	2,5 / 5,0 Ah
Weight without battery	2,9 kg

Standard Equipment:
2 batteries 5.0 Ah AP 18.0/5.0 (445.894) ·
1 charger CA 10.8/18.0 (417.882) ·
1 carrying case L-BOXX® 238 (414.093) ·
1 case insert (423.246)

NEW




CHE 18.0-EC/5.0 Set Cordless rotary hammer drill 18,0 V Order no. 461.768

Battery voltage	18 V
Battery capacity	2,5 / 5,0 Ah
No load speed	0-1400 rpm
Blows per minute	0-4500 bpm
Single impact energy (EPTA)	1,7 J
Max. drill hole Ø in steel	13 mm
Max. drill hole Ø in concrete	18 mm
Max. drill hole Ø in wood	20 mm
Tool fixture	SDS-plus
Weight without battery	2,0 kg

Standard Equipment:
1 handle (436.364) ·
1 depth stop (436.372) ·
2 batteries 5.0 Ah AP 18.0/5.0 (445.894) ·
1 charger CA 10.8/18.0 (417.882) ·
1 carrying case L-BOXX® 238 (414.093) ·
1 case insert (435.945)

NEW




CS 62 18.0-EC Cordless circular saw with pendulum hood 18,0 V Order no. 417.939

Battery voltage	18 V
Battery capacity	2,5 / 5,0 Ah
No load speed	5000 rpm
Pivoting range	0°-50°
Saw blade holder	20 mm
Cutting depth	0-62 mm
Depth of cut - mitre cut	0-38 mm
Depth of cut - mitre cut with guide rail	0-32 mm
Blade Ø	165 mm
Angle preset	0°/22,5°/45°/50°
Size (W x L x H)	335 x 190 x 210 mm
Weight without battery	3,1 kg

Standard Equipment:
1 saw blade Z 24-WZ (456.012) ·
1 dust bag (1 piece) ·
1 extraction adapter (1 piece) ·
1 carrying case L-BOXX® 374 (414.107) ·
1 case insert (459.380)

NEW



CS 62 18.0-EC/5.0 Set Cordless circular saw with pendulum hood 18,0 V Order no. 454.028

Battery voltage	18 V
Battery capacity	2,5 / 5,0 Ah
No load speed	5000 rpm
Pivoting range	0°-50°
Saw blade holder	20 mm
Cutting depth	0-62 mm
Depth of cut - mitre cut	0-38 mm
Depth of cut - mitre cut with guide rail	0-32 mm
Blade Ø	165 mm
Angle preset	0°/22,5°/45°/50°
Size (W x L x H)	335 x 190 x 210 mm
Weight without battery	3,1 kg


Standard Equipment:
1 saw blade Z 24-WZ (456.012) ·
1 dust bag (1 piece) ·
1 extraction adapter (1 piece) ·
2 batteries 5.0 Ah AP 18.0/5.0 (445.894) ·
1 charger CA 10.8/18.0 (417.882) ·
1 carrying case L-BOXX® 374 (414.107) ·
1 case insert (459.380)



RS 29 18.0 Cordless reciprocating saw 18,0 V Order no. 417.874

Orbit rate, no load	0-3100 opm
Orbit	29 mm
Battery voltage	18 V
Battery capacity	2,5 / 5,0 Ah
Weight without battery	2,9 kg

Standard Equipment:
1 carrying case L-BOXX® 238 (414.093) ·
1 case insert (423.246)



L 125 18.0-EC Cordless angle grinder ACCUFLEX 18.0 V, 125 mm Order no. 461.725

Battery voltage	18 V
Battery capacity	2,5 / 5,0 Ah
Max. disc diameter	125 mm
No load speed	8500 rpm
Tool fixture	M 14
Weight without battery	1,75 kg

Standard Equipment:
 1 guard grinding 125 Ø (436.860) ·
 1 handle (450.774) ·
 1 pin wrench (100.110) ·
 1 clamping flange (335.282) ·
 1 clamping nut (100.080) ·
 1 carrying case L-BOXX® 136 (414.085) ·
 1 case insert (444.405)

Accessories for cordless tools

Accessories



Battery powered heating jacket

Designation	Size	QTY/ PKG	Order no.		
TJ 10.8/18.0 M	M	1	417.998		
TJ 10.8/18.0 L	L	1	423.165		
TJ 10.8/18.0 XL	XL	1	423.173		
TJ 10.8/18.0 XXL	XXL	1	423.181		



L 125 18.0-EC/5.0 Set Cordless angle grinder ACCUFLEX 18.0 V, 125 mm Order no. 417.947

Battery voltage	18 V
Battery capacity	2,5 / 5,0 Ah
Max. disc diameter	125 mm
No load speed	8500 rpm
Tool fixture	M 14
Weight without battery	1,75 kg

Standard Equipment:
 1 guard grinding 125 Ø (436.860) ·
 1 handle (450.774) ·
 1 pin wrench (100.110) ·
 1 clamping flange (335.282) ·
 1 clamping nut (100.080) ·
 2 batteries 5.0 Ah AP 18.0/5.0 (445.894) ·
 1 charger CA 10.8/18.0 (417.882) ·
 1 carrying case L-BOXX® 136 (414.085) ·
 1 case insert (444.405)



LED worklamp

Designation	QTY/ PKG	Order no.		
WL LED 18.0	1	417.955		



Li-Ion rechargeable battery pack 10,8 V

Designation	Battery capacity	Battery voltage	QTY/ PKG	Order no.		
AP 10.8/2.5	2,5 Ah	10,8 V	1	418.048		
AP 10.8/4.0	4,0 Ah	10,8 V	1	439.657		
AP 10.8/6.0	6,0 Ah	10,8 V	1	438.294		



Li-Ion rechargeable battery pack 18,0 V

Designation	Battery capacity	Battery voltage	QTY/ PKG	Order no.		
AP 18.0/2.5	2,5 Ah	18,0 V	1	445.886		
AP 18.0/5.0	5,0 Ah	18,0 V	1	445.894		



Rapid charger 10.8 Volt

Designation	QTY/ PKG	Order no.		
CA 10.8	1	418.021		



Rapid charger

Designation	QTY/ PKG	Order no.		
CA 10.8/18.0	1	417.882		

Range of Products 2018



Battery adapter

Designation	QTY/ PKG	Order no.		
PS 10.8/18.0	1	456.071		



Auxiliary handle

Designation	QTY/ PKG	Order no.		
HZ-S DD/PD 18.0	1	428.698		



Angle attachment

Designation	QTY/ PKG	Order no.		
WV 10.8-EC	1	442.372		



Diamond dry drill bits

Designation	D in mm	T in mm	L in mm	QTY/ PKG	Order no.		
DD-DRY D6x30 HEX	6 Ø	30	80	1	386.286		
DD-DRY D8x30 HEX	8 Ø	30	80	1	386.294		
DD-DRY D10x30 HEX	10 Ø	30	80	1	386.308		
DD-DRY D14x30 HEX	14 Ø	30	80	1	386.316		



Angle attachment

Designation	QTY/ PKG	Order no.		
WV 18.0-EC	1	454.001		



Tile drill bits

Designation	D in mm	T in mm	L in mm	QTY/ PKG	Order no.		
TD D5x50 D10	5 Ø	50	110	1	386.324		
TD D6x50 D10	6 Ø	50	110	1	386.332		
TD D8x50 D10	8 Ø	50	110	1	386.340		



Keyless chuck

Designation	QTY/ PKG	Order no.		
BF 10.8-EC	1	442.364		



Carrying case L-BOXX®



Chuck

Designation	QTY/ PKG	Order no.		
BF 18.0-EC	1	453.986		

Designation	External dimensions L x W x H	Internal dimensions L x W x H	Weight	QTY/ PKG	Order no.		
TK-L 136	442 x 357 x 151 mm	378 x 311 x 107 mm	2,2 kg	1	414.085		
TK-L 238	442 x 357 x 253 mm	378 x 306 x 209 mm	2,8 kg	1	414.093		
TK-L 374	442 x 357 x 389 mm	378 x 296 x 345 mm	3,4 kg	1	414.107		



Bit holder

Designation	QTY/ PKG	Order no.		
BV 10.8-EC	1	442.380		

Case insert



Bit holder

Designation	QTY/ PKG	Order no.		
BV 18.0-EC	1	453.994		

Designation	QTY/ PKG	Order no.		
TKE DD/PD/ID/IW 18.0	1	423.238		
TKE DD/PD 2G 18.0-EC	1	454.125		
TKE DD/PD 2G 10.8-EC	1	440.841		
TKE CHE 18.0-EC	1	435.945		
TKE RS 18.0	1	423.246		
TKE CS 62 18.0-EC	1	459.380		
TKE L125 18.0-EC	1	444.405		



Bit set

Designation	QTY/ PKG	Order no.		
DB T-Box Set-1	1	455.881		


Giraffe® wall and ceiling sander



GE 5 Giraffe® wall and ceiling sander Order no. 405.884*

Power input	500 watt
Power output	270 watt
No load speed	1100-1650 rpm
Sanding disc Ø	225 mm
Tool fixture	velcro
Tilt angle on the head	100 °
Length	1520 mm
Cable length	5,0 m
Weight	3,9 kg

Standard Equipment:
1 velcro sanding disc supersoft
(399.418) ·
1 clip-on quick clamping ring SH-FC 32
(406.023)



GE 5 + TB-L Giraffe® wall and ceiling sander Order no. 409.316*

Standard Equipment:
1 velcro sanding disc supersoft
(399.418) ·
1 clip-on quick clamping ring SH-FC 32
(406.023) ·
1 carrying bag (408.867)



GE 5 + SH Kit Giraffe® wall and ceiling sander Order no. 409.375

Standard Equipment:
1 velcro sanding disc supersoft
(399.418) ·
1 clip-on quick clamping ring SH-FC 32
(406.023) ·
Antistatic suction hose 32 mm Ø x 4 m
with snap coupling and coupling bush for
vacuum cleaner, with auxiliary air control
(406.708)



GE 5 + TB-L + SH Giraffe® wall and ceiling sander Order no. 409.391


Standard Equipment:
1 velcro sanding disc supersoft
(399.418) ·
1 clip-on quick clamping ring SH-FC 32
(406.023) ·
Antistatic suction hose 32 mm Ø x 4 m
with snap coupling and coupling bush for
vacuum cleaner, with auxiliary air control
(406.708) ·
1 carrying bag (408.867)



GE 5 R Giraffe® wall and ceiling sander Order no. 405.892*


Power input	500 watt
Power output	270 watt
No load speed	1100-1650 rpm
Sanding disc Ø	225 mm
Tool fixture	velcro
Tilt angle on the head	100 °
Length	1520 mm
Cable length	5,0 m
Weight	3,9 kg

Standard Equipment:
1 velcro sanding disc supersoft
(399.418) ·
1 clip-on quick clamping ring SH-FC 32
(406.023)




GE 5 R + TB-L Giraffe® wall and ceiling sander Order no. 409.324*

Standard Equipment:
1 velcro sanding disc supersoft
(399.418) ·
1 clip-on quick clamping ring SH-FC 32
(406.023) ·
1 carrying bag (408.867)



GE 5 R + SH Kit Giraffe® wall and ceiling sander Order no. 409.383

Standard Equipment:
1 velcro sanding disc supersoft
(399.418) ·
1 clip-on quick clamping ring SH-FC 32
(406.023) ·
Antistatic suction hose 32 mm Ø x 4 m
with snap coupling and coupling bush for
vacuum cleaner, with auxiliary air control
(406.708)



GE 5 R + TB-L + SH Giraffe® wall and ceiling sander Order no. 409.405

Standard Equipment:
1 velcro sanding disc supersoft
(399.418) ·
1 clip-on quick clamping ring SH-FC 32
(406.023) ·
Antistatic suction hose 32 mm Ø x 4 m
with snap coupling and coupling bush for
vacuum cleaner, with auxiliary air control
(406.708) ·
1 carrying bag (408.867)


* Giraffe does not include vacuum hose for connecting to a FLEX safety vacuum cleaner

Range of Products 2018



GSE 5 R + TB-L
Okapi® compact wall and ceiling sander
Order no. 416.207*

Power input	500 watt
Power output	270 watt
No load speed	1100-1650 rpm
Sanding disc Ø	225 mm
Tool fixture	velcro
Tilt angle on the head	100 °
Length	1160 mm
Cable length	5,0 m
Weight	3,6 kg




Standard Equipment:
1 velcro sanding disc supersoft (399.418) ·
1 clip-on quick clamping ring SH-FC 32 (406.023) ·
1 carrying bag (415.189)



WSE 7 Vario Set
Handy-Giraffe® wall and ceiling sander
Order no. 385.166

Power input	710 watt
Power output	420 watt
No load speed	600-1950 rpm
Corner sander no-load speed	1800-5400 opm
Sanding disc Ø	225 mm
Size (W x L x H)	330 x 120 x 170 mm
Cable length	4,0 m
Weight	2,8 kg




Standard Equipment:
Round sanding head with velcro sanding pad supersoft (350.346) ·
Velcro backed sanding paper, 1 x P 60, 80, 100, 220 (1 set) ·
1 carrying case (366.641) ·
2 case inserts (383.902/383.899)



GSE 5 R + TB-L + SH
Okapi® compact wall and ceiling sander
Order no. 417.823

Standard Equipment:
1 velcro sanding disc supersoft (399.418) ·
1 clip-on quick clamping ring SH-FC 32 (406.023) ·
Antistatic suction hose 32 mm Ø x 4 m with snap coupling and coupling bush for vacuum cleaner, with auxiliary air control (406.708) ·
1 carrying bag (415.189)



WSE 7 Vario Plus
Handy-Giraffe® wall and ceiling sander
Order no. 385.190*

Standard Equipment:
Round sanding head with velcro sanding pad supersoft (350.346) ·
Triangular sanding head (388.289) ·
Velcro backed sanding paper, 1 x P 60, 80, 100, 220 (1 set) ·
Velcro backed sanding paper, triangular, Select, 1 x P 60, 80, 100, 220 (1 set) ·
1 carrying case (366.641) ·
2 case inserts (383.902/383.899)



WSE 7 Vario
Handy-Giraffe® wall and ceiling sander
Order no. 377.821

Power input	710 watt
Power output	420 watt
No load speed	600-1950 rpm
Corner sander no-load speed	1800-5400 opm
Sanding disc Ø	225 mm
Size (W x L x H)	330 x 120 x 170 mm
Cable length	4,0 m
Weight	2,8 kg



WST 700 VV
Vario-Giraffe® wall and ceiling sander
Order no. 350.311

Power input	710 watt
Power output	420 watt
No load speed	1100-1700 rpm
Corner sander no-load speed	3300-5100 opm
Sanding disc Ø	225 mm
Dimensions in mm	1330-1730
Cable length	4,0 m
Weight	4,8 kg



Standard Equipment:
Round sanding head with velcro sanding pad supersoft (350.346) ·
Velcro backed sanding paper, 1 x P 60, 80, 100, 220 (1 set) ·
1 hexagon socket wrench, SW 5 (115.460) ·
Antistatic suction hose 32 mm Ø x 4 m with snap coupling and coupling bush for vacuum cleaner, with auxiliary air control (406.708) ·
1 carrying case (389.986)



WST 700 VV Plus Vario-Giraffe® wall and ceiling sander Order no. 350.338

Power input	710 watt
Power output	420 watt
No load speed	1100-1700 rpm
Corner sander no-load speed	3300-5100 opm
Sanding disc Ø	225 mm
Dimensions in mm	1330-1730
Cable length	4,0 m
Weight	4,8 kg



Standard Equipment:
 Triangular sanding head (388.289) ·
 Round sanding head with velcro sanding pad supersoft (350.346) ·
 Velcro backed sanding paper, 1 x P 60, 80, 100, 220 (1 set) ·
 Velcro backed sanding paper, triangular, Select, 1 x P 60, 80, 100, 220 (1 set) ·
 1 hexagon socket wrench, SW 5 (115.460) ·
 Antistatic suction hose 32 mm Ø x 4 m with snap coupling and coupling bush for vacuum cleaner, with auxiliary air control (406.708) ·
 1 carrying case (389.986)



GM 320 Mobile workstation for wall and ceiling sanders Order no. 382.167

Power outlet	2 x 230 V
Size (W x L x H)	1140 x 660 x 1780 mm
Tool fixture	all Giraffe types (except WSE 7, GSE 5)
Max. working height	3200 mm
Weight	31,5 kg

Standard Equipment:
 Adapter for all FLEX Giraffes (382.205)

Accessories for ceiling and wall finishing

Accessories GE 5 / GE 5 R / GSE 5 R



Extension

Designation	Dimensions in mm	QTY/ PKG	Order no.		
GV 50	500	1	409.294		



Carrying bag

Designation	Size (W x L x H)	QTY/ PKG	Order no.		
TB-L 1560x320x360	1560 x 320 x 360 mm	1	408.867		
TB-L 1210x320x360	1210 x 320 x 360	1	415.189		



Insert carrying case head retainer

Designation	QTY/ PKG	Order no.			
TBE-T G	1	408.735			



Insert carrying case handle retainer

Designation	QTY/ PKG	Order no.			
TBE-B G	1	408.743			



Auxiliary handle

Designation	QTY/ PKG	Order no.			
HZ-S G	1	408.972			



Adapter

Designation	QTY/ PKG	Order no.			
GMA G	1	409.308			



Antistatic suction hose with auxiliary air control

Designation	QTY/ PKG	Order no.			
SH-C 32x4m AS/NL	1	406.708			

Range of Products 2018



Fast clip adapter

Designation	QTY/ PKG	Order no.		
SAD-FC 32	1	410.497		



Velcro backing pad Ø 225, round

Designation	Type	QTY/ PKG	Order no.		
SP-H D225-10	hard	1	350.362		



Clip-on quick clamping ring red

Designation	QTY/ PKG	Order no.		
SH-FC 32	1	406.023		



Velcro backing pad Ø 225, round

Designation	Type	QTY/ PKG	Order no.		
SP-M D225-10	medium	1	352.306		

Velcro backing pads, adapter



Velcro backing pad Ø 225, round

Designation	Type	QTY/ PKG	Order no.		
KAD D225/16 Set	supersoft	1	399.418		



Velcro backing pad Ø 225, round

Designation	Type	QTY/ PKG	Order no.		
SP-S D225-10	soft	1	366.862		



Padded adapter for velcro paper

Designation	Type	Height	QTY/ PKG	Order no.		
KAD D225/13 S	supersoft	13 mm	1	437.956		
KAD D225/13 H	hard	13 mm	1	439.800		




Triangular sanding head

Designation	QTY/ PKG	Order no.		
V SX 290x290	1	388.289		



Padded adapter for velcro paper


Designation	Type	Height	QTY/ PKG	Order no.		
KAD D225/16 S	supersoft	16 mm	1	260.232		
KAD D225/16 H	hard	16 mm	1	412.899		



Velcro triangular backing pad

QTY/ PKG	Order no.		
1	354.988		

Velcro abrasives



Interface Ø 225, round

Designation	QTY/ PKG	Order no.		
IP D225-10 VE2	2	377.848		



Velcro sanding paper (perforated)


Designation	Dimensions in mm	Grit	QTY/ PKG	Order no.		
D225 PF-P40 VE25	225 Ø	P 40	25	280.739		
D225 PF-P60 VE25	225 Ø	P 60	25	260.233		
D225 PF-P80 VE25	225 Ø	P 80	25	260.234		
D225 PF-P100 VE25	225 Ø	P 100	25	260.235		
D225 PF-P120 VE25	225 Ø	P 120	25	282.405		
D225 PF-P150 VE25	225 Ø	P 150	25	311.995		
D225 PF-P180 VE25	225 Ø	P 180	25	311.987		
D225 PF-P220 VE25	225 Ø	P 220	25	260.236		

Accessories WST 700 VV, WSE 7



Round sanding head

Designation	QTY/ PKG	Order no.		
VSR D225	1	350.346		



Velcro sanding paper SELECTFLEX

Designation	Dimensions in mm	Grit	QTY/ PKG	Order no.		
D225-10 SE-P16 VE10	225 Ø	P 16	10	350.079		
D225-10 SE-P40 VE20	225 Ø	P 40	20	370.924		
D225-10 SE-P60 VE25	225 Ø	P 60	25	348.503		
D225-10 SE-P80 VE25	225 Ø	P 80	25	348.511		
D225-10 SE-P100 VE25	225 Ø	P 100	25	348.538		
D225-10 SE-P120 VE25	225 Ø	P 120	25	349.216		
D225-10 SE-P150 VE25	225 Ø	P 150	25	349.224		
D225-10 SE-P180 VE25	225 Ø	P 180	25	349.232		
D225-10 SE-P220 VE25	225 Ø	P 220	25	348.546		
D225-10 SE-P80-180 VE25	225 Ø	*	25	370.932		

* 5x P 80/100/120/150/180



Velcro sanding paper SELECTFLEX

Designation	Dimensions in mm	Grit	QTY/ PKG	Order no.		
290-12 SE-P16 VE10	290	P 16	10	350.095		
290-12 SE-P40 VE20	290	P 40	20	370.940		
290-12 SE-P60 VE25	290	P 60	25	348.554		
290-12 SE-P80 VE25	290	P 80	25	348.562		
290-12 SE-P100 VE25	290	P 100	25	348.570		
290-12 SE-P120 VE25	290	P 120	25	349.240		
290-12 SE-P150 VE25	290	P 150	25	349.259		
290-12 SE-P180 VE25	290	P 180	25	349.267		
290-12 SE-P220 VE25	290	P 220	25	348.589		
290-12 SE-P80-180 VE25	290	*	25	370.959		

* 5x P 80/100/120/150/180



Velcro sanding grid

Designation	Dimensions in mm	Grit	QTY/ PKG	Order no.		
D225 GT-K80 VE25	225 Ø	grit 80	25	260.237		
D225 GT-K100 VE25	225 Ø	grit 100	25	260.230		



Velcro sanding net NETFLEX

Designation	Dimensions in mm	Grit	QTY/ PKG	Order no.		
D225 XGT-P80 VE25	225 Ø	P 80	25	446.173		
D225 XGT-P100 VE25	225 Ø	P 100	25	446.181		
D225 XGT-P120 VE25	225 Ø	P 120	25	446.203		
D225 XGT-P150 VE25	225 Ø	P 150	25	446.211		



Superfinishing pad

Designation	Dimensions in mm	Grit	QTY/ PKG	Order no.		
D225 SU-S320 VE10	225 Ø	S 320	10	281.026		
D225 SU-S1200 VE10	225 Ø	S 1200	10	281.018		




Velcro sanding fleece

Designation	Dimensions in mm	Grit	QTY/ PKG	Order no.		
D225 SC-A100 VE10	225 Ø	A 100	10	281.042		
D225 SC-A180 VE10	225 Ø	A 180	10	281.034		



Velcro polishing sponge

Designation	Dimensions in mm	Grit	QTY/ PKG	Order no.		
PS-W 225/5 VE5	225 Ø	soft	5	280.992		



Diamond sanding pad

Designation	Dimensions in mm	Grit	QTY/ PKG	Order no.		
DP 30 DRY D225	225 Ø	30	1	419.060		
DP 50 DRY D225	225 Ø	50	1	419.079		
DP 80 DRY D225	225 Ø	80	1	419.087		
DP 100 DRY D225	225 Ø	100	1	419.095		

Other accessories



Carrying case

Designation	Size (W x L x H)	QTY/ PKG	Order no.		
TK-L 609x409x201	609 x 409 x 201 mm	1	366.641		

Case insert - lid

Designation	QTY/ PKG	Order no.		
TKE-T WSE7	1	383.902		

Case insert - bottom

Designation	QTY/ PKG	Order no.		
TKE-B WSE7	1	383.899		



Carrying case

Designation	QTY/ PKG	Order no.		
TK-S WST/WSE 7	1	389.986		


Range of Products 2018

Surface finishing sanding, rotary



SE 14-2 125 Set
SUPRAFLEX, the sanding specialist
for painted surfaces, wood, stone and metal
Order no. 391.174

Max. back-up pad diameter 125 mm
No load speed 600-2100 rpm
Power input 1400 watt
Power output 880 watt
Tool fixture M 14
Size (W x L x H) 365x150x120 mm
Cable length 4,0 m
Weight 2,6 kg



Standard Equipment:
1 guard SG D125 SE (393.363) ·
1 extraction adapter SAD-C D32 AS (393.398) ·
1 auxiliary handle SE 14-2 125 M8 (391.581) ·
1 velcro sanding pad SP D125-8 H/F (391.727) ·
4 sheets of sandingpaper Ø 125 mm (1 set) ·
1 offset face spanner (392.537) ·
1 hexagon socket wrench, SW 4 (102.229) ·
1 hexagon socket wrench, SW 5 long (392.731) ·
3 cable clips (252.188 (3x)) ·
1 carrying case L-BOXX® 238 (414.093) ·
1 case insert (414.158)



LG 1704 VR
1500 watt grinder without extraction,
178 mm
Order no. 293.768

Max. disc diameter 178 mm
No load speed 1400-4200 rpm
Power input 1500 watt
Power output 1000 watt
Cable length 4,0 m
Weight 2,7 kg



Standard Equipment:
1 side handle (252.721)



LK 604
1200 watt grinder without extraction,
175 mm
Order no. 250.346

Max. disc diameter 175 mm
No load speed 4000 rpm
Power input 1200 watt
Power output 720 watt
Tool fixture M 14
Cable length 4,0 m
Weight 3,2 kg




Standard Equipment:
1 side handle (252.721) ·
1 pin wrench (100.110) ·
1 flexible backing pad 170 Ø + clamping nut M 14 (124.079)



SE 14-2 150 Set
SUPRAFLEX, the sanding specialist
for painted surfaces, wood, stone and metal
Order no. 419.206

Max. back-up pad diameter 150 mm
No load speed 600-2100 rpm
Power input 1400 watt
Power output 880 watt
Tool fixture M 14
Size (W x L x H) 365x200x120 mm
Cable length 4,0 m
Weight 2,6 kg



Standard Equipment:
1 guard SG D150 SE (419.176) ·
1 auxiliary handle SE 14-2 125 M8 (391.581) ·
1 velcro sanding pad SP D150-8/6 H/F (419.192) ·
4 sheets of sandingpaper Ø 150 mm (1 set) ·
1 offset face spanner (392.537) ·
1 hexagon socket wrench, SW 4 (102.229) ·
1 hexagon socket wrench, SW 5 long (392.731) ·
3 cable clips (252.188 (3x)) ·
1 carrying case L-BOXX® 238 (414.093) ·
1 case insert (414.158)



SFE 8-2 115
800 watt flat-head sander
Order no. 420.565

Power input 800 watt
Power output 325 watt
No load speed 700-2300 rpm
Max. disc diameter 115 mm
Sanding head level 13 mm
Cable length 4,0 m
Weight 2,5 kg



Standard Equipment:
1 side handle (194.034) ·
1 sanding paper PURFLEX P 40 (1 piece of 381.209) ·
1 sanding paper PURFLEX P 80 (1 piece of 381.225) ·
1 sanding paper PURFLEX P 120 (1 piece of 381.241) ·
1 velcro velours with foam coating 80 mm Ø (296.155)


Surface finishing sanding, random orbital



XS 713 230 watt random-orbit sander Order no. 334.111

Power input	230 watt
Power output	75 watt
Orbit rate, no load	12000 opm
Orbit	1,6 mm
Sand paper	Ø 125 mm
Sanding media fixing	velcro
Cable length	4,0 m
Weight	1,3 kg

Standard Equipment:
1 velcro sanding paper, with 8 perforations (1 piece) ·
1 dust bag (332.992) ·
1 adapter for dust extractor (333.026)



ORE 150-3 Powerful random-orbit sander with speed control, 150 mm Order no. 379.441

Power input	350 watt
No load speed	5800 - 10000 rpm
Orbit rate, no load	11600 - 20000 opm
Orbit	3,0 mm
Backing pad	Ø 150 mm
Sanding media fixing	velcro
Dust extraction connection	Ø 27 mm
Cable length	4,0 m
Weight	2,1 kg


Standard Equipment:
1 velcro sanding pad hard (408.301) ·
1 PES microfilter cartridge with filter (407.984) ·
1 hexagon socket wrench, SW 5 (115.460)



ORE 125-2 Handy random-orbit sander with speed control, 125 mm Order no. 429.872

Power input	200 watt
No load speed	8000 - 13000 rpm
Orbit rate, no load	16000 - 26000 opm
Orbit	2,0 mm
Backing pad	Ø 125 mm
Sanding media fixing	velcro
Dust extraction connection	Ø 27 mm
Cable length	4,0 m
Weight	1,2 kg


Standard Equipment:
1 velcro backing pad (436.348) ·
1 PES microfilter cartridge with filter (407.984)



ORE 150-3 Set Powerful random-orbit sander with speed control in set, 150 mm Order no. 379.603

Power input	350 watt
No load speed	5800 - 10000 rpm
Orbit rate, no load	11600 - 20000 opm
Orbit	3,0 mm
Backing pad	Ø 150 mm
Sanding media fixing	velcro
Dust extraction connection	Ø 27 mm
Cable length	4,0 m
Weight	2,1 kg

Standard Equipment:
1 velcro sanding pad hard (408.301) ·
1 PES microfilter cartridge with filter (407.984) ·
1 sanding paper SELECTFLEX P 80 (1 piece of 408.174) ·
1 sanding paper PURFLEX P 120 (1 piece of 408.050) ·
1 hexagon socket wrench, SW 5 (115.460) ·
1 carrying case L-BOXX® 238 (414.093) ·
1 case insert (407.895)



ORE 125-2 Set Random-orbit sander with speed control in set, 125 mm Order no. 429.880

Power input	200 watt
No load speed	8000 - 13000 rpm
Orbit rate, no load	16000 - 26000 opm
Orbit	2,0 mm
Backing pad	Ø 125 mm
Sanding media fixing	velcro
Dust extraction connection	Ø 27 mm
Cable length	4,0 m
Weight	1,2 kg

Standard Equipment:
1 velcro backing pad (436.348) ·
1 PES microfilter cartridge with filter (407.984) ·
1 sanding paper SELECTFLEX P 80 (1 piece of 380.547) ·
1 sanding paper PURFLEX P 120 (1 piece of 380.687) ·
1 carrying case L-BOXX® 136 (414.085) ·
1 case insert (412.198)




ORE 150-5 Powerful random-orbit sander with speed control, 150 mm Order no. 379.468

Power input	350 watt
No load speed	5800 - 10000 rpm
Orbit rate, no load	11600 - 20000 opm
Orbit	5,0 mm
Backing pad	Ø 150 mm
Sanding media fixing	velcro
Dust extraction connection	Ø 27 mm
Cable length	4,0 m
Weight	2,1 kg

Standard Equipment:
1 velcro sanding pad hard (408.301) ·
1 PES microfilter cartridge with filter (407.984) ·
1 hexagon socket wrench, SW 5 (115.460)

Range of Products 2018



ORE 150-5 Set Powerful random-orbit sander with speed control in set, 150 mm Order no. 379.611

Power input	350 watt
No load speed	5800 - 10000 rpm
Orbit rate, no load	11600 - 20000 opm
Orbit	5,0 mm
Backing pad	Ø 150 mm
Dust extraction connection	Ø 27 mm
Cable length	4,0 m
Weight	2,1 kg

Standard Equipment:
 1 velcro sanding pad hard (408.301) ·
 1 PES microfilter cartridge with filter (407.984) ·
 1 sanding paper SELECTFLEX P 80 (1 piece of 408.174) ·
 1 sanding paper PURFLEX P 120 (1 piece of 408.050) ·
 1 hexagon socket wrench, SW 5 (115.460) ·
 1 carrying case L-BOXX® 238 (414.093) ·
 1 case insert (407.895)



OSE 80-2 Palm sander with speed control Order no. 429.821

Power input	200 watt
No load speed	8000 - 13000 rpm
Orbit rate, no load	16000 - 26000 opm
Orbit	2,0 mm
Backing plate	80 x 130 mm
Sanding media fixing	velcro
Dust extraction connection	Ø 27 mm
Weight	1,2 kg


Standard Equipment:
 1 velcro backing plate, 80x130 8F (436.305) ·
 1 PES microfilter cartridge with filter (407.984)



X 1107 VE 710 watt random-orbit sander with dust extraction Order no. 218.669

Power input	710 watt
Power output	420 watt
Orbit	8,8 mm
Orbit rate, no load	4300-13000 opm
Max. disc diameter	150 mm
Sanding media fixing	velcro
Cable length	4,0 m
Weight	2,7 kg

Standard Equipment:
 1 side handle (194.034) ·
 1 open-ended wrench SW 14 (100.102) ·
 1 hexagon socket wrench, SW 4 (102.229) ·
 1 grip cover (239.771) ·
 1 velcro pad (hard) 150 Ø (228.176) ·
 Sanding tool starter set: 5 various grit sizes (1 set)



OSE 80-2 Set Palm sander with speed control in set Order no. 429.848

Power input	200 watt
No load speed	8000 - 13000 rpm
Orbit rate, no load	16000 - 26000 opm
Orbit	2,0 mm
Backing plate	80 x 130 mm
Sanding media fixing	velcro
Dust extraction connection	Ø 27 mm
Cable length	4,0 m
Weight	1,2 kg

Standard Equipment:
 1 velcro backing plate, 80x130 8F (436.305) ·
 1 PES microfilter cartridge with filter (407.984) ·
 1 sanding paper SELECTFLEX P 80 (1 piece of 380.776) ·
 1 sanding paper PURFLEX P 120 (1 piece of 380.903) ·
 1 carrying case L-BOXX® 136 (414.085) ·
 1 case insert (412.198)



MS 713 220 watt palm sander Order no. 332.380

Power input	220 watt
Power output	120 watt
Orbit rate, no load	14000 opm
Orbit	1,6 mm
Sand paper	115 x 105 mm
Sanding media fixing	velcro/clamp
Cable length	4,0 m
Weight	1,2 kg

Standard Equipment:
 1 paper punch (333.018) ·
 1 dust bag (332.992) ·
 1 adapter for dust extractor (333.026)



ODE 100-2 Delta sander with speed control Order no. 429.856


Power input	200 watt
No load speed	8000 - 13000 rpm
Orbit rate, no load	16000 - 26000 opm
Orbit	2,0 mm
Backing plate	100 x 150 mm
Sanding media fixing	velcro
Dust extraction connection	Ø 27 mm
Cable length	4,0 m
Weight	1,2 kg

Standard Equipment:
 1 velcro backing plate (436.321) ·
 1 PES microfilter cartridge with filter (407.984)



ODE 100-2 Set
Delta sander with speed control in set
Order no. 429.864

Power input 200 watt
No load speed 8000 - 13000 rpm
Orbit rate, no load 16000 - 26000 opm
Orbit 2,0 mm
Backing plate 100 x 150 mm
Sanding media fixing velcro
Dust extraction connection Ø 27 mm
Cable length 4,0 m
Weight 1,2 kg



Standard Equipment:
1 velcro backing plate (436.321) ·
1 PES microfilter cartridge with filter (407.984) ·
1 sanding paper SELECTFLEX P 80 (1 piece of 380.997) ·
1 sanding paper PURFLEX P 120 (1 piece of 381.136) ·
1 carrying case L-BOXX® 136 (414.085) ·
1 case insert (412.198)

Accessories for surface finishing sanding

Abrasives SFE 8-2 115



Velcro sanding paper PURFLEX

Designation	Dimensions in mm	Grit	QTY/ PKG	Order no.		
D115 PU-P24 VE25	115 Ø	P 24	25	381.195		
D115 PU-P40 VE50	115 Ø	P 40	50	381.209		
D115 PU-P60 VE50	115 Ø	P 60	50	381.217		
D115 PU-P80 VE50	115 Ø	P 80	50	381.225		
D115 PU-P100 VE50	115 Ø	P 100	50	381.233		
D115 PU-P120 VE50	115 Ø	P 120	50	381.241		
D115 PU-P150 VE50	115 Ø	P 150	50	381.268		
D115 PU-P180 VE50	115 Ø	P 180	50	381.276		



Velcro velours

Dimensions in mm	QTY/ PKG	Order no.		
80 Ø	1	296.155		

Abrasives Ø 125, Ø 150



Velcro sanding paper ZIRCOFLEX

Designation	Dimensions in mm	Grit	QTY/ PKG	Order no.		
D125-8 ZI-A40 VE25	125 Ø	A 40	25	393.185		
D125-8 ZI-A60 VE25	125 Ø	A 60	25	393.193		
D125-8 ZI-A80 VE25	125 Ø	A 80	25	393.207		



Velcro sanding paper CERAFLEX

Designation	Dimensions in mm	Grit	QTY/ PKG	Order no.		
D125 CE-K80 VE50	125 Ø	K 80	50	393.215		
D125 CE-K120 VE50	125 Ø	K 120	50	393.223		
D125 CE-K180 VE50	125 Ø	K 180	50	393.231		



Natural fibre felt pad

Designation	Dimensions in mm	Type	QTY/ PKG	Order no.		
FP D125 H VE5	125 Ø	hard	5	393.347		
FP D125 S VE5	125 Ø	soft	5	393.355		

Range of Products 2018




SC-Fleece velcro backed disc

Designation	Dimensions in mm	Grit	QTY/ PKG	Order no.		
D125 SC-C VE10	125 Ø	coarse	10	358.614		
D125 SC-M VE10	125 Ø	medium	10	358.622		
D125 SC-VF VE10	125 Ø	very fine	10	358.630		



Velcro sanding paper SELECTFLEX

Designation	Dimensions in mm	Grit	QTY/ PKG	Order no.		
D125-8 SE-P40 VE50	125 Ø	P 40	50	380.520		
D125-8 SE-P60 VE50	125 Ø	P 60	50	380.539		
D125-8 SE-P80 VE50	125 Ø	P 80	50	380.547		
D125-8 SE-P100 VE50	125 Ø	P 100	50	380.555		
D125-8 SE-P120 VE50	125 Ø	P 120	50	380.563		
D125-8 SE-P150 VE50	125 Ø	P 150	50	380.571		
D125-8 SE-P180 VE50	125 Ø	P 180	50	380.598		
D125-8 SE-P220 VE50	125 Ø	P 220	50	380.601		
D125-8 SE-P320 VE50	125 Ø	P 320	50	380.628		
D125-8 SE-P400 VE50	125 Ø	P 400	50	380.636		



Velcro sanding paper PURFLEX

Designation	Dimensions in mm	Grit	QTY/ PKG	Order no.		
D125-8 PU-P40 VE50	125 Ø	P 40	50	380.644		
D125-8 PU-P60 VE50	125 Ø	P 60	50	380.652		
D125-8 PU-P80 VE50	125 Ø	P 80	50	380.660		
D125-8 PU-P100 VE50	125 Ø	P 100	50	380.679		
D125-8 PU-P120 VE50	125 Ø	P 120	50	380.687		
D125-8 PU-P150 VE50	125 Ø	P 150	50	380.695		
D125-8 PU-P180 VE50	125 Ø	P 180	50	380.709		




Velcro sanding fleece MESHFLEX

Designation	Dimensions in mm	Grit	QTY/ PKG	Order no.		
D125 ME-A100 VE5	125 Ø	A 100	5	380.717		
D125 ME-A280 VE5	125 Ø	A 280	5	380.725		
D125 ME-S1500 VE5	125 Ø	S 1500	5	380.733		




Diamond sanding pad

Designation	Dimensions in mm	Grit	QTY/ PKG	Order no.		
DP 50 DRY D125	125 Ø	50	1	382.817		
DP 100 DRY D125	125 Ø	100	1	382.825		
DP 200 DRY D125	125 Ø	200	1	382.833		
DP 400 DRY D125	125 Ø	400	1	382.841		
DP 800 DRY D125	125 Ø	800	1	382.868		
DP 1500 DRY D125	125 Ø	1500	1	382.876		
DP 3000 DRY D125	125 Ø	3000	1	382.884		
DP 10000 DRY D125	125 Ø	10000	1	382.965		



Velcro sanding paper SELECTFLEX

Designation	Dimensions in mm	Grit	QTY/ PKG	Order no.		
D150-15 SE-P40 VE50	150 Ø	P 40	50	408.085		
D150-15 SE-P60 VE50	150 Ø	P 60	50	408.166		
D150-15 SE-P80 VE50	150 Ø	P 80	50	408.174		
D150-15 SE-P100 VE50	150 Ø	P 100	50	408.182		
D150-15 SE-P120 VE50	150 Ø	P 120	50	408.190		
D150-15 SE-P150 VE50	150 Ø	P 150	50	408.204		
D150-15 SE-P180 VE50	150 Ø	P 180	50	408.212		
D150-15 SE-P220 VE50	150 Ø	P 220	50	408.220		
D150-15 SE-P320 VE50	150 Ø	P 320	50	408.239		
D150-15 SE-P400 VE50	150 Ø	P 400	50	408.247		




Velcro sanding paper PURFLEX

Designation	Dimensions in mm	Grit	QTY/ PKG	Order no.		
D150-15 PU-P40 VE50	150 Ø	P 40	50	408.018		
D150-15 PU-P60 VE50	150 Ø	P 60	50	408.026		
D150-15 PU-P80 VE50	150 Ø	P 80	50	408.034		
D150-15 PU-P100 VE50	150 Ø	P 100	50	408.042		
D150-15 PU-P120 VE50	150 Ø	P 120	50	408.050		
D150-15 PU-P150 VE50	150 Ø	P 150	50	408.069		
D150-15 PU-P180 VE50	150 Ø	P 180	50	408.077		



Velcro sanding fleece MESHFLEX


Designation	Dimensions in mm	Grit	QTY/ PKG	Order no.		
D150 ME-A100 VE5	150 Ø	A 100	5	408.255		
D150 ME-A280 VE5	150 Ø	A 280	5	408.263		
D150 ME-S1500 VE5	150 Ø	S 1500	5	408.271		



Diamond sanding pad

Designation	Dimensions in mm	Grit	QTY/ PKG	Order no.		
DP 30 DRY D150	150 Ø	30	1	418.951		
DP 50 DRY D150	150 Ø	50	1	418.978		
DP 100 DRY D150	150 Ø	100	1	418.986		
DP 200 DRY D150	150 Ø	200	1	418.994		
DP 400 DRY D150	150 Ø	400	1	419.001		
DP 800 DRY D150	150 Ø	800	1	419.028		
DP 1500 DRY D150	150 Ø	1500	1	419.036		
DP 3000 DRY D150	150 Ø	3000	1	419.044		
DP 10000 DRY D150	150 Ø	10000	1	419.052		


Abrasives XS 713



Velcro sanding paper PURFLEX


Designation	Dimensions in mm	Grit	QTY/ PKG	Order no.		
D125-XS PU-P40 VE25	125 Ø	P 40	25	334.308		
D125-XS PU-P60 VE25	125 Ø	P 60	25	334.324		
D125-XS PU-P80 VE25	125 Ø	P 80	25	334.340		
D125-XS PU-P100 VE25	125 Ø	P 100	25	318.027		
D125-XS PU-P120 VE25	125 Ø	P 120	25	317.993		
D125-XS PU-P180 VE25	125 Ø	P 180	25	318.000		
D125-XS PU-P220 VE25	125 Ø	P 220	25	318.019		

Abrasives OSE 80-2




Velcro sanding paper SELECTFLEX

Designation	Dimensions in mm	Grit	QTY/ PKG	Order no.		
80x133 SE-P40 VE50	80 x 133	P 40	50	380.741		
80x133 SE-P60 VE50	80 x 133	P 60	50	380.768		
80x133 SE-P80 VE50	80 x 133	P 80	50	380.776		
80x133 SE-P100 VE50	80 x 133	P 100	50	380.784		
80x133 SE-P120 VE50	80 x 133	P 120	50	380.792		
80x133 SE-P150 VE50	80 x 133	P 150	50	380.806		
80x133 SE-P180 VE50	80 x 133	P 180	50	380.814		
80x133 SE-P220 VE50	80 x 133	P 220	50	380.822		
80x133 SE-P320 VE50	80 x 133	P 320	50	380.830		
80x133 SE-P400 VE50	80 x 133	P 400	50	380.849		



Velcro sanding paper PURFLEX


Designation	Dimensions in mm	Grit	QTY/ PKG	Order no.		
80x133 PU-P40 VE50	80 x 133	P 40	50	380.857		
80x133 PU-P60 VE50	80 x 133	P 60	50	380.865		
80x133 PU-P80 VE50	80 x 133	P 80	50	380.873		
80x133 PU-P100 VE50	80 x 133	P 100	50	380.881		
80x133 PU-P120 VE50	80 x 133	P 120	50	380.903		
80x133 PU-P150 VE50	80 x 133	P 150	50	380.911		
80x133 PU-P180 VE50	80 x 133	P 180	50	380.938		



Velcro sanding fleece MESHFLEX

Designation	Dimensions in mm	Grit	QTY/ PKG	Order no.		
80x133 ME-A100 VE5	80 x 133	A 100	5	380.946		
80x133 ME-A280 VE5	80 x 133	A 280	5	380.954		
80x133 ME-S1500 VE5	80 x 133	S 1500	5	380.962		

Abrasives MS 713



Velcro sanding paper PURFLEX

Designation	Dimensions in mm	Grit	QTY/ PKG	Order no.		
115x105 PU-P40 VE25	115 x 105	P 40	25	334.251		
115x105 PU-P60 VE25	115 x 105	P 60	25	334.286		
115x105 PU-P80 VE25	115 x 105	P 80	25	332.771		
115x105 PU-P100 VE25	115 x 105	P 100	25	332.798		
115x105 PU-P120 VE25	115 x 105	P 120	25	332.801		
115x105 PU-P180 VE25	115 x 105	P 180	25	332.828		
115x105 PU-P220 VE25	115 x 105	P 220	25	332.836		

Abrasives ODE 100-2



Velcro sanding paper SELECTFLEX

Designation	Dimensions in mm	Grit	QTY/ PKG	Order no.		
100x150 SE-P40 VE50	100 x 150	P 40	50	380.970		
100x150 SE-P60 VE50	100 x 150	P 60	50	380.989		
100x150 SE-P80 VE50	100 x 150	P 80	50	380.997		
100x150 SE-P100 VE50	100 x 150	P 100	50	381.004		
100x150 SE-P120 VE50	100 x 150	P 120	50	381.012		
100x150 SE-P150 VE50	100 x 150	P 150	50	381.020		
100x150 SE-P180 VE50	100 x 150	P 180	50	381.039		
100x150 SE-P220 VE50	100 x 150	P 220	50	381.047		
100x150 SE-P320 VE50	100 x 150	P 320	50	381.055		
100x150 SE-P400 VE50	100 x 150	P 400	50	381.063		



Velcro sanding paper PURFLEX

Designation	Dimensions in mm	Grit	QTY/ PKG	Order no.		
100x150 PU-P40 VE50	100 x 150	P 40	50	381.071		
100x150 PU-P60 VE50	100 x 150	P 60	50	381.098		
100x150 PU-P80 VE50	100 x 150	P 80	50	381.101		
100x150 PU-P100 VE50	100 x 150	P 100	50	381.128		
100x150 PU-P120 VE50	100 x 150	P 120	50	381.136		
100x150 PU-P150 VE50	100 x 150	P 150	50	381.144		
100x150 PU-P180 VE50	100 x 150	P 180	50	381.152		



Velcro sanding fleece MESHFLEX

Designation	Dimensions in mm	Grit	QTY/ PKG	Order no.		
100x150 ME-A100 VE5	100 x 150	A 100	5	381.160		
100x150 ME-A280 VE5	100 x 150	A 280	5	381.179		
100x150 ME-S1500 VE5	100 x 150	S 1500	5	381.187		

Accessories SUPRAFLEX SE 14-2 125 / 150



Paint Set

Designation	QTY/ PKG	Order no.		
P-Box SE 14-2 125	1 set	393.436		



Paint Set

Designation	QTY/ PKG	Order no.		
Paint-Set D150	1 set	408.468		

Range of Products 2018



Inox Set

Designation	QTY/ PKG	Order no.		
I-Box SE 14-2 125	1 set	393.428		



Antistatic suction hose with auxiliary air control

Designation	QTY/ PKG	Order no.		
SH-C 32x4m AS/NL	1	406.708		



Stone Set

Designation	QTY/ PKG	Order no.		
S-Box SE 14-2 125	1 set	393.444		



Side handgrip

Designation	QTY/ PKG	Order no.		
GS-S SE14-2	1	391.581		



Velcro backing pad

Designation	Dimensions in mm	QTY/ PKG	Order no.		
SP D125-8 H/F	125 Ø	1	391.727		
SP D150-8/6 H/F	150 Ø	1	419.192		



Clamping flange

Designation	QTY/ PKG	Order no.		
CF SE 14-2	1	393.371		



Disc brush

Designation	Tool fixture	QTY/ PKG	Order no.		
BT-NY D130/50 P46 M14	M 14	1	409.030		



Clamping nut M 14

Designation	QTY/ PKG	Order no.		
	1	100.080		



Dust guard with pivoting edge segment

Designation	Dimensions in mm	QTY/ PKG	Order no.		
SG-R D125 SE	125 Ø	1	393.363		



FixTec quick clamp nut M 14

Designation	QTY/ PKG	Order no.		
	1	313.459		



Dust guard with pivoting edge segment

Designation	Dimensions in mm	QTY/ PKG	Order no.		
SG-R D150 SE	150 Ø	1	419.176		



Face pin spanner

Designation	QTY/ PKG	Order no.		
Wrench, face spanner 35x5 gek	1	398.365		



Brush ring

Designation	Dimensions in mm	QTY/ PKG	Order no.		
BK-H SE 14-2 125	125 Ø	1	394.076		
BK-H SE 14-2 125 VE3	125 Ø	3	421.138		
BK-H SE 14-2 150	150 Ø	1	419.184		
BK-H SE 14-2 150 VE3	150 Ø	3	421.146		



Hexagon socket wrench

Designation	QTY/ PKG	Order no.		
SW 6	1	104.167		
SW 5 long	1	392.731		
SW 4	1	102.229		



Carrying case L-BOXX®

Designation	External dimensions L x W x H	Internal dimensions L x W x H	Weight	QTY/ PKG	Order no.		
TK-L 102	442 x 357 x 117 mm	378 x 313 x 71 mm	2,1 kg	1	414.077		
TK-L 238	442 x 357 x 253 mm	378 x 306 x 209 mm	2,8 kg	1	414.093		

Case insert

Designation	QTY/ PKG	Order no.		
TKE 4x D130/1x 135x295	1	414.166		
TKE SE 14-2 125/150	1	414.158		


Accessories ORE 125-2



Velcro backing pad


Designation	Dimensions in mm	QTY/ PKG	Order no.		
SP D125-8	125 Ø	1	379.379*		
SP D125-8 (FL)	125 Ø	1	436.348		

Accessories ORE 150-3/ORE 150-5



Velcro sanding pad soft


Designation	Dimensions in mm	QTY/ PKG	Order no.		
SP-S D150	150 Ø	1	408.298		



Velcro sanding pad hard

Designation	Dimensions in mm	QTY/ PKG	Order no.		
SP-H D150	150 Ø	1	408.301		

Accessories OSE 80-2



Velcro backing pad

Designation	Dimensions in mm	QTY/ PKG	Order no.		
SP 80x133-8F	80 x 130	1	379.344*		
SP 80x133-8F (FL)	80 x 130	1	436.305		

Accessories ODE 100-2



Velcro backing pad Delta

Designation	Dimensions in mm	QTY/ PKG	Order no.		
SP 100x150-7	100 x 150	1	379.360*		
SP 100x150-7 (FL)	100 x 150	1	436.321		

Other accessories OSE, ODE, ORE




PES microfilter cartridge

Designation	QTY/ PKG	Order no.		
FP E D27	1	407.984		



PES microfilter

Designation	QTY/ PKG	Order no.		
PF-PES	1	407.992		



Paper filter bags

Designation	QTY/ PKG	Order no.		
FT-ODE/ODE/ORE VE5	5	379.336		



Antistatic suction hose

Designation	Dimensions in mm	QTY/ PKG	Order no.		
SH 27x4m AS	27 Ø x 4m	1	379.395		



Adapter

Designation	QTY/ PKG	Order no.		
SAD 27 AS	1	382.736		

* for machines with order no. 379.xxx

Range of Products 2018



Carrying case L-BOXX®

Designation	External dimensions L x W x H	Internal dimensions L x W x H	Weight	QTY/ PKG	Order no.		
TK-L 136	442 x 357 x 151 mm	378 x 311 x 107 mm	2,2 kg	1	414.085		
TK-L 238	442 x 357 x 253 mm	378 x 306 x 209 mm	2,8 kg	1	414.093		

Case insert


Designation	QTY/ PKG	Order no.		
TKE ORE 150	1	407.895		
TKE 4x D150	1	407.704		
TKE OSE/ODE/ORE 125	1	412.198		

Accessories LK 604, LG 1704 VR



Flexible backing pad with clamping nut M 14

Dimensions in mm	QTY/ PKG	Order no.		
170 Ø	1	124.079		



Clamping nut M 14

QTY/ PKG	Order no.		
1	124.109		

Accessories XS 713



Velcro backing pad

Dimensions in mm	QTY/ PKG	Order no.		
125 Ø	1	334.146		

Accessories X 1107 VE



Velcro backing pad


Designation	Dimensions in mm	Grit	QTY/ PKG	Order no.		
SP-H D150-6 X1107	150 Ø	hard	1	228.176		
SP-S D150-6 X1107	150 Ø	soft	1	228.184		

Renovation machines



WST 1000 FV
Concrete-Giraffe® grinder for walls and ceilings

Disc Ø	125 mm
No load speed	8000 rpm
Power input	1010 watt
Power output	600 watt
Tool fixture	28 mm Ø
Dimensions in mm	1330-1650
Cable length	5,0 m
Weight	5,5 kg



Standard Equipment:
1 FixTec quick-clamp nut M 14 (313.459) ·
Antistatic suction hose 32 mm Ø x 4 m
with snap coupling and coupling bush for
vacuum cleaner (406.708) ·
1 carrying case (389.986)



WST 1000 FV, Turbo-Jet kit
Order no. 355.747

Standard Equipment:
WST 1000 FV + 1 Turbo-Jet grinding disc
(349.623)



WST 1000 FV, Thermo-Whirljet kit
Order no. 355.755

Standard Equipment:
WST 1000 FV + 1 Thermo-Whirljet
(323.071)



WST 1000 FV, Screed-Whirljet kit
Order no. 355.763

Standard Equipment:
WST 1000 FV + 1 Screed-Whirljet
(324.361)



WST 1000 FV, Concrete-Whirljet kit
Order no. 355.771

Standard Equipment:
WST 1000 FV + 1 Concrete-Whirljet
(323.063)



RE 14-5 115 RETECFLEX - the universal tool for renovation and modernization

Max. disc diameter	115 mm
Max. milling head Ø	80 mm
No load speed	1800-5200 rpm
Power input	1400 watt
Power output	880 watt
Tool fixture	M 14
Size (W x L x H)	340x185x145 mm
Cable length	4,0 m
Weight	3,1 kg



Kit
System

Standard Equipment:
1 SoftVib handle (325.376) ·
1 extractor guard grinding Ø 115 mm with
a brush ring (366.528) ·
1 adjustable base scouring Ø 80 mm
(366.897) ·
1 velcro backing pad Bowl Ø 115/M14
(366.609) ·
Corundum sanding disc set Ø 115 (1 set) ·
1 pin wrench (366.536) ·
1 hexagon socket wrench, SW 4
(102.229) ·
1 carrying case L-BOXX® 238 (414.093) ·
1 case insert (414.182)



RE 14-5 115, pointed scouring head kit Order no. 369.217

Standard Equipment:
RE 14-5 115 + 1 pointed scouring head
Ø 80, M 14 (366.552)



RE 14-5 115, flat scouring head kit Order no. 369.225

Standard Equipment:
RE 14-5 115 + 1 scouring head, flat,
Ø 80, M 14 (366.560)



RE 14-5 115, Kit B-Jet Order no. 369.233

Standard Equipment:
RE 14-5 115 + 1 Concrete-Jet diamond
grinding disc (418.757)



RE 14-5 115, Kit E-Jet Order no. 369.241

Standard Equipment:
RE 14-5 115 + 1 Screed-Jet diamond
grinding disc (418.803)



LD 15-10 125 Compact renovation grinder for dust- free grinding, 125 mm

Disc Ø	125 mm
No load speed	10000 rpm
Power input	1450 watt
Power output	950 watt
Vibration	< 6,4 m/s ²
Tool fixture	M 14
Cable length	4,0 m
Weight	3,2 kg



Kit
System

Standard Equipment:
1 extraction hood with rubber extraction
ring (421.111) ·
1 bail handle (1 piece) ·
3 cable clips (252.188 (3x)) ·
1 hexagon socket wrench, SW 4
(102.229) ·
1 extraction adapter SAD-C D25-32 AS
(320.188) ·
1 pin wrench (392.537) ·
1 carrying case L-BOXX® 238 (414.093) ·
1 case insert (414.131)



LD 15-10 125, Kit Turbo-Jet Order no. 405.914

Standard Equipment:
LD 15-10 125 + 1 Turbo-Jet grinding disc
(348.899)



LD 15-10 125, Kit TH-Jet Order no. 405.930

Standard Equipment:
LD 15-10 125 + 1 Thermo-Jet diamond
grinding disc (359.378)



LD 15-10 125, Kit E-Jet Order no. 405.957

Standard Equipment:
LD 15-10 125 + 1 Screed-Jet diamond
grinding disc (359.394)

Range of Products 2018



LD 15-10 125 R Compact renovation grinder for dust-free grinding close to edges, 125 mm

Disc Ø	125 mm
No load speed	10000 rpm
Power input	1450 watt
Power output	950 watt
Vibration	< 6,4 m/s ²
Tool fixture	M 14
Cable length	4,0 m
Weight	2,9 kg



Standard Equipment:
 1 dust extraction hood with brush ring (393.363) ·
 1 bail handle (1 piece) ·
 3 cable clips (252.188 (3x)) ·
 1 hexagon socket wrench, SW 4 (102.229) ·
 1 extraction adapter SAD-C D32 AS (393.398) ·
 1 pin wrench (392.537) ·
 1 carrying case L-BOXX® 238 (414.093) ·
 1 case insert (414.131)



LD 18-7 125 R 1800 watt powerful grinding machine for working close to edges, 125 mm

Disc Ø	125 mm
No load speed	7000 rpm
Power input	1800 watt
Power output	1200 watt
Tool fixture	M 14
Cable length	4,0 m
Weight	4,2 kg



Standard Equipment:
 1 dust extraction hood with brush ring (393.363) ·
 1 bail handle (1 piece) ·
 3 cable clips (252.188 (3x)) ·
 1 hexagon socket wrench (102.229) ·
 1 extraction adapter (340.790) ·
 1 pin wrench (392.537) ·
 1 clamping nut M14 (100.080) ·
 1 carrying case (444.391)



LD 15-10 125 R, Kit Turbo-Jet Order no. 405.906

Standard Equipment:
 LD 15-10 125 R + 1 Turbo-Jet grinding disc (348.899)



LD 18-7 125 R, Kit Turbo-Jet Order no. 408.603

Standard Equipment:
 LD 18-7 125 R + 1 Turbo-Jet grinding disc (348.899)



LD 15-10 125 R, Kit TH-Jet Order no. 405.922

Standard Equipment:
 LD 15-10 125 R + 1 Thermo-Jet diamond grinding disc (359.378)



LD 18-7 125 R, Kit TH-Jet Order no. 408.611

Standard Equipment:
 LD 18-7 125 R + 1 Thermo-Jet diamond grinding disc (359.378)



LD 15-10 125 R, Kit E-Jet Order no. 405.949

Standard Equipment:
 LD 15-10 125 R + 1 Screed-Jet diamond grinding disc (359.394)



LD 18-7 125 R, Kit E-Jet Order no. 408.638

Standard Equipment:
 LD 18-7 125 R + 1 Screed-Jet diamond grinding disc (359.394)



LD 18-7 150 R 1800 watt powerful grinding machine for working close to edges, 150 mm

Disc Ø	150 mm
No load speed	7000 rpm
Power input	1800 watt
Power output	1200 watt
Tool fixture	M 14
Cable length	4,0 m
Weight	4,3 kg



Standard Equipment:
 1 dust extraction hood with brush ring (419.176) ·
 1 bail handle (1 piece) ·
 3 cable clips (252.188 (3x)) ·
 1 hexagon socket wrench (102.229) ·
 1 clamping nut M14 (100.080) ·
 1 pin wrench (392.537) ·
 1 carrying case (444.391)



LD 24-6 180 Grinding machine for large areas, 180 mm

Disc Ø	180 mm
No load speed	6500 rpm
Power input	2400 watt
Power output	1450 watt
Tool fixture	M 14
Cable length	4,0 m
Weight	6,6 kg



Standard Equipment:
 1 extraction hood with rubber extraction ring (421.154) ·
 1 extraction adapter (393.398) ·
 1 clamping nut M14 (100.080) ·
 1 clamping flange SW 17 (191.604) ·
 1 bail handle (1 piece) ·
 3 cable clips (302.538 (3x)) ·
 1 hexagon socket wrench, SW 6 (256.832) ·
 1 pin wrench (392.537) ·
 1 carrying case (444.391)



LD 18-7 150 R, Kit Turbo-Jet Order no. 418.765

Standard Equipment:
 LD 18-7 150 R + 1 Turbo-Jet grinding disc (418.935)



LD 18-7 150 R, Kit TH-Jet Order no. 418.773

Standard Equipment:
 LD 18-7 150 R + 1 Thermo-Jet diamond grinding disc (418.919)




LD 18-7 150 R, Kit E-Jet Order no. 418.781

Standard Equipment:
 LD 18-7 150 R + 1 Screed-Jet diamond grinding disc (418.927)



LD 24-6 180, Kit Turbo-Jet Order no. 420.514

Standard Equipment:
 LD 24-6 180 + 1 Turbo-Jet grinding disc (420.409)



LD 24-6 180, Kit TH-Jet Order no. 418.870

Standard Equipment:
 LD 24-6 180 + 1 Thermo-Jet diamond grinding disc (359.386)



LD 24-6 180, Kit E-Jet Order no. 418.862

Standard Equipment:
 LD 24-6 180 + 1 Screed-Jet diamond grinding disc (359.408)

Range of Products 2018

Accessories for renovation grinder, scoring

Accessories for WST 1000 FV scourer



Turbo-Jet diamond grinding disc

Designation	Dimensions in mm	QTY/ PKG	Order no.		
Turbo-Jet D125 28x23,5	125 Ø x 28 x 23,5	1	349.623		




Thermo-Whirljet diamond grinding disc

Designation	Dimensions in mm	QTY/ PKG	Order no.		
TH-Whirljet D125 28x23,5	125 Ø x 28 x 23,5	1	323.071		



Screed-Whirljet diamond grinding disc

Designation	Dimensions in mm	QTY/ PKG	Order no.		
E-Whirljet D125 28x23,5	125 Ø x 28 x 23,5	1	324.361		



Concrete-Whirljet diamond grinding disc

Designation	Dimensions in mm	QTY/ PKG	Order no.		
B-Whirljet D125 28x23,5	125 Ø x 28 x 23,5	1	323.063		



Rubber extraction ring

Dimensions in mm	QTY/ PKG	Order no.			
125 Ø	1	257.246			



Concrete grinder head without disc

Designation	Dimensions in mm	QTY/ PKG	Order no.		
VSF D125	125 Ø	1	350.931		



Antistatic suction hose with auxiliary air control

Designation	QTY/ PKG	Order no.			
SH-C 32x4m AS/NL	1	406.708			



Fast clip adapter

Designation	QTY/ PKG	Order no.			
SAD-FC 32	1	410.497			



Carrying case

Designation	QTY/ PKG	Order no.			
TK-S WST/WSE 7	1	389.986			

Accessories RETECFLEX



Velcro backing pad Ø 115, Bowl

Dimensions in mm	QTY/ PKG	Order no.			
115 Ø	1	366.609			




Velcro sanding paper PURFLEX

Designation	Dimensions in mm	Grit	QTY/ PKG	Order no.		
D115 PU-P24 VE25	115 Ø	P 24	25	381.195		
D115 PU-P40 VE50	115 Ø	P 40	50	381.209		
D115 PU-P60 VE50	115 Ø	P 60	50	381.217		
D115 PU-P80 VE50	115 Ø	P 80	50	381.225		
D115 PU-P100 VE50	115 Ø	P 100	50	381.233		
D115 PU-P120 VE50	115 Ø	P 120	50	381.241		
D115 PU-P150 VE50	115 Ø	P 150	50	381.268		
D115 PU-P180 VE50	115 Ø	P 180	50	381.276		



Diamond sanding pad

Designation	Dimensions in mm	Grit	QTY/ PKG	Order no.		
DP 50 DRY D115	115 Ø	50	1	386.197		
DP 100 DRY D115	115 Ø	100	1	386.200		
DP 200 DRY D115	115 Ø	200	1	386.219		
DP 400 DRY D115	115 Ø	400	1	386.227		
DP 800 DRY D115	115 Ø	800	1	386.235		
DP 1500 DRY D115	115 Ø	1500	1	386.243		
DP 3000 DRY D115	115 Ø	3000	1	386.251		
DP 10000 DRY D115	115 Ø	10000	1	386.278		



Base for scouring work

Diameter in mm	QTY/ PKG	Order no.		
80 Ø	1	369.314		



Dust extraction guard

Diameter in mm	QTY/ PKG	Order no.		
115 Ø	1	366.528		



Brush ring

Designation	Dimensions in mm	QTY/ PKG	Order no.		
BK-H RE14-5-115	115 Ø	1	369.454		



SoftVib side handle

Designation	Type	QTY/ PKG	Order no.		
GS-M M8 SV	M 8	1	325.376		



Face pin spanner

	QTY/ PKG	Order no.		
	1	366.536		



Carrying case L-BOXX®

Designation	External dimensions L x W x H	Internal dimensions L x W x H	Weight	QTY/ PKG	Order no.		
TK-L 238	442 x 357 x 253 mm	378 x 306 x 209 mm	2,8 kg	1	414.093		

Case insert

Designation	QTY/ PKG	Order no.		
TKE RE 14-5	1	414.182		



Carrying case L-BOXX®

Designation	External dimensions L x W x H	Internal dimensions L x W x H	Weight	QTY/ PKG	Order no.		
TK-L 102	442 x 357 x 117 mm	378 x 313 x 71 mm	2,1 kg	1	414.077		

Case insert

Designation	QTY/ PKG	Order no.		
TKE 4x D130/1x 135x295	1	414.166		



Clip adapter

Designation	QTY/ PKG	Order no.		
SAD-C D36/27 AS/NL	1	408.360		



Fast clip adapter

Designation	QTY/ PKG	Order no.		
SAD-FC 32	1	410.497		



„Perforator“ tool head with HSS cutting wheels

Dimensions in mm	QTY/ PKG	Order no.		
80 Ø	1	366.757		



HSS cutting wheels

Dimensions in mm	QTY/ PKG	Order no.		
38 Ø	4	366.765		



Scouring head complete, pointed

Dimensions in mm	QTY/ PKG	Order no.		
80 Ø	1	366.552		

Range of Products 2018



TC scouring discs, pointed

QTY/ PKG	Order no.		
1 set	366.501		



TC-Jet carbide grinding disc

Designation	Dimensions in mm	QTY/ PKG	Order no.		
TC-Jet D115 C M14	115 Ø	1	418.897		



Scouring head complete, flat

Dimensions in mm	QTY/ PKG	Order no.		
80 Ø	1	366.560		



Turbo-Jet diamond grinding disc

Designation	Dimensions in mm	QTY/ PKG	Order no.		
Turbo-Jet D115 C M14	115 Ø	1	418.846		



TC scouring discs, flat

QTY/ PKG	Order no.		
1 set	366.617		

Accessories for renovation sander LD... Ø 125 / Ø 150 / Ø 180



Thermo-Jet diamond grinding disc

Designation	Dimensions in mm	QTY/ PKG	Order no.		
TH-Jet D125 22,2	125 Ø	1	359.378		
TH-Jet D150 22,2	150 Ø	1	418.919		
TH-Jet D180 22,2	180 Ø	1	359.386		



Concrete-Jet diamond grinding disc

Designation	Dimensions in mm	QTY/ PKG	Order no.		
B-Jet D115 C M14	115 Ø	1	418.757		



Screed-Jet diamond grinding disc

Designation	Dimensions in mm	QTY/ PKG	Order no.		
E-Jet D125 22,2	125 Ø	1	359.394		
E-Jet D150 22,2	150 Ø	1	418.927		
E-Jet D180 22,2	180 Ø	1	359.408		



Screed-Jet diamond grinding disc

Designation	Dimensions in mm	QTY/ PKG	Order no.		
E-Jet D115 C M14	115 Ø	1	418.803		



Surface-Jet diamond grinding disc

Designation	Dimensions in mm	QTY/ PKG	Order no.		
S-Jet D115 C M14	115 Ø	1	418.811		



Surface-Jet diamond grinding disc

Designation	Dimensions in mm	QTY/ PKG	Order no.		
S-Jet D125 22,2	125 Ø	1	359.424		



PCD grinding disc

Designation	Dimensions in mm	QTY/ PKG	Order no.		
PKD-Jet 4-Cut D115 C M14	115 Ø	1	418.889		



PCD grinding disc

Designation	Dimensions in mm	QTY/ PKG	Order no.		
PKD-Jet D125 22,2	125 Ø	1	359.416		



PCD grinding disc

Designation	Dimensions in mm	QTY/ PKG	Order no.		
PKD-Jet 5-Cut D125 22,2	125 Ø	1	406.015		
PKD-Jet 6-Cut D150 22,2	150 Ø	1	418.943		
PKD-Jet 6-Cut D180 22,2	180 Ø	1	420.425		

Guard with rubber extraction ring

Designation	Dimensions in mm	QTY/ PKG	Order no.		
SG D125 LD	125 Ø	1	421.111		
SG D180 LD	180 Ø	1	421.154		



Turbo-Jet diamond grinding disc

Designation	Dimensions in mm	QTY/ PKG	Order no.		
Turbo-Jet II D125 22,2	125 Ø	1	453.773		
Turbo-Jet D125 22,2	125 Ø	1	348.899		
Turbo-Jet D150 22,2	150 Ø	1	418.935		
Turbo-Jet D180 22,2	180 Ø	1	420.409		



Rubber extraction ring

Dimensions in mm	QTY/ PKG	Order no.		
125 Ø	1	257.246		
180 Ø	1	258.626		



Diamond grinding disc

Designation	Dimensions in mm	QTY/ PKG	Order no.		
Basic-Cut D125 22,2	125 Ø	1	420.417		



Carrying case L-BOXX®

Designation	External dimensions L x W x H	Internal dimensions L x W x H	Weight	QTY/ PKG	Order no.		
TK-L 102	442 x 357 x 117 mm	378 x 313 x 71 mm	2,1 kg	1	414.077		
TK-L 136	442 x 357 x 151 mm	378 x 311 x 107 mm	2,2 kg	1	414.085		
TK-L 238	442 x 357 x 253 mm	378 x 306 x 209 mm	2,8 kg	1	414.093		

Accessories for LD 15-10 125 / R and LD 18-7 125 R / 150 R, LD 24-6 180



Dust guard with pivoting edge segment

Designation	Dimensions in mm	QTY/ PKG	Order no.		
SG-R D125 SE	125 Ø	1	393.363		

Case insert

Designation	QTY/ PKG	Order no.		
TKE LD 15-10 125	1	414.131		
TKE 4x D130/1x 135x295	1	414.166		
TKE 4x D150	1	407.704		



Dust guard with pivoting edge segment

Designation	Dimensions in mm	QTY/ PKG	Order no.		
SG-R D150 SE	150 Ø	1	419.176		



Carrying case

Designation	Weight	QTY/ PKG	Order no.		
TK-S L230/LD180/LD150	4,0 kg	1	444.391		



Brush ring

Designation	Dimensions in mm	QTY/ PKG	Order no.		
BK-H SE 14-2 125	125 Ø	1	394.076		
BK-H SE 14-2 125 VE3	125 Ø	3	421.138		
BK-H SE 14-2 150	150 Ø	1	419.184		
BK-H SE 14-2 150 VE3	150 Ø	3	421.146		


Range of Products 2018

Special tools



MS 1706 FR Set Wall chaser for push and pull cutting Order no. 329.673

Cutting depth	0-35 mm
Groove width	10-30 mm
Disc Ø	140 mm
No load speed	7500 rpm
Power input	1400 watt
Power output	950 watt
Tool fixture	M 14
Cable length	4,0 m
Weight	4,6 kg



Standard Equipment:
 2 Diamantjet VI-Speedcut-cutting disc
 140 mm Ø (334.464 (2x)) ·
 1 side handle (194.034) ·
 1 SDS-Clc quick-clamp nut M 14
 (253.049) ·
 Distance spacers (251.478 (1x)) ·
 Stacking discs (318.914 (2x)) ·
 Clamping flanges (191.612 (2x)) ·
 1 web remover (229.253) ·
 1 extraction adapter (408.360) ·
 Cable clip (252.188 (3x)) ·
 1 carrying case (327.034)



F 1109 710 watt gutter support groove cutter Order no. 251.338


Power input	710 watt
Power output	420 watt
No load speed	10000 rpm
Planer width	40 mm
Planer depth	6 / 8 mm
No. of cutters	4 pieces
Tool fixture	M 14
Cable length	4,0 m
Weight	3,9 kg



Standard Equipment:
 1 set HHS reversible cutters (4 pieces)
 (241.091) ·
 1 torx wrench (258.861) ·
 1 open-ended wrench SW 30/17
 (106.461) ·
 1 carrying case L-BOXX® 238 (414.093) ·
 1 case insert (434.248)

Accessories for special tools

Accessories MS 1706 FR Set



Diamantjet VI - Speedcut

Dimensions in mm	QTY/ PKG	Order no.		
140 Ø	1	334.464		



Clip adapter

Designation	QTY/ PKG	Order no.		
SAD-C D36/27 AS/NL	1	408.360		



Fast clip adapter

Designation	QTY/ PKG	Order no.		
SAD-FC 32	1	410.497		

Accessories F 1109



HM reversible blades

Dimensions in mm	QTY/ PKG	Order no.		
21 x 21	4	229.555		



HSS reversible blades

Dimensions in mm	QTY/ PKG	Order no.		
21 x 21	4	241.091		



Carrying case L-BOXX®

Designa- tion	External dimensions L x W x H	Internal dimensions L x W x H	Weight	QTY/ PKG	Order no.		
TK-L 238	442 x 357 x 253 mm	378 x 306 x 209 mm	2,8 kg	1	414.093		

Case insert

Designation	QTY/ PKG	Order no.		
TKE F1109	1	434.248		


Rotary hammer drills



FHE 2-22 SDS-plus Rotary hammer drill, 2,3 kg, SDS-plus Order no. 413.674

No load speed	0-1400 rpm
Blows per minute	0-4300 bpm
Single impact energy (EPTA)	2,1 J
Max. drill hole Ø in concrete	22 mm
Max. drill hole Ø in steel	13 mm
Max. drill hole Ø in wood	26 mm
Power input	710 watt
Tool fixture	SDS-plus
Cable length	4,0 m
Weight	2,3 kg

Standard Equipment:
1 handle (416.126) ·
1 drill depth stop (416.118) ·
1 carrying case L-BOXX® 136 (414.085) ·
1 case insert (414.042)



CHE 5-40 SDS-max Universal rotary hammer drill, 5 kg, SDS-max Order no. 439.665

No load speed	0-380 rpm
Blows per minute	1300-2900 bpm
Single impact energy (EPTA)	10 J
Chisel positions	12
Max. drill hole Ø in concrete	40 mm
Max. drill hole Ø in masonry (drill bit)	90 mm
Max. drill hole Ø in steel	13 mm
Max. drill hole Ø in wood	32 mm
Power input	1050 watt
Tool fixture	SDS-max
Cable length	4,0 m
Weight	6,4 kg

Standard Equipment:
1 handle (1 piece) ·
1 carrying case (1 piece)



CHE 2-28 SDS-plus Universal rotary hammer drill, 2,5 kg, SDS-plus Order no. 413.666

No load speed	0-1300 rpm
Blows per minute	0-4000 bpm
Single impact energy (EPTA)	2,7 J
Max. drill hole Ø in concrete	26 mm
Max. drill hole Ø in steel	13 mm
Max. drill hole Ø in wood	30 mm
Power input	800 watt
Tool fixture	SDS-plus
Cable length	4,0 m
Weight	2,65 kg


Standard Equipment:
1 handle (417.661) ·
1 drill depth stop (417.769) ·
1 carrying case L-BOXX® 136 (414.085) ·
1 case insert (414.042)



DH 5 SDS-max Demolition hammer, 5 kg, SDS-max Order no. 365.920

Blows per minute	3500 bpm
Power input	1050 watt
Single impact energy (EPTA)	6,7 J
Chisel positions	12
Tool fixture	SDS-max
Cable length	4,0 m
Weight	5 kg

Standard Equipment:
1 handle (370.916) ·
1 tube of grease (370.894) ·
1 carrying case (402.583)



CHE 4-32 SDS-plus Universal rotary hammer drill, 4 kg, SDS-plus Order no. 428.337

No load speed	0-850 rpm
Blows per minute	0-3700 bpm
Single impact energy (EPTA)	4,8 J
Max. drill hole Ø in concrete	32 mm
Max. drill hole Ø in masonry (drill bit)	82 mm
Max. drill hole Ø in steel	13 mm
Max. drill hole Ø in wood	32 mm
Power input	900 watt
Tool fixture	SDS-plus
Cable length	4,0 m
Weight	4,6 kg

Standard Equipment:
1 handle (436.232) ·
1 drill depth stop (436.062) ·
1 carrying case L-BOXX® 238 (414.093) ·
1 case insert (429.104)

Range of Products 2018

Accessories for rotary hammer drills

Accessories SDS-plus



SDS 2-plus drill

Designation	Diameter in mm	Length in mm	QTY/ PKG	Order no.		
HD 2-C D4x110 SDS-plus	4	110	1	367.931		
HD 2-C D5x110 SDS-plus	5	110	1	367.958		
HD 2-C D6x110 SDS-plus	6	110	1	367.966		
HD 2-C D5x160 SDS-plus	5	160	1	367.974		
HD 2-C D6x160 SDS-plus	6	160	1	367.982		
HD 2-C D8x160 SDS-plus	8	160	1	367.990		
HD 2-C D10x160 SDS-plus	10	160	1	368.008		
HD 2-C D12x160 SDS-plus	12	160	1	368.016		
HD 2-C D6x210 SDS-plus	6	210	1	368.024		
HD 2-C D8x210 SDS-plus	8	210	1	368.032		
HD 2-C D10x210 SDS-plus	10	210	1	368.040		
HD 2-C D12x210 SDS-plus	12	210	1	368.059		
HD 2-C D14x210 SDS-plus	14	210	1	368.067		
HD 2-C D16x210 SDS-plus	16	210	1	368.075		
HD 2-C D8x260 SDS-plus	8	260	1	368.083		
HD 2-C D10x260 SDS-plus	10	260	1	368.091		
HD 2-C D12x260 SDS-plus	12	260	1	368.105		
HD 2-C D14x260 SDS-plus	14	260	1	368.113		
HD 2-C D16x310 SDS-plus	16	310	1	368.121		
HD 2-C D18x200 SDS-plus	18	200	1	368.148		
HD 2-C D20x200 SDS-plus	20	200	1	368.156		
HD 2-C D18x450 SDS-plus	18	450	1	368.164		
HD 2-C D20x450 SDS-plus	20	450	1	368.172		
HD 2-C D22x450 SDS-plus	22	450	1	368.180		
HD 2-C D25x450 SDS-plus	25	450	1	368.199		



SDS-plus flat chisel

Dimensions in mm	Type	QTY/ PKG	Order no.		
20 x 250	flat	1	368.490		



SDS-plus sharp chisel

Dimensions in mm	Type	QTY/ PKG	Order no.		
250	pointed	1	368.504		



SDS-plus broad-flat chisel

Dimensions in mm	Type	QTY/ PKG	Order no.		
40 x 250	spat	1	368.512		



SDS-plus tile chisel

Dimensions in mm	Type	QTY/ PKG	Order no.		
40 x 250	cambered	1	368.628		



Chisel/drill set SDS-plus

Designation	QTY/ PKG	Order no.		
HD 2-C D5-10 Set SDS-plus	1	368.571		



Hammer drill bit set SDS-plus

Designation	QTY/ PKG	Order no.		
HD 2-C D5-10 Set SDS-plus	1	414.026		



Hammer drill bit set SDS-plus

Designation	Diameter in mm	Length in mm	QTY/ PKG	Order no.		
HD 4-C D8x310 SDS-plus VE5	8	250	5	414.034		



SDS-plus adapter

Designation	QTY/ PKG	Order no.		
HD 4-C D8x310 SDS-plus VE5	1	368.652		

Accessories SDS-max



SDS 2-max drill

Designation	Diameter in mm	Length in mm	QTY/ PKG	Order no.		
HD 2-C D12x340 SDS-max	12	340	1	368.202		
HD 2-C D14x340 SDS-max	14	340	1	368.210		
HD 2-C D15x340 SDS-max	15	340	1	368.229		
HD 2-C D12x540 SDS-max	12	540	1	368.237		
HD 2-C D14x540 SDS-max	14	540	1	368.245		
HD 2-C D15x540 SDS-max	15	540	1	368.253		



SDS 4-max drill

Designation	Diameter in mm	Length in mm	QTY/ PKG	Order no.		
HD 4-C D16x340 SDS-max	16	340	1	368.261		
HD 4-C D18x340 SDS-max	18	340	1	368.288		
HD 4-C D20x320 SDS-max	20	320	1	368.296		
HD 4-C D22x320 SDS-max	22	320	1	368.318		
HD 4-C D25x320 SDS-max	25	320	1	368.326		
HD 4-C D28x370 SDS-max	28	370	1	368.334		
HD 4-C D30x370 SDS-max	30	370	1	368.342		
HD 4-C D32x370 SDS-max	32	370	1	368.350		
HD 4-C D35x370 SDS-max	35	370	1	368.369		
HD 4-C D16x540 SDS-max	16	540	1	368.377		
HD 4-C D18x540 SDS-max	18	540	1	368.385		
HD 4-C D20x520 SDS-max	20	520	1	368.393		
HD 4-C D22x520 SDS-max	22	520	1	368.407		
HD 4-C D24x520 SDS-max	24	520	1	368.415		
HD 4-C D25x520 SDS-max	25	520	1	368.423		
HD 4-C D28x570 SDS-max	28	570	1	368.431		
HD 4-C D30x570 SDS-max	30	570	1	368.458		
HD 4-C D32x570 SDS-max	32	570	1	368.466		
HD 4-C D35x570 SDS-max	35	570	1	368.474		
HD 4-C D40x570 SDS-max	40	570	1	368.482		

Other accessories



Drill dust adapter

Designation	Dimensions in mm	QTY/ PKG	Order no.		
SAD BS D32	290 x 65	1	394.025		



Carrying case L-BOXX®

Designation	External dimensions L x W x H	Internal dimensions L x W x H	Weight	QTY/ PKG	Order no.		
TK-L 136	442 x 357 x 151 mm	378 x 311 x 107 mm	2,2 kg	1	414.085		
TK-L 238	442 x 357 x 253 mm	378 x 306 x 209 mm	2,8 kg	1	414.093		



SDS-max flat chisel

Dimensions in mm	Type	QTY/ PKG	Order no.		
25 x 400	flat	1	368.539		

Case insert

Designation	QTY/ PKG	Order no.		
TKE CHE2-28/FHE2-22	1	414.042		
TKE CHE 4-32	1	429.104		



SDS-max sharp chisel

Dimensions in mm	Type	QTY/ PKG	Order no.		
400	pointed	1	368.547		



SDS-max broad-flat chisel

Dimensions in mm	Type	QTY/ PKG	Order no.		
50 x 400	spat	1	368.555		



SDS-max tile chisel

Dimensions in mm	Type	QTY/ PKG	Order no.		
50 x 300	cambered	1	368.563		



SDS-max chisel set

QTY/ PKG	Order no.		
1	368.601		

Range of Products 2018

Safety vacuum cleaner compact class



VC 21 L MC
Safety vacuum cleaner with manual
filter cleaning system, 20 l, class L
Order no. 405.418

Power input P. max.	1250 watt
Max. volume flow	3600 l/min
Max. vacuum	21000 Pa
Filter surface	3000 cm ²
Container volume	20 l
Liquid capacity	11 l
Power take off	100-2000 watt
Size (W x L x H)	430 x 380 x 506 mm
Cable length	5,0 m
Weight	7,4 kg



Standard Equipment:
Suction hose 32 mm Ø x 3.5 m with elbow (385.484) ·
1 filter element class L/M (385.085) ·
2x 0.5 m aluminium suction tube (385.522) ·
1 combination floor nozzle, switchable (385.565) ·
1 round brush (385.646) ·
1 crevice nozzle (385.530) ·
1 upholstery nozzle (385.549) ·
1 filter bag (385.093) ·
1 PP waste disposal bag (385.107) ·
1 suction pipe holder (410.993) ·
1 cable hook (410.705) ·
1 adapter Ø 27-32 mm (385.506)

Safety vacuum cleaner construction/workshop class



VCE 33 L MC
Safety vacuum cleaner with manual
filter cleaning system, 30 l, class L
Order no. 444.103

Power input P. max.	1400 watt
Max. volume flow	4500 l/min
Max. vacuum	25000 Pa
Filter surface	5000 cm ²
Container volume	30 l
Liquid capacity	17 l
Power take off	100-2400 watt
Size (W x L x H)	565 x 385 x 520 mm
Cable length	7,5 m
Weight	14,5 kg



Standard Equipment:
1 suction hose 32 mm Ø x 4 m (445.037) ·
1 flat-fold filter PES L/M/H (445.118) ·
1 fleece filter bag class L/M (1 piece of 445.088) ·
1 PP waste disposal bag (1 piece of 445.061) ·
3x 35 cm INOX suction pipe (445.207) ·
1 elbow (445.010) ·
1 floor nozzle (445.509) ·
1 crevice nozzle (385.530) ·
1 upholstery nozzle (385.549) ·
1 round brush (385.646) ·
1 adapter Ø 25-32 mm, anti-static (445.029) ·
1 expander (1 piece) ·
Hose clip (1 piece)



VCE 26 L MC
Safety vacuum cleaner with manual
filter cleaning system, 25 l, class L
Order no. 405.426

Power input P. max.	1250 watt
Max. volume flow	3600 l/min
Max. vacuum	21000 Pa
Filter surface	3000 cm ²
Container volume	25 l
Liquid capacity	16 l
Power take off	100-2600 watt
Size (W x L x H)	475 x 377 x 526 mm
Cable length	7,5 m
Weight	8,4 kg



Standard Equipment:
Suction hose 32 mm Ø x 3.5 m with elbow (385.484) ·
1 filter element class L/M (385.085) ·
2x 0.5 m aluminium suction tube (385.522) ·
1 combination floor nozzle, switchable (385.565) ·
1 round brush (385.646) ·
1 crevice nozzle (385.530) ·
1 upholstery nozzle (385.549) ·
1 filter bag (385.093) ·
1 PP waste disposal bag (385.107) ·
1 suction pipe holder (410.993) ·
1 cable hook (410.705) ·
1 flexible hose strap for hose holder (411.108) ·
1 box for accessories with holder (411.124) ·
1 adapter Ø 27-32 mm (385.506)



VCE 33 L AC
Safety vacuum cleaner with automatic
filter cleaning system, 30 l, class L
Order no. 444.111

Power input P. max.	1400 watt
Max. volume flow	4500 l/min
Max. vacuum	25000 Pa
Filter surface	5000 cm ²
Container volume	30 l
Liquid capacity	17 l
Power take off	100-2400 watt
Size (W x L x H)	565 x 385 x 565 mm
Cable length	7,5 m
Weight	15,2 kg



**Kit
System**



Standard Equipment:
Antistatic suction hose Ø 32 mm x 4 m with clip connection including auxiliary air control and suction adapter SAD-C D25-32AS (406.708) ·
1 L-BOXX® holder (445.169) ·
1 flat-fold filter PES L/M/H (445.118) ·
1 fleece filter bag class L/M (445.088) ·
1 PP waste disposal bag (445.061) ·
1 adapter Ø 25-32 mm, anti-static (445.029) ·
Hose clip (2 pieces)



VCE 33 L AC-Kit
Order no. 445.983


Standard Equipment:
VCE 33 L AC + 1 cleaning set (445.053)



VCE 33 M AC

Safety vacuum cleaner with automatic filter cleaning system, 30 l, class M
Order no. 444.138

Power input P. max.	1400 watt
Max. volume flow	4500 l/min
Max. vacuum	25000 Pa
Filter surface	5000 cm ²
Container volume	30 l
Liquid capacity	17 l
Power take off	100-2400 watt
Size (W x L x H)	565 x 385 x 565 mm
Cable length	7,5 m
Weight	15,2 kg



Kit
System



Standard Equipment:
Antistatic suction hose Ø 32 mm x 4 m with clip connection including auxiliary air control and suction adapter SAD-C D25-32AS (406.708) ·
1 L-BOXX® holder (445.169) ·
1 flat-fold filter PES L/M/H (445.118) ·
1 fleece filter bag class L/M (445.088) ·
1 PP waste disposal bag (445.061) ·
1 adapter Ø 25-32 mm, anti-static (445.029) ·
Hose clip (2 pieces)



VCE 44 M AC

Safety vacuum cleaner with automatic filter cleaning system, 42 l, class M
Order no. 444.170

Power input P. max.	1400 watt
Max. volume flow	4500 l/min
Max. vacuum	25000 Pa
Filter surface	5000 cm ²
Container volume	42 l
Liquid capacity	26 l
Power take off	100-2400 watt
Size (W x L x H)	565 x 385 x 650 mm
Cable length	7,5 m
Weight	16,7 kg



Kit
System



Standard Equipment:
Antistatic suction hose Ø 32 mm x 4 m with clip connection including auxiliary air control and suction adapter SAD-C D25-32AS (406.708) ·
1 L-BOXX® holder (445.169) ·
1 flat-fold filter PES L/M/H (445.118) ·
1 fleece filter bag class L/M (445.088) ·
1 PP waste disposal bag (445.061) ·
1 adapter Ø 25-32 mm, anti-static (445.029) ·
Hose clip (2 pieces)



VCE 33 M AC-Kit

Order no. 445.991

Standard Equipment:
VCE 33 M AC + 1 cleaning set (445.053)



VCE 44 M AC-Kit

Order no. 446.017


Standard Equipment:
VCE 44 M AC + 1 cleaning set (445.053)



VCE 44 L AC

Safety vacuum cleaner with automatic filter cleaning system, 42 l, class L
Order no. 444.154

Power input P. max.	1400 watt
Max. volume flow	4500 l/min
Max. vacuum	25000 Pa
Filter surface	5000 cm ²
Container volume	42 l
Liquid capacity	26 l
Power take off	100-2400 watt
Size (W x L x H)	565 x 385 x 650 mm
Cable length	7,5 m
Weight	16,7 kg



Kit
System



Standard Equipment:
Antistatic suction hose Ø 32 mm x 4 m with clip connection including auxiliary air control and suction adapter SAD-C D25-32AS (406.708) ·
1 L-BOXX® holder (445.169) ·
1 flat-fold filter PES L/M/H (445.118) ·
1 fleece filter bag class L/M (445.088) ·
1 PP waste disposal bag (445.061) ·
1 adapter Ø 25-32 mm, anti-static (445.029) ·
Hose clip (2 pieces)



VCE 44 M AC Air

Safety vacuum cleaner with automatic filter cleaning system, 42 l, class M
Order no. 444.189

Power input P. max.	1400 watt
Max. volume flow	4500 l/min
Max. vacuum	25000 Pa
Filter surface	5000 cm ²
Container volume	42 l
Liquid capacity	26 l
Power take off	100-2400 watt
Size (W x L x H)	565 x 385 x 650 mm
Cable length	7,5 m
Weight	17,5 kg



Kit
System



Standard Equipment:
Antistatic suction hose Ø 32 mm x 4 m with clip connection including auxiliary air control and suction adapter SAD-C D25-32AS (406.708) ·
1 L-BOXX® Air holder (445.177) ·
1 flat-fold filter PES L/M/H (445.118) ·
1 fleece filter bag class L/M (445.088) ·
1 PP waste disposal bag (445.061) ·
1 adapter Ø 25-32 mm, anti-static (445.029) ·
Hose clip (2 pieces) ·
1 handle (445.150)



VCE 44 L AC-Kit

Order no. 446.009


Standard Equipment:
VCE 44 L AC + 1 cleaning set (445.053)

Range of Products 2018



VCE 44 H AC
Safety vacuum cleaner with automatic
filter cleaning system, 42 l, class H
Order no. 444.197

Power input P. max.	1400 watt
Max. volume flow	4500 l/min
Max. vacuum	25000 Pa
Filter surface	5000 cm ²
Container volume	42 l
Liquid capacity	26 l
Power take off	100-2400 watt
Size (W x L x H)	565 x 385 x 650 mm
Cable length	7,5 m
Weight	17,6 kg



Kit
System



Standard Equipment:
Antistatic suction hose Ø 32 mm x 4 m
with clip connection including auxiliary
air control and suction adapter SAD-C
D25-32AS (406.708) ·
1 L-BOX® holder (445.169) ·
1 flat-fold filter PES L/M/H (445.118) ·
1 flat folded filter class H/HEPA 14
(445.126) ·
1 safety filter bag (445.096) ·
1 adapter Ø 25-32 mm, anti-static
(445.029) ·
Hose clip (2 pieces)



VCE 44 H AC-Kit
Order no. 446.025

Standard Equipment:
VCE 45 M AC + 1 cleaning set (445.053)

Accessories for industrial/safety vacuum cleaners

Accessories for VC/VCE 21, 26 L MC



Suction hose

Designation	QTY/ PKG	Order no.		
SH 32x3.5m	1	385.484		




Adapter

Designation	QTY/ PKG	Order no.		
SAD D27-32	1	385.506		




Filter element

Designation	QTY/ PKG	Order no.		
FE VC/E 21-26 PET M	1	385.085		



Fleece filter bags


Designation	QTY/ PKG	Order no.		
FS-F VC/E 21-26 L VE5	5	385.093		



Disposal bag

Designation	QTY/ PKG	Order no.		
ES-PP VC/E 21-26 VE5	5	385.107		

Accessories for VCE 33, 44 L/M/H




PES flat folded filter

Designation	QTY/ PKG	Order no.		
FE VCE PES L/M/H	1	445.118		



Filter element

Designation	QTY/ PKG	Order no.		
FE VCE44 H/HEPA	1	445.126		




PES flat folded filter

Designation	QTY/ PKG	Order no.		
VFE VCE L/M/H	1	445.134		



Giraffe holder

Designation	QTY/ PKG	Order no.		
VCE-GE Fix	1	445.185		



Fleece filter bags

Designation	QTY/ PKG	Order no.		
FS-F VCE L/M VE5	5	445.088		

Accessories for industrial/safety vacuum cleaners VCE



Antistatic suction hose with auxiliary air control

Designation	QTY/ PKG	Order no.		
SH-C 32x4m AS/NL	1	406.708		




Longlife filter sack

Designation	QTY/ PKG	Order no.		
FS-LL VCE 33/44	1	445.517		



Antistatic suction hose

Designation	Dimensions in mm	QTY/ PKG	Order no.		
SH 27x4m AS	27 Ø x 4m	1	379.395		




Safety filter bag

Designation	QTY/ PKG	Order no.		
SFS VCE H VE5	5	445.096		



Suction hose with auxiliary air control

Designation	QTY/ PKG	Order no.		
SH-C 32x4m	1	445.037		



Disposal bag

Designation	QTY/ PKG	Order no.		
ES-PP VCE L/M VE5	5	445.061		



Suction hose

Designation	QTY/ PKG	Order no.		
SH 32x4m WS 702	1	341.355		



Handle

Designation	QTY/ PKG	Order no.		
VCE-TH	1	445.150		



Suction hose extension

Designation	QTY/ PKG	Order no.		
SHV-C 32x0,5m	1	296.953		



L-BOXX® holder

Designation	QTY/ PKG	Order no.		
VCE-AP	1	445.169		



Suction hose snap coupling repair kit

Designation	QTY/ PKG	Order no.		
SAM-C R32 AS/NL	1	408.697		



L-BOXX® Air holder

Designation	QTY/ PKG	Order no.		
VCE-AP Air	1	445.177		



Snap-ring grey

Designation	QTY/ PKG	Order no.		
SH-C 32	1	379.654		

Range of Products 2018



Clip-on quick clamping ring red

Designation	QTY/ PKG	Order no.		
SH-FC 32	1	406.023		



Adapter

Designation	QTY/ PKG	Order no.		
SAD 27 AS	1	382.736		



Threaded ring clip with auxiliary air control

Designation	QTY/ PKG	Order no.		
SAM-C 32 AS/NL	1	406.716		



Adapter

Designation	QTY/ PKG	Order no.		
SAD D25-32 AS	1	259.827		



Clip adapter

Designation	QTY/ PKG	Order no.		
SAD-C D36/27 AS/NL	1	408.360		



Special adapter

Designation	QTY/ PKG	Order no.		
SAD D32 WS/WSK	1	340.790		



Fast clip adapter

Designation	QTY/ PKG	Order no.		
SAD-FC 32	1	410.497		



Special adapter

Designation	QTY/ PKG	Order no.		
SAD-C WS/WSE	1	364.460		



Adapter

Designation	QTY/ PKG	Order no.		
SAD-C D25-32 AS	1	445.029		



Special adapter

Designation	QTY/ PKG	Order no.		
SAD D32-32 R	1	328.308		



Adapter

Designation	QTY/ PKG	Order no.		
SAD-C 32 AS	1	445.142		



Special adapter

Designation	QTY/ PKG	Order no.		
SAD D32-28	1	251.847		



Adapter

Designation	QTY/ PKG	Order no.		
SAD-C 27 AS	1	461.628		



Rotating vacuum adapter

Designation	QTY/ PKG	Order no.		
SAD-32 VC/VCE AS	1	340.804		



Adapter

Designation	QTY/ PKG	Order no.		
SAD-C 36 AS	1	461.636		



Coupling bush

Designation	QTY/ PKG	Order no.		
SAD D32-36	1	257.169		



Coupling bush

Designation	QTY/ PKG	Order no.		
SAD 32/32	1	296.996		



Surface nozzle

Designation	QTY/ PKG	Order no.		
FD D36 90x120mm	1	413.437		



Cleaning set

Designation	QTY/ PKG	Order no.		
CLE 32 AS	1 set	445.053		



Combination floor nozzle

Designation	QTY/ PKG	Order no.		
KN 36x260	1	385.565		



Elbow

Designation	QTY/ PKG	Order no.		
K-C 32 KU AS	1	445.010		



Floor nozzle with rollers

Designation	QTY/ PKG	Order no.		
FN-AL 36x370	1	369.896		



Extension tube

Designation	QTY/ PKG	Order no.		
V 36x350 INOX VE3	3	445.207		



Brush strip

Designation	QTY/ PKG	Order no.		
BL-FN-AL 36x370 VE2	2	374.075		



Brush nozzle

Designation	QTY/ PKG	Order no.		
BN 36x220	1	385.557		



Rubber strip

Designation	QTY/ PKG	Order no.		
GL-FN-AL 36x370 VE2	2	374.083		



Round brush

Designation	QTY/ PKG	Order no.		
RN 36x120	1	385.646		



Floor nozzle

Designation	QTY/ PKG	Order no.		
FN D36x300	1	445.509		



Upholstery nozzle

Designation	QTY/ PKG	Order no.		
PN 36x115	1	385.549		



Clip floor nozzle with rollers

Designation	QTY/ PKG	Order no.		
CNW 36x400	1	385.573		



Crevice nozzle

Designation	QTY/ PKG	Order no.		
CN 36x300	1	385.530		



Brush strip

Designation	QTY/ PKG	Order no.		
BL-CNW 36x400 VE2	2	385.581		

Range of Products 2018



Rubber strip

Designation	QTY/ PKG	Order no.		
GL-CNW 36x400 VE2	2	385.603		




Paper-Filter bags

Designation	QTY/ PKG	Order no.		
FS-P VC/E 35 VE5	5	296.961		



Drill dust adapter

Designation	Dimensions in mm	QTY/ PKG	Order no.		
SAD BS D32	290 x 65	1	394.025		



Paper-Filter bags

Designation	QTY/ PKG	Order no.		
FS-P VCE 45 VE5	5	340.758		



Cable clip

Designation	QTY/ PKG	Order no.		
	1	252.188		



Cotton filter bag


Designation	Dimensions in mm	QTY/ PKG	Order no.		
FS-M VC/E 35/45	750 x 380	1	404.330		

Accessories for VCE 35, 45 L/M/H




Suction hose

Designation	QTY/ PKG	Order no.		
SH-C 32x4m	1	299.782		
SH 32x4m	1	338.508		



Safety filter bag

Designation	QTY/ PKG	Order no.		
SFS VCE 45 H VE5	5	379.115		




PES flat folded filter

Designation	QTY/ PKG	Order no.		
FE VC/E 35/45 PES M	1	369.829		



Fleece filter bags

Designation	QTY/ PKG	Order no.		
FS-F VC/E 35 VE5	5	329.630		




Flat folded filter

Designation	QTY/ PKG	Order no.		
FE VC/E 35/45 P M	1	337.692		




Fleece filter bags

Designation	QTY/ PKG	Order no.		
FS-F VCE 45 VE5	5	402.982		




Flat folded filter

Designation	QTY/ PKG	Order no.		
FE VCE 45 H HEPA 14	1	379.107		



Disposal bag

Designation	QTY/ PKG	Order no.		
ES-PP VC/E 35/45 VE10	10	340.766		



Transport bag

Designation	QTY/ PKG	Order no.		
TS VCE 45 H	1	379.123		

Mixers



MXE 1000 1010 watt 1-speed mixer with accelerator trigger switch

No load speed	0-530 rpm
Power input	1010 watt
Power output	550 watt
Tool fixture	M 14
Clamping collar Ø	53 mm
Max. mixing paddle Ø	120 mm
Size (W x L x H)	405 x 215 x 340 mm
Cable length	4,0 m
Weight (without mixing paddle)	4,5 kg

Standard Equipment:
1 open-ended wrench SW 19 (439.967) ·
1 open-ended wrench SW 22 (439.975)



MXE 1000 + WR2 120 Order no. 433.179

Standard Equipment:
MXE 1000 + 1 WR2 helix paddle 120x600
M14 (368.881)



MXE 1000 + WR3R 120 Order no. 461.385


Standard Equipment:
MXE 1000 + 1 helix paddle WR3R
120x600 M14 (368.911)



MXE 1000 + RR2 120 Order no. 433.187

Standard Equipment:
MXE 1000 + 1 RR2 spiral paddle 120x600
M14 (368.903)

NEW



MXE 1001 1010 watt 1-speed mixer with accelerator trigger switch

No load speed	0-780 rpm
Power input	1010 watt
Power output	550 watt
Tool fixture	M 14
Clamping collar Ø	53 mm
Max. mixing paddle Ø	120 mm
Size (W x L x H)	405 x 215 x 340 mm
Cable length	4,0 m
Weight (without mixing paddle)	4,5 kg

Standard Equipment:
1 open-ended wrench SW 19 (439.967) ·
1 open-ended wrench SW 22 (439.975)



MXE 1001 + WR2 120 Order no. 459.208

Standard Equipment:
MXE 1001 + 1 WR2 helix paddle 120x600
M14 (368.881)



MXE 1001 + WR3R 120 Order no. 461.393

Standard Equipment:
MXE 1001 + 1 helix paddle WR3R
120x600 M14 (368.911)



MXE 1001 + RR2 120 Order no. 459.216

Standard Equipment:
MXE 1001 + 1 RR2 spiral paddle 120x600
M14 (368.903)



MXE 1001 + RB 120 Order no. 459.224

Standard Equipment:
MXE 1001 + 1 beater RB 140x600 M14
(369.152)



MXE 1002 1010 watt 2-speed mixer with accelerator trigger switch

No load speed 1st gear	0-530 rpm
No load speed 2nd gear	0-780 rpm
Power input	1010 watt
Power output	550 watt
Tool fixture	M 14
Clamping collar Ø	53 mm
Max. mixing paddle Ø	120 mm
Size (W x L x H)	405 x 215 x 340 mm
Cable length	4,0 m
Weight (without mixing paddle)	4,6 kg

Standard Equipment:
1 open-ended wrench SW 22 (439.975)



MXE 1002 + WR2 120 Order no. 433.209

Standard Equipment:
MXE 1002 + 1 WR2 helix paddle 120x600
M14 (368.881)



MXE 1002 + WR3R 120 Order no. 433.195

Standard Equipment:
MXE 1002 + 1 helix paddle WR3R
120x600 M14 (368.911)



MXE 1002 + RR2 120 Order no. 433.217

Standard Equipment:
MXE 1002 + 1 RR2 spiral paddle 120x600
M14 (368.903)

Range of Products 2018



MXE 1200 1200 watt 1-speed mixer with 3-level speed switch

No load speed	0-210/325/530 rpm
Power input	1200 watt
Power output	710 watt
Tool fixture	M 14
Clamping collar Ø	53 mm
Max. mixing paddle Ø	140 mm
Size (W x L x H)	405 x 215 x 340 mm
Cable length	4,0 m
Weight (without mixing paddle)	4,5 kg

Standard Equipment:
1 open-ended wrench SW 22 (439.975)



MXE 1200 + WR2 140 Order no. 433.233

Standard Equipment:
MXE 1200 + 1 helix paddle WR2 140x600 M14 (368.997)



MXE 1200 + WR3R 140 Order no. 433.225

Standard Equipment:
MXE 1200 + 1 helix paddle
WR3R 140x600 M14 (369.012)



MXE 1200 + SR2 140 Order no. 433.241

Standard Equipment:
MXE 1200 + 1 disc paddle SR2 140x600 M14 (369.128)



MXE 1202 1200 watt 2-speed mixer with 3-level speed switch

No load speed	0-210/325/530 rpm
1st gear	0-320/490/780 rpm
2nd gear	0-320/490/780 rpm
Power input	1200 watt
Power output	710 watt
Tool fixture	M 14
Clamping collar Ø	53 mm
Max. mixing paddle Ø	140 mm
Size (W x L x H)	405 x 215 x 340 mm
Cable length	4,0 m
Weight (without mixing paddle)	4,6 kg

Standard Equipment:
1 open-ended wrench SW 22 (439.975)



MXE 1202 + WR2 140 Order no. 433.276

Standard Equipment:
MXE 1202 + 1 helix paddle WR2 140x600 M14 (368.997)



MXE 1202 + WR3R 140 Order no. 433.268

Standard Equipment:
MXE 1202 + 1 helix paddle
WR3R 140x600 M14 (369.012)



MXE 1202 + SR2 140 Order no. 433.284

Standard Equipment:
MXE 1202 + 1 disc paddle SR2 140x600 M14 (369.128)

NEW



MXE 1602 1600 watt 2-speed mixer with 3-level speed switch

No load speed	0-210/325/530 rpm
1st gear	0-320/490/780 rpm
2nd gear	0-320/490/780 rpm
Power input	1600 watt
Power output	925 watt
Tool fixture	M 14
Clamping collar Ø	53 mm
Max. mixing paddle Ø	160 mm
Size (W x L x H)	343 x 405 x 215 mm
Cable length	4,0 m
Weight (without mixing paddle)	5,0 kg

Standard Equipment:
1 open-ended wrench SW 22 (439.975)



MXE 1602 + WR2 160 Order no. 459.232

Standard Equipment:
MXE 1602 + 1 WR2 helix paddle 160x600 M14 (369.004)



MXE 1602 + WR3R 160 Order no. 459.240

Standard Equipment:
MXE 1602 + 1 helix paddle
WR3R 160x600 M14 (369.020)

Accessories for mixers

Mixing paddles, with M 14 external thread



Spiral paddle RR2

Designation	Paddle in mm	Mix in kg	QTY/ PKG	Order no.		
RR2 120x600 M14	120 Ø	20-40	1	368.903		



Helix paddle WR2

Designation	Paddle in mm	Mix in kg	QTY/ PKG	Order no.		
WR2 120x600 M14	120 Ø	15-25	1	368.881		
WR2 140x600 M14	140 Ø	20-40	1	368.997		
WR2 160x600 M14	160 Ø	20-40	1	369.004		



Helix paddle WR3R

Designation	Paddle in mm	Mix in kg	QTY/ PKG	Order no.		
WR3R 120x600 M14	120 Ø	15-25	1	368.911		
WR3R 140x600 M14	140 Ø	20-40	1	369.012		
WR3R 160x600 M14	160 Ø	30-60	1	369.020		



Plaster paddle PR3L

Designation	Paddle in mm	Mix in kg	QTY/ PKG	Order no.		
PR3L 180x600 M14	180 Ø	40-80	1	369.039		
PR3L 200x600 M14	200 Ø	60-100	1	369.047		



Helix paddle WR3L

Designation	Paddle in mm	Mix in kg	QTY/ PKG	Order no.		
WR3L 120x600 M14	120 Ø	15-25	1	369.055		
WR3L 140x600 M14	140 Ø	20-40	1	369.063		
WR3L 160x600 M14	160 Ø	30-60	1	369.071		




Disc paddle SR2

Designation	Paddle in mm	Mix in kg	QTY/ PKG	Order no.		
SR2 120x600 M14	120 Ø	15-25	1	368.938		
SR2 140x600 M14	140 Ø	20-40	1	369.128		
SR2 160x600 M14	160 Ø	30-60	1	369.136		



Beater RB

Designation	Paddle in mm	Mix in kg	QTY/ PKG	Order no.		
RB 120x600 M14	120 Ø	10-30	1	369.152		
RB 140x600 M14	140 Ø	30-60	1	369.160		



Mixing paddle, M 14

Dimensions in mm	QTY/ PKG	Order no.		
120 Ø	1	124.761		



Mixing paddle, M 14

Dimensions in mm	QTY/ PKG	Order no.		
70 Ø	1	124.753		

Mixing paddles for drill chucks



VORTINOX mixing paddle

Designation	Paddle in mm	Mix in kg	QTY/ PKG	Order no.		
VR 80x320 D 10	80 Ø	0,5-5	1	385.301		
VR 140x520 D 10	140 Ø	3-15	1	385.328		



Spiral paddle RR2

Designation	Paddle in mm	Mix in kg	QTY/ PKG	Order no.		
RR2 85x400 SW8	85 Ø	- 10	1	368.946		
RR2 100x600 SW10	100 Ø	8-25	1	368.954		

Range of Products 2018



Helix paddle WR2

Designation	Paddle in mm	Mix in kg	QTY/ PKG	Order no.		
WR2 85x500 SW8	85 Ø	-10	1	368.962		
WR2 100x500 SW10	100 Ø	8-20	1	368.970		
WR2 120x600 SW10	120 Ø	15-25	1	368.989		



SDS-plus M14 adapter

QTY/ PKG	Order no.		
1	374.091		



Disc paddle SR2

Designation	Paddle in mm	Mix in kg	QTY/ PKG	Order no.		
SR2 80x500 SW8	80 Ø	-10	1	369.098		
SR2 100x600 SW10	100 Ø	8-15	1	369.101		



Extension M14

Designation	Dimensions in mm	QTY/ PKG	Order no.		
R-V 100 M14 M/F	100	1	390.755		



Beater RB

Designation	Paddle in mm	Mix in kg	QTY/ PKG	Order no.		
RB 120x600 SW10	120 Ø	-15	1	369.144		



Extension M14

Designation	Dimensions in mm	QTY/ PKG	Order no.		
R-V 200 M14 M/F	200	1	374.105		
R-V 400 M14 M/F	400	1	374.113		

Mixing heads for RZ 600 VV



Mixing paddles I and II, galvanized version

Paddle in mm	Mix in kg	QTY/ PKG	Order no.		
130 Ø	5 - 60	1	252.200		

Adapter



M 14 to M 14 adapter

QTY/ PKG	Order no.		
1	255.195		



M 18 to M 14 adapter

QTY/ PKG	Order no.		
1	250.484		

Measuring technology/laser



ALC 2/1-Basic Self-levelling crossline laser Order no. 409.235

Number of lines	1 horizontal/ 1 vertical
Visible area lines	90°
Precision	± 0,3 mm/m
Self-levelling range	± 4 °
Max. working range	20 m
Operation duration	6 h
Temperature range	-5° - +50 °C
Laser class	2
International Protection	IP 54
Weight	0,42 kg

Standard Equipment:
Batteries 3x AA (1 set) ·
1 carrying bag (1 piece)

NEW



ALC 3/1-G Self-levelling crossline laser Order no. 456.004

Number of lines	1 horizontal/ 2 vertical plus plumb
Visible area lines	90°
Precision	± 0,3 mm/m (plumb ± 0,6 mm/m)
Self-levelling range	± 4 °
Max. working range	20 m / plumb 5 m
Operation duration	6 h
Temperature range	-5° - +50 °C
Laser class	2
International Protection	IP 54
Integrated battery	3,7 V 2000 mAh / Li-on
Weight	0,53 kg

Standard Equipment:
1 wall bracket magnetic
WB-M/S 1/4 ALC-Basic (428.167) ·
1 USB-cable (1 piece) ·
1 USB-charger (1 piece) ·
1 carrying bag (1 piece)

NEW



ALC 2/1-G Self-levelling crossline laser Order no. 455.997

Number of lines	1 horizontal/ 1 vertical
Visible area lines	90°
Precision	± 0,3 mm/m
Self-levelling range	± 4 °
Max. working range	20 m
Operation duration	6 h
Temperature range	-5° - +50 °C
Laser class	2
International Protection	IP 54
Integrated battery	3,7 V 2000 mAh / Li-on
Weight	0,36 kg

Standard Equipment:
1 wall bracket magnetic
WB-M/S 1/4 ALC-Basic (428.167) ·
1 USB-cable (1 piece) ·
1 USB-charger (1 piece) ·
1 carrying bag (1 piece)

NEW



ADM 60 Li Laser range finder Order no. 447.862

Precision	± 3 mm
Max. working range	0,15 - 60 m
Laser class	2
Visible laser diodes	< 1 mW, 635 nm
International Protection	IP 54
Integrated battery	3,7 V 500 mAh / Li-on
Weight	0,13 kg

Standard Equipment:
1 USB-cable (1 piece) ·
1 USB-charger (1 piece) ·
1 carrying bag (1 piece)



ALC 3/1-Basic Self-levelling crossline laser Order no. 409.243

Number of lines	1 horizontal/ 2 vertical plus plumb
Visible area lines	90°
Precision	± 0,3 mm/m (plumb ± 0,6 mm/m)
Self-levelling range	± 4 °
Max. working range	20 m / plumb 5 m
Operation duration	6 h
Temperature range	-5° - +50 °C
Laser class	2
International Protection	IP 54
Weight	0,58 kg

Standard Equipment:
1 wall bracket magnetic
WB-M/S 1/4 ALC-Basic (428.167) ·
Batteries 3x AA (1 set) ·
1 carrying bag (1 piece)



ADM 60-T Laser range finder with touchscreen Order no. 409.162

Precision	± 2 mm
Max. working range	0,1 - 60 m
Laser class	2
Size (W x L x H)	115 x 56 x 31 mm
International Protection	IP 54
Weight	0,18 kg

Standard Equipment:
Batteries 4x AAA (1 set) ·
1 carrying bag (1 piece)

Range of Products 2018



LKS 100-300 5/8
Laser tripod
Order no. 398.616

Working range 1,01 - 3,00 m
Connection thread 5/8"
Weight 5,7 kg

Standard Equipment:
1 carrying strap (1 piece) ·
1 adapter LAD 5/8 I-1/4 A (398.608)



LKS 65-170 F 1/4
Laser tripod
Order no. 398.624

Working range 0,65 - 1,65 m
Connection thread 1/4"
Weight 1,4 kg

Standard Equipment:
1 carrying bag (1 piece)



Accessories for laser measuring technology



Laser wall bracket


Designation	QTY/ PKG	Order no.		
WB-M/S 1/4 ALC-Basic	1	428.167		



Laser tripod adapter

Designation	QTY/ PKG	Order no.		
LAD 5/8 I-1/4 A	1	398.608		

Polishers



PE 8-4 80 Polisher for small areas Order no. 405.817

Max. polishing pad diameter	80 mm
Max. back-up pad diameter	75 mm
No load speed	1300-3900 rpm
Power input	800 watt
Power output	350 watt
Tool fixture	M 14
Cable length	4,0 m
Weight	1,8 kg

Standard Equipment:
1 side handle (194.034)



PE 14-2 150 POLISHFLEX, variable-speed polisher with a high torque Order no. 373.680

Max. polishing pad diameter	200 mm
Max. back-up pad diameter	150 mm
No load speed	380-2100 rpm
Power input	1400 watt
Power output	880 watt
Tool fixture	M 14
Size (L x H)	405x117 mm
Cable length	4,0 m
Weight	2,3 kg

Standard Equipment:
1 handle (252.721)



PE 14-3 125 Ergonomic polisher with speed control trigger Order no. 406.813

Max. polishing pad diameter	160 mm
Max. back-up pad diameter	125 mm
No load speed	1100-3700 rpm
Power input	1400 watt
Power output	880 watt
Tool fixture	M 14
Size (L x H)	375 x 120 mm
Cable length	4,0 m
Weight	2,2 kg

Standard Equipment:
1 side handle (252.721)



PE 14-2 150 P-Set POLISHFLEX, variable-speed polisher with a high torque Order no. 376.175

Max. polishing pad diameter	200 mm
Max. back-up pad diameter	150 mm
No load speed	380-2100 rpm
Power input	1400 watt
Power output	880 watt
Tool fixture	M 14
Size (L x H)	405x117 mm
Cable length	4,0 m
Weight	2,3 kg

Standard Equipment:
1 handle (252.721) ·
1 velcro backing pad, cushioned,
Ø 150 mm (350.745) ·
1 polishing sponge PS-O 160 (434.329) ·
1 polishing sponge PS-V 160 (434.469) ·
1 lambswool TW-PT 160 (376.523) ·
1 polish P03/06-LDX 250 ml (443.298) ·
1 polish P05/05-LDX 250 ml (443.271) ·
1 microfibre cloth MW-P (376.531) ·
1 carrying case L-BOX® 238 (414.093) ·
1 case insert (444.375)



PE 14-3 125 P-Set Ergonomic polisher with speed control trigger in set Order no. 407.569

Max. polishing pad diameter	160 mm
Max. back-up pad diameter	125 mm
No load speed	1100-3700 rpm
Power input	1400 watt
Power output	880 watt
Tool fixture	M 14
Size (L x H)	375x120 mm
Cable length	4,0 m
Weight	2,2 kg

Standard Equipment:
1 side handle (252.721) ·
1 velcro pad 125 Ø (350.737) ·
1 polishing sponge PS-O 160 (434.329) ·
1 polishing sponge PS-V 160 (434.469) ·
1 polish P03/06-LDX 250 ml (443.298) ·
1 polish P05/05-LDX 250 ml (443.271) ·
1 microfibre polishing cloth MW-C
(317.098)

NEW



PE 150 18.0-EC Cordless rotary polisher 18.0 V Order no. 459.062

Max. polishing pad diameter	160 mm
Max. back-up pad diameter	150 mm
No load speed	150-1450 rpm
Battery voltage	18 V
Battery capacity	2,5 / 5,0 Ah
Size (L x H)	370 x 120 mm
Weight without battery	1,9 kg

Standard Equipment:
1 velcro pad 150 Ø (350.745) ·
1 handle (252.721) ·
1 carrying case L-BOX® 238 (414.093) ·
1 case insert (459.534)

Range of Products 2018

NEW



PE 150 18.0-EC/5.0 Set Cordless rotary polisher 18.0 V Order no. 447.153

Max. polishing pad diameter	160 mm
Max. back-up pad diameter	150 mm
No load speed	150-1450 rpm
Battery voltage	18 V
Battery capacity	2,5 / 5,0 Ah
Size (L x H)	370 x 120 mm
Weight without battery	1,9 kg



Standard Equipment:
1 velcro pad 150 Ø (350.745) ·
1 handle (252.721) ·
2 batteries 5.0 Ah AP 18.0/5.0 (445.894) ·
1 charger CA 10.8/18.0 (417.882) ·
1 carrying case L-BOXX® 238 (414.093) ·
1 case insert (459.534)

NEW



PE 150 18.0-EC/5.0 P-Set Cordless rotary polisher 18.0 V Order no. 461.229

Max. polishing pad diameter	160 mm
Max. back-up pad diameter	150 mm
No load speed	150-1450 rpm
Battery voltage	18 V
Battery capacity	2,5 / 5,0 Ah
Size (L x H)	370 x 120 mm
Weight without battery	1,9 kg



Standard Equipment:
1 polishing sponge PS-O 160 (434.329) ·
1 polishing sponge PS-V 160 (434.469) ·
1 lambswool TW-PT 160 (376.523) ·
1 polish P03/06-LDX 250 ml (443.298) ·
1 polish P05/05-LDX 250 ml (443.271) ·
1 microfibre cloth MW-P (376.531) ·
1 velcro pad 150 Ø (350.745) ·
1 handle (252.721) ·
2 batteries 5.0 Ah AP 18.0/5.0 (445.894) ·
1 charger CA 10.8/18.0 (417.882) ·
1 carrying case L-BOXX® 238 (414.093) ·
1 case insert (459.534)

PE 14-1 180 Polisher with high torque for processing large painted surfaces Order no. 395.749



Max. polishing pad diameter	250 mm
Max. back-up pad diameter	180 mm
No load speed	250-1380 rpm
Power input	1400 watt
Power output	880 watt
Tool fixture	M 14
Size (L x H)	405x117 mm
Cable length	4,0 m
Weight	2,3 kg

Standard Equipment:
1 handle (252.721)



L 602 VR Variable-speed polisher with a high torque Order no. 329.800

Max. polishing pad diameter	220 mm
Max. back-up pad diameter	175 mm
No load speed	400-2400 rpm
Power input	1500 watt
Power output	1000 watt
Tool fixture	M 14
Cable length	4,0 m
Weight	3,5 kg

Standard Equipment:
1 side handle (252.721) ·
1 bail handle (287.709)



L 1503 VR Polisher with a wide speed range Order no. 250.280

Max. polishing pad diameter	140 mm
Max. back-up pad diameter	125 mm
No load speed	1200-4900 rpm
Power input	1200 watt
Power output	700 watt
Cable length	4,0 m
Weight	1,9 kg

Standard Equipment:
1 side handle (194.034)



L 1202 Powerful low-speed polisher, 1600 watt Order no. 278.688

Max. polishing pad diameter	250 mm
Max. back-up pad diameter	175 mm
No load speed	1750 rpm
Power input	1600 watt
Power output	1100 watt
Tool fixture	M 14
Cable length	4,0 m
Weight	5,1 kg

Standard Equipment:
1 side handle (193.356) ·
1 hand guard (253.618) ·
1 handle (253.510)

NEW




XFE 7-12 80 Roto random orbit polisher for small areas Order no. 447.129

Max. polishing pad diameter	80 mm
Max. back-up pad diameter	75 mm
Orbit	12 mm
No load speed	1800-5500 rpm
Orbit rate, no load	3600-10800 opm
Power input	700 watt
Power output	420 watt
Size (L x H)	320 x 120 mm
Cable length	4,0 m
Weight	2,1 kg

Standard Equipment:
1 special velcro backing pad, 75 Ø (454.141)

NEW



XFE 7-12 80 P-Set
Roto random orbit polisher for small areas
Order no. 447.137

Max. polishing pad diameter	80 mm
Max. back-up pad diameter	75 mm
Orbit	12 mm
No load speed	1800-5500 rpm
Orbit rate, no load	3600-10800 opm
Power input	700 watt
Power output	420 watt
Size (L x H)	320 x 120 mm
Cable length	4,0 m
Weight	2,1 kg

Standard Equipment:
1 special velcro backing pad, 75 Ø (454.141) · 1 polishing sponge PSX-G 80 (1 piece of 434.264) · 1 polishing sponge PS-O 80 (1 piece of 434.302) · 1 polishing sponge PS-R 80 (1 piece of 434.345) · 1 microfibre polishing cloth MW-C (317.098) · 1 polish P05/05-LDX 250 ml (443.271) · 1 sealing W02/04 250 ml (443.301) · 1 carrying case L-BOXX® 136 (414.085) · 1 case insert (446.963)

NEW



XFE 15 150 18.0-EC
Cordless roto random orbit polisher 18,0 V
Order no. 459.089

Max. polishing pad diameter	160 mm
Max. back-up pad diameter	150 mm
Orbit	15 mm
No load speed	2300-3800 rpm
Orbit rate, no load	4600-7600 opm
Battery voltage	18 V
Battery capacity	2,5 / 5,0 Ah
Size (L x H)	380 x 140 mm
Weight	2,1 kg

Standard Equipment:
1 velcro pad 125 Ø (442.445) · 1 carrying case L-BOXX® 238 (414.093) · 1 case insert (459.526)

NEW



XFE 15 150 18.0-EC/5.0 Set
Cordless roto random orbit polisher 18,0 V
Order no. 418.099

Max. polishing pad diameter	160 mm
Max. back-up pad diameter	150 mm
Orbit	15 mm
No load speed	2300-3800 rpm
Orbit rate, no load	4600-7600 opm
Battery voltage	18 V
Battery capacity	2,5 / 5,0 Ah
Size (L x H)	380 x 140 mm
Weight without battery	2,1 kg

Standard Equipment:
1 velcro pad 125 Ø (442.445) · 2 batteries 5.0 Ah AP 18.0/5.0 (445.894) · 1 charger CA 10.8/18.0 (417.882) · 1 case insert (459.526) · 1 carrying case L-BOXX® 238 (414.093)

NEW



XFE 15 150 18.0-EC/5.0 P-Set
Cordless roto random orbit polisher 18,0 V
Order no. 461.237

Max. polishing pad diameter	160 mm
Max. back-up pad diameter	150 mm
Orbit	15 mm
No load speed	2300-3800 rpm
Orbit rate, no load	4600-7600 opm
Battery voltage	18 V
Battery capacity	2,5 / 5,0 Ah
Size (L x H)	380 x 140 mm
Weight without battery	2,1 kg

Standard Equipment:
1 polishing sponge PS-O 160 (434.329) · 1 polishing sponge PS-R 160 (434.361) · 1 polish P03/06-LDX 250 ml (443.298) · 1 sealing W02/04 250 ml (443.301) · 1 microfibre polishing cloth MW-C (317.098) · 1 velcro pad 125 Ø (442.445) · 2 batteries 5.0 Ah AP 18.0/5.0 (445.894) · 1 charger CA 10.8/18.0 (417.882) · 1 carrying case L-BOXX® 238 (414.093) · 1 case insert (459.526)



XFE 7-15 150
Roto random orbit polisher
Order no. 418.080

Max. polishing pad diameter	160 mm
Max. back-up pad diameter	150 mm
Orbit	15 mm
No load speed	1500-4500 rpm
Orbit rate, no load	2900-8600 opm
Power input	710 watt
Power output	420 watt
Size (L x H)	370 x 140 mm
Cable length	4,0 m
Weight	2,4 kg

Standard Equipment:
1 special velcro backing pad, 150 Ø (437.077) · 1 special velcro backing pad, 125 Ø (442.445)



XFE 7-15 150 P-Set
Roto random orbit polisher
Order no. 447.110

Max. polishing pad diameter	160 mm
Max. back-up pad diameter	150 mm
Orbit	15 mm
No load speed	1500-4500 rpm
Orbit rate, no load	2900-8600 opm
Power input	710 watt
Power output	420 watt
Size (L x H)	370 x 140 mm
Cable length	4,0 m
Weight	2,4 kg

Standard Equipment:
1 special velcro backing pad, 150 Ø (437.077) · 1 special velcro backing pad, 125 Ø (442.445) · 1 polishing sponge PS-O 160 (434.329) · 1 polishing sponge PS-R 160 (434.361) · 1 polish P03/06-LDX 250 ml (443.298) · 1 sealing W02/04 250 ml (443.301) · 1 microfibre polishing cloth MW-C (317.098) · 1 carrying case L-BOXX® 238 (414.093) · 1 case insert (437.093)

Range of Products 2018



XC 3401 VRG
Positive-drive orbital polisher
Order no. 322.008

Max. polishing pad diameter 160 mm
Velcro backing pad Ø 140 mm
No load speed 160-480 rpm
Orbit 8 mm
Orbit rate, no load 3200-9600 opm
Power input 1010 watt
Power output 590 watt
Cable length 4,0 m
Weight 2,6 kg




Standard Equipment:
1 bail handle (333.565) ·
1 special velcro backing pad, 140 Ø
(342.637)



XC 3401 VRG P-Set
Positive-drive orbital polisher in set
Order no. 334.081

Max. polishing pad diameter 160 mm
Velcro backing pad Ø 140 mm
No load speed 160-480 rpm
Orbit 8 mm
Orbit rate, no load 3200-9600 opm
Power input 1010 watt
Power output 590 watt
Cable length 4,0 m
Weight 2,6 kg



Standard Equipment:
1 bail handle (333.565) ·
1 special velcro backing pad, 140 Ø
(342.637) ·
1 polishing sponge PS-O 160 (434.329) ·
1 polishing sponge PSX-G 160 (434.280) ·
1 polish P03/06-LDX 250 ml (443.298) ·
1 polish P05/05-LDX 250 ml (443.271) ·
1 microfibre polishing cloth MW-C
(317.098) ·
1 carrying bag (333.573)

Accessories for polishers

Accessories for polishing systems




Polish

Designation	Contents	QTY/ PKG	Order no.		
P 05/05-LDX	250 ml	1	443.271		
P 03/06-LDX	250 ml	1	443.298		



Sealing

Designation	Contents	QTY/ PKG	Order no.		
W 02/04	250 ml	1	443.301		



Microfibre polishing cloth, classic

Designation	Dimensions in mm	QTY/ PKG	Order no.		
MW-C	400 x 400	1	317.098		



Microfibre polishing cloth, premium

Designation	Dimensions in mm	QTY/ PKG	Order no.		
MW-P	400 x 400	1	376.531		



Velcro-backed pad with gearwheel

Designation	Dimensions in mm	QTY/ PKG	Order no.		
BP-M D115 XC	115 Ø	1	386.715		



Velcro-backed pad with gearwheel

Designation	Dimensions in mm	QTY/ PKG	Order no.		
BP-M D140 XC	140 Ø	1	342.637		



Velcro pad, cushioned M 14

Designation	Dimensions in mm	QTY/ PKG	Order no.		
BP-M D35 M14	35 Ø	1	446.254		
BP-M D75 M14	75 Ø	1	420.492		
BP-M D115 M14	115 Ø	1	240.311		
BP-M D125 M14	125 Ø	1	350.737		
BP-M D150 M14	150 Ø	1	350.745		



Adapter for BP-M D35 M14

Designation	Dimensions in mm	QTY/ PKG	Order no.		
BP-AD M14 I/M14 A	40	1	446.270		



Polishing sponge, yellow

Designation	Dimensions in mm	QTY/ PKG	Order no.		
PSF-Y 220	220 Ø x 20	1	256.908		



Special velcro pad, cushioned

Designation	Dimensions in mm	QTY/ PKG	Order no.		
BP-M D75 XFE 7-12	75 Ø	1	454.141		
BP-M D125 XFE/XCE	125 Ø	1	442.445		
BP-M D150 XFE/XCE	150 Ø	1	437.077		



Polishing sponge, white

Designation	Dimensions in mm	QTY/ PKG	Order no.		
PSF-W 220	220 Ø x 30	1	256.909		



Polishing sponge

Designation	Dimensions in mm	QTY/ PKG	Order no.		
PSX-G 40 VE2	40 Ø x 25	2	442.631		
PSX-G 80 VE2	80 Ø x 25	2	434.264		
PSX-G 140	135 Ø x 25	1	434.272		
PSX-G 160	160 Ø x 25	1	434.280		
PSX-G 200	200 Ø x 25	1	434.299		



Microfibre polishing pad

Designation	Dimensions in mm	QTY/ PKG	Order no.		
MC-PT 160	160 Ø x 10	1	434.434		



Polishing sponge

Designation	Dimensions in mm	QTY/ PKG	Order no.		
PS-V 40 VE2	40 Ø x 25	2	442.658		
PS-V 80 VE2	80 Ø x 25	2	434.442		
PS-V 140	135 Ø x 25	1	434.450		
PS-V 160	160 Ø x 25	1	434.469		
PS-V 200	200 Ø x 25	1	436.410		



Velcro backed, classic

Designation	Dimensions in mm	QTY/ PKG	Order no.		
TW-C 150	150 Ø	1	342.521		
TW-C 200	200 Ø	1	350.265		



Polishing sponge

Designation	Dimensions in mm	QTY/ PKG	Order no.		
PS-O 40 VE2	40 Ø x 25	2	442.666		
PS-O 80 VE2	80 Ø x 25	2	434.302		
PS-O 140	135 Ø x 25	1	434.310		
PS-O 160	160 Ø x 25	1	434.329		
PS-O 200	200 Ø x 25	1	434.337		



Polishing lambswool, premium

Designation	Dimensions in mm	QTY/ PKG	Order no.		
TW-PT 80	80 Ø	1	420.484		
TW-PT 140	140 Ø	1	376.515		
TW-PT 160	160 Ø	1	376.523		



Polishing sponge

Designation	Dimensions in mm	QTY/ PKG	Order no.		
PS-R 40 VE2	40 Ø x 25	2	442.674		
PS-R 80 VE2	80 Ø x 25	2	434.345		
PS-R 140	135 Ø x 25	1	434.353		
PS-R 160	160 Ø x 25	1	434.361		
PS-R 200	200 Ø x 25	1	434.426		



Polishing fleece

Designation	Dimensions in mm	QTY/ PKG	Order no.		
WF-C 230	230 Ø	1	398.632		



Polishing sponge

Designation	Dimensions in mm	QTY/ PKG	Order no.		
PUK-R 130	130 Ø	1	442.682		




Flexible backing pad

Designation	Dimensions in mm	QTY/ PKG	Order no.		
BP D175 WH	175 Ø	1	123.862		

Range of Products 2018

Accessories for universal polishing



Backed fleece

Dimensions in mm	QTY/ PKG	Order no.		
125 Ø	1	122.726		
175 Ø	1	122.734		



Spare fleece

Dimensions in mm	QTY/ PKG	Order no.		
125 Ø	1	122.742		
175 Ø	1	122.750		



Buffing wheel mount, M 14

Dimensions in mm	QTY/ PKG	Order no.		
60	1	123.803		



SoftVib side handle

Designation	Type	QTY/ PKG	Order no.		
GS-M M8 SV	M 8	1	325.376		



Carrying bag for polisher

Designation	QTY/ PKG	Order no.		
TB-L 460x260x300	1	333.573		



Carrying case L-BOXX®

Designation	External dimensions L x W x H	Internal dimensions L x W x H	Weight	QTY/ PKG	Order no.		
TK-L 136	442 x 357 x 151 mm	378 x 311 x 107 mm	2,2 kg	1	414.085		
TK-L 238	442 x 357 x 253 mm	378 x 306 x 209 mm	2,8 kg	1	414.093		


Case insert

Designation	QTY/ PKG	Order no.		
TKE PE14	1	444.375		
TKE PE 150 18.0 EC	1	459.534		
TKE XFE 7-12/PE 8-4	1	446.963		
TKE XFE/XCE	1	437.093		
TC XFE 18.0 EC	1	459.526		

Stone working



LE 12-3 100 WET
1150 watt wet stone polisher with variable speed, plug for isolating transformer, 115 mm
Order no. 368.660




Max. polishing pad diameter 115 mm
No load speed 1200-3700 rpm
Power input 1150 watt
Power output 700 watt
Tool fixture M 14
Size (L x H) 350 x 140 mm
Connecting hose with quick coupling 2 m
Cable length 5,0 m
Weight 2,4 kg

Standard Equipment:
1 bail handle (368.709) ·
1 hook-and-loop cable ties (364.169)



LE 12-3 100 WET, PRCD
1150 watt wet stone polisher with variable speed, with GFCI circuit breaker, 115 mm
Order no. 378.461




Max. polishing pad diameter 115 mm
No load speed 1200-3700 rpm
Power input 1150 watt
Power output 700 watt
Tool fixture M 14
Size (L x H) 350 x 140 mm
Connecting hose with quick coupling 2 m
Cable length 4,0 m
Weight 2,4 kg

Standard Equipment:
1 bail handle (368.709) ·
1 hook-and-loop cable ties (364.169)



L 12-3 100 WET
1150 watt wet stone polisher with plug for isolating transformer, 115 mm
Order no. 375.675




Max. polishing pad diameter 115 mm
No load speed 3700 rpm
Power input 1150 watt
Power output 700 watt
Tool fixture M 14
Size (L x H) 350 x 140 mm
Connecting hose with quick coupling 2 m
Cable length 5,0 m
Weight 2,4 kg

Standard Equipment:
1 bail handle (368.709) ·
1 hook-and-loop cable ties (364.169)



L 12-3 100 WET, PRCD
1150 watt wet stone polisher with
GFCI circuit breaker, 115 mm
Order no. 378.488

Max. polishing pad diameter 115 mm
No load speed 3700 rpm
Power input 1150 watt
Power output 700 watt
Tool fixture M 14
Size (L x H) 350 x 140 mm
Connecting hose with
quick coupling 2 m
Cable length 4,0 m
Weight 2,4 kg



Standard Equipment:
1 bail handle (368.709) ·
1 hook-and-loop cable ties (364.169)



LW 802 VR
1800 watt wet stone polisher with plug
for isolating transformer, 130 mm
Order no. 258.597

Max. polishing pad diameter 130 mm
No load speed 800-2400 rpm
Power input 1800 watt
Power output 1200 watt
Tool fixture M 14
Cable length 4,0 m
Weight 4,3 kg



Standard Equipment:
1 bail handle (263.397) ·
1 open-ended wrench SW 17 (106.461)



LW 1202
1600 watt wet stone polisher with plug
for isolating transformer, 130 mm
Order no. 276.375

Max. polishing pad diameter 130 mm
No load speed 1750 rpm
Power input 1600 watt
Power output 1040 watt
Tool fixture M 14
Cable length 4,0 m
Weight 5,1 kg




Standard Equipment:
1 bail handle (258.639) ·
1 open-ended wrench SW 17 (106.461)



LW 1202 S
1600 watt wet stone polisher with
GFCI circuit breaker, 130 mm
Order no. 289.000

Max. polishing pad diameter 130 mm
No load speed 1750 rpm
Power input 1600 watt
Power output 1040 watt
Tool fixture M 14
Cable length 4,0 m
Weight 5,1 kg



Standard Equipment:
1 bail handle (258.639) ·
1 open-ended wrench SW 17 (106.461)




TT 2000
Isolating transformer
Order no. 373.370

Max. performance up to 45 min.
non-stop operation 2000 VA
Size (W x L x H) 200 x 200 x 270 mm
Primary voltage 230 V
Secondary voltage 230 V
Weight 15,8 kg



BHW 1549 VR
Blind hole drill with integrated water
feed with GFCI circuit breaker
Order no. 299.197

Power input 1200 watt
Power output 700 watt
Speed under load 3000-9000 rpm
No load speed 3500-10000 rpm
Tool fixture M 14
Diamond drill Ø 5-10 mm
Cable length 4,0 m
Weight 3,3 kg




Standard Equipment:
1 bail handle (236.934) ·
1 open-ended wrench SW 17 (106.461) ·
1 splash guard (255.171) ·
1 metal carrying case (273.686)



LST 803 VR
Bushhammer for stairs and large
surfaces
Order no. 259.639

No load speed 800-2400 rpm
Power input 1800 watt
Power output 1200 watt
Working width 55-130 mm
Cable length 4,0 m
Weight 7,2 kg



Standard Equipment:
1 stop, complete (259.193) ·
1 carbide tipped complete 140 Ø
(261.654) ·
1 hexagon socket wrench, SW 5
(115.460) ·
1 extraction adapter (340.790) ·
Vacuum hose extension (296.953)



LST 1503 VR
Bushhammer for stairs
Order no. 259.229

No load speed 800-2400 rpm
Power input 1200 watt
Power output 700 watt
Working width 40-92 mm
Cable length 4,0 m
Weight 5,9 kg



Standard Equipment:
1 stop, complete (259.193) ·
1 carbide tipped complete 100 Ø
(261.653) ·
1 hexagon socket wrench, SW 5
(115.460) ·
1 extraction adapter (340.790) ·
Vacuum hose extension (296.953)

Range of Products 2018



LK 602 VR
Polisher with grip hood
Order no. 258.580

Max. polishing pad diameter 220 mm
Max. back-up pad diameter 175 mm
No load speed 800-2400 rpm
Power input 1500 watt
Power output 1000 watt
Tool fixture M 14
Cable length 4,0 m
Weight 3,5 kg



Standard Equipment:
1 side handle (252.721)



LG 1704 VR
1500 watt grinder without extraction,
178 mm
Order no. 293.768

Max. disc diameter 178 mm
No load speed 1400-4200 rpm
Power input 1500 watt
Power output 1000 watt
Cable length 4,0 m
Weight 2,7 kg



Standard Equipment:
1 side handle (252.721)



CS 60 WET
Diamond stone cutter for wet cuts,
mitre cuts up to 45 °, with GFCI circuit
breaker
Order no. 374.016

Power input 1400 watt
Power output 840 watt
No load speed 6200 rpm
Diamond cutting disc Ø /
arbor (inside Ø) 170 / 22,2 mm
Cutting depth /
with guide rail 60 / 54 mm
Mitre cuttings 0-45°
Depth of cut - mitre cut 5-44 mm
Depth of cut - mitre cut
with guide rail 0-38 mm
Cable length 4,0 m
Weight 4,5 kg



Standard Equipment:
1 diamond cutting disc with segmented
cutting edge (347.515) ·
1 wrench for saw blade change
(359.343) ·
1 parallel guide fence (350.613) ·
1 carrying case L-BOXX® 238 (414.093) ·
1 case insert (436.771)

Accessories for stone working

Accessories for wet polishing



Velcro pad, soft

Dimensions in mm	QTY/ PKG	Order no.		
100 Ø	1	253.814		



Dia-Jet velcro diamond discs wet (single)

Dimensions in mm	Grit	colour	QTY/ PKG	Order no.		
100 Ø	grit 60	dark green	1	253.815		
100 Ø	grit 100	blue	1	253.816		
100 Ø	grit 200	light green	1	253.817		
100 Ø	grit 400	yellow	1	253.818		
100 Ø	grit 800	orange	1	253.819		
100 Ø	grit 1500	red	1	253.820		
100 Ø	grit 3000	brown	1	253.821		
100 Ø	grit 10000	black	1	253.822		




Dia-Jet velcro diamond discs wet in a set

Dimensions in mm	Grit	QTY/ PKG	Order no.		
100 Ø	grit 100 - 1500	5	253.823		



Adapter plate

Dimensions in mm	QTY/ PKG	Order no.		
100 Ø	1	126.098		



Grinding rings

Dimensions in mm	Grit	QTY/ PKG	Order no.		
100 Ø	F 30	1	126.144		
100 Ø	F 60	1	126.152		
100 Ø	F 120	1	126.160		

Wet drills for the BHW 1549 VR, BED 18 and BED 69



Diamond hollow hole drill bits

Designation	Diameter in mm	Length in mm	QTY/ PKG	Order no.		
DD-WET D5x30 M14	5	30	1	386.359		
DD-WET D6x30 M14	6	30	1	386.367		
DD-WET D8x30 M14	8	30	1	386.375		
DD-WET D10x30 M14	10	30	1	386.383		



Hollow diamond drill bit

D in mm	T in mm	L in mm	QTY/ PKG	Order no.		
6 Ø	58	88	1	315.052		
8 Ø	73	103	1	315.060		
10 Ø	88	118	1	315.079		
12 Ø	98	128	1	315.087		
14 Ø	113	143	1	315.095		

Accessories BED 18



Suction hose

QTY/ PKG	Order no.		
1	255.506		



Suction hose

QTY/ PKG	Order no.		
1	255.505		



Vacuum hose connection


QTY/ PKG	Order no.		
1	255.507		

Accessories for dry grinding



Velcro backing pad Ø 115, Bowl

Dimensions in mm	QTY/ PKG	Order no.		
115 Ø	1	366.609		



Velcro pad, cushioned M 14

Designation	Dimensions in mm	QTY/ PKG	Order no.		
BP-M D115 M14	115 Ø	1	240.311		
BP-M D125 M14	125 Ø	1	350.737		
BP-M D150 M14	150 Ø	1	350.745		



Diamond sanding pad


Designation	Dimensions in mm	Grit	QTY/ PKG	Order no.		
DP 50 DRY D115	115 Ø	50	1	386.197		
DP 100 DRY D115	115 Ø	100	1	386.200		
DP 200 DRY D115	115 Ø	200	1	386.219		
DP 400 DRY D115	115 Ø	400	1	386.227		
DP 800 DRY D115	115 Ø	800	1	386.235		
DP 1500 DRY D115	115 Ø	1500	1	386.243		
DP 3000 DRY D115	115 Ø	3000	1	386.251		
DP 10000 DRY D115	115 Ø	10000	1	386.278		



Diamond sanding pad

Designation	Dimensions in mm	Grit	QTY/ PKG	Order no.		
DP 50 DRY D125	125 Ø	50	1	382.817		
DP 100 DRY D125	125 Ø	100	1	382.825		
DP 200 DRY D125	125 Ø	200	1	382.833		
DP 400 DRY D125	125 Ø	400	1	382.841		
DP 800 DRY D125	125 Ø	800	1	382.868		
DP 1500 DRY D125	125 Ø	1500	1	382.876		
DP 3000 DRY D125	125 Ø	3000	1	382.884		
DP 10000 DRY D125	125 Ø	10000	1	382.965		

Range of Products 2018



Diamond sanding pad

Designation	Dimensions in mm	Grit	QTY/ PKG	Order no.		
DP 30 DRY D150	150 Ø	30	1	418.951		
DP 50 DRY D150	150 Ø	50	1	418.978		
DP 100 DRY D150	150 Ø	100	1	418.986		
DP 200 DRY D150	150 Ø	200	1	418.994		
DP 400 DRY D150	150 Ø	400	1	419.001		
DP 800 DRY D150	150 Ø	800	1	419.028		
DP 1500 DRY D150	150 Ø	1500	1	419.036		
DP 3000 DRY D150	150 Ø	3000	1	419.044		
DP 10000 DRY D150	150 Ø	10000	1	419.052		

Accessories LST 803 VR, LST 1503 VR


Replacement carbide wheels

	QTY/ PKG	Order no.		
	6	259.833		
	8	259.834		

Replacement bearing block with 2 carbide wheels


	QTY/ PKG	Order no.		
	1	260.576		

Accessories for CSW 4161, CS 60 WET diamond stone saws



Diamond cutting disc

Designation	Dimensions in mm	QTY/ PKG	Order no.		
Turbo-F-Jet D170x22,2	170 Ø x 22,2	1	386.189		




Diamond cutting disc

Dimensions in mm	QTY/ PKG	Order no.		
170 Ø x 22,2	1	347.515		



Diamond cutting disc

Dimensions in mm	QTY/ PKG	Order no.		
170 Ø x 22,2	1	367.214		



Guide rail GRS

Designation	Length in mm	QTY/ PKG	Order no.		
GRS 80	800	1	353.280		
GRS 160	1600	1	359.351		



Connector for guide rail GRS

Designation	QTY/ PKG	Order no.		
GRS-V	1	353.272		



End caps

	QTY/ PKG	Order no.		
	2	364.967		



Antislip profile

	QTY/ PKG	Order no.		
	6,8 m	366.854		



Anti-splinter guard

	QTY/ PKG	Order no.		
	3,4 m	366.846		



Carrying case L-BOXX®

Designation	External dimensions L x W x H	Internal dimensions L x W x H	Weight	QTY/ PKG	Order no.		
TK-L 238	442 x 357 x 253 mm	378 x 306 x 209 mm	2,8 kg	1	414.093		

Case insert

Designation	QTY/ PKG	Order no.		
TKE CS 60 Wet II	1	436.771		

Carrying case system L-BOXX®



Carrying case L-BOXX®




Designation	External dimensions L x W x H	Internal dimensions L x W x H	Weight	QTY/ PKG	Order no.		
TK-L 102	442 x 357 x 117 mm	378 x 313 x 71 mm	2,1 kg	1	414.077		
TK-L 136	442 x 357 x 151 mm	378 x 311 x 107 mm	2,2 kg	1	414.085		
TK-L 238	442 x 357 x 253 mm	378 x 306 x 209 mm	2,8 kg	1	414.093		
TK-L 374	442 x 357 x 389 mm	378 x 296 x 345 mm	3,4 kg	1	414.107		




Trolley L-BOXX®

Designation	Dimensions in mm	Weight	QTY/ PKG	Order no.		
RW L-BOXX	646 x 492 x 182	3,8 kg	1	419.400		



Grid foam insert L-BOXX®

Designation	QTY/ PKG	Order no.		
TKE-RS 136	1	419.370		



Anti slip insert L-BOXX®

Designation	Size (W x L x H)	QTY/ PKG	Order no.		
TKE-AR 238	378 x 306 x 3 mm	1	419.389		
TKE-AR 374	378 x 296 x 3 mm	1	419.397		

FLEX-Elektrowerkzeuge GmbH
Bahnhofstraße 15
71711 Steinheim
Germany
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

Subject to technical alterations.

Your FLEX retailer: